

| No. | Part Number | Description                                                                        | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1   | MS27466     | MIL-DTL-38999 Series I, Wall Mounting Receptacle                                   | MIL-DTL-38999           | MS27466                |
| 2   | MS27467     | MIL-DTL-38999 Series I, Straight Plug, Grounded                                    | MIL-DTL-38999           | MS27467                |
| 3   | MS27468     | MIL-DTL-38999 Series I, Jam Nut Receptacle                                         | MIL-DTL-38999           | MS27468                |
| 4   | MS27469     | MIL-DTL-38999 Series I, Wall Mounting Receptacle, Solder Cup Contacts              | MIL-DTL-38999           | MS27469                |
| 5   | MS27470     | MIL-DTL-38999 Series I, Jam Nut Receptacle Solder Cup Contacts                     | MIL-DTL-38999           | MS27470                |
| 6   | MS27471     | MIL-DTL-38999 Series I, Solder Mounting, Solder Cup Contacts                       | MIL-DTL-38999           | MS27471                |
| 7   | MS27496     | MIL-DTL-38999 Series I, Box Mounting Receptacle                                    | MIL-DTL-38999           | MS27496                |
| 8   | MS27505     | MIL-DTL-38999 Series I, Box Mounting Receptacle, Back Mount                        | MIL-DTL-38999           | MS27505                |
| 9   | MS27515     | MIL-DTL-38999 Series I, Wall Mounting Receptacle, Back Mount (Inactive, Use 27656) | MIL-DTL-38999           | MS27515                |
| 10  | MS27652     | MIL-DTL-38999 Series I, Wall Mounting Receptacle (Inactive, Use 27466)             | MIL-DTL-38999           | MS27652                |
| 11  | MS27653     | MIL-DTL-38999 Series I, Straight Plug (Inactive, Use 27467)                        | MIL-DTL-38999           | MS27653                |
| 12  | MS27654     | MIL-DTL-38999 Series I, Wall Mounting Receptacle, Back Panel (Inactive, Use 27656) | MIL-DTL-38999           | MS27654                |
| 13  | MS27656     | MIL-DTL-38999 Series I, Wall Mounting Receptacle, Back Mount                       | MIL-DTL-38999           | MS27656                |
| 14  | MS27661     | MIL-DTL-38999 Series I, Plug, Lanyard Release                                      | MIL-DTL-38999           | MS27661                |
| 15  | MS27662     | MIL-DTL-38999 Series I, Thru-Bulkhead Mounting                                     | MIL-DTL-38999           | MS27662                |
| 16  | MS27472     | MIL-DTL-38999 Series II, Wall Mounting Receptacle                                  | MIL-DTL-38999           | MS27472                |
| 17  | MS27473     | MIL-DTL-38999 Series II, Straight Plug                                             | MIL-DTL-38999           | MS27473                |
| 18  | MS27474     | MIL-DTL-38999 Series II, Jam Nut Receptacle                                        | MIL-DTL-38999           | MS27474                |
| 19  | MS27475     | MIL-DTL-38999 Series II, Wall Mounting Receptacle, Solder Cup Contacts             | MIL-DTL-38999           | MS27475                |
| 20  | MS27476     | MIL-DTL-38999 Series II, Box Mounting Receptacle, Solder Cup Contacts              | MIL-DTL-38999           | MS27476                |
| 21  | MS27477     | MIL-DTL-38999 Series II, Jam Nut Receptacle, Solder Cup Contacts                   | MIL-DTL-38999           | MS27477                |
| 22  | MS27478     | MIL-DTL-38999 Series II, Solder Mounting Receptacle, Solder Cup Contacts           | MIL-DTL-38999           | MS27478                |
| 23  | MS27479     | MIL-DTL-38999 Series II, Wall Mounting Receptacle                                  | MIL-DTL-38999           | MS27479                |
| 24  | MS27480     | MIL-DTL-38999 Series II, Straight Plug                                             | MIL-DTL-38999           | MS27480                |
| 25  | MS27481     | MIL-DTL-38999 Series II, Jam Nut Receptacle                                        | MIL-DTL-38999           | MS27481                |
| 26  | MS27484     | MIL-DTL-38999 Series II, Straight Plug, Grounded                                   | MIL-DTL-38999           | MS27484                |
| 27  | MS27497     | MIL-DTL-38999 Series II, Wall Mounting Receptacle, Back Mount                      | MIL-DTL-38999           | MS27497                |
| 28  | MS27499     | MIL-DTL-38999 Series II, Box Mounting Receptacle                                   | MIL-DTL-38999           | MS27499                |
| 29  | MS27500     | MIL-DTL-38999 Series II, 90 Degree Elbow                                           | MIL-DTL-38999           | MS27500                |
| 30  | MS27504     | MIL-DTL-38999 Series II, Box Mounting Receptacle                                   | MIL-DTL-38999           | MS27504                |

| No. | Part Number | Description                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 31  | MS27508     | MIL-DTL-38999 Series II, Box Mounting Receptacle, Back Mount                                                                                    | MIL-DTL-38999           | MS27508                |
| 32  | MS27513     | MIL-DTL-38999 Series II, Box Mounting Receptacle, Back Mount                                                                                    | MIL-DTL-38999           | MS27513                |
| 33  | D38999/9    | MIL-DTL-38999 Series I, Wall Mounting Receptacle, Dummy Stowage                                                                                 | MIL-DTL-38999           | MIL-DTL-38999/9        |
| 34  | D38999/10   | MIL-DTL-38999 Series II, Wall Mounting Receptacle, Dummy Stowage                                                                                | MIL-DTL-38999           | MIL-DTL-38999/10       |
| 35  | D38999/20   | MIL-DTL-38999 Series III, Wall Mounting Receptacle                                                                                              | MIL-DTL-38999           | MIL-DTL-38999/20       |
| 36  | D38999/21   | MIL-DTL-38999 Series III, Box Mounting Flange, Solder Cup Contacts                                                                              | MIL-DTL-38999           | MIL-DTL-38999/21       |
| 37  | D38999/22   | MIL-DTL-38999 Series III, Wall Mounting Receptacle, Dummy Stowage                                                                               | MIL-DTL-38999           | MIL-DTL-38999/22       |
| 38  | D38999/23   | MIL-DTL-38999 Series III, Jam Nut Receptacle, Solder Cup Contacts                                                                               | MIL-DTL-38999           | MIL-DTL-38999/23       |
| 39  | D38999/24   | MIL-DTL-38999 Series III, Jam Nut Receptacle                                                                                                    | MIL-DTL-38999           | MIL-DTL-38999/24       |
| 40  | D38999/25   | MIL-DTL-38999 Series III, Solder Mounting Receptacle, Solder Cup Contacts                                                                       | MIL-DTL-38999           | MIL-DTL-38999/25       |
| 41  | D38999/26   | MIL-DTL-38999 Series III, Straight Plug, Grounded                                                                                               | MIL-DTL-38999           | MIL-DTL-38999/26       |
| 42  | D38999/27   | MIL-DTL-38999 Series III, Weld Mounting Receptacle, Solder Cup Contacts                                                                         | MIL-DTL-38999           | MIL-DTL-38999/27       |
| 43  | D38999/28   | Connectors, Electrical, Circular, Nut, Hexagon, Connector Mounting, Series III and IV, Metric                                                   | MIL-DTL-38999           | MIL-DTL-38999/28       |
| 44  | D38999/29   | MIL-DTL-38999 Series III, Receptacle, Lanyard Release, Removable Crimp Contacts, Pins                                                           | MIL-DTL-38999           | MIL-DTL-38999/29       |
| 45  | D38999/30   | MIL-DTL-38999 Series III, Receptacle, Lanyard Release, Removable Crimp Contacts, Sockets                                                        | MIL-DTL-38999           | MIL-DTL-38999/30       |
| 46  | D38999/31   | MIL-DTL-38999 Series III, Receptacle, Lanyard Release, Shell Size 25, Removable Crimp Contacts, Pins                                            | MIL-DTL-38999           | MIL-DTL-38999/31       |
| 47  | D38999/32   | Connector, Electrical Circular, Cover, Protective, Plug, Series III, Metric                                                                     | MIL-DTL-38999           | MIL-DTL-38999/32       |
| 48  | D38999/33   | Connector, Electrical Circular, Cover, Protective, Receptacle, Series III, Metric                                                               | MIL-DTL-38999           | MIL-DTL-38999/33       |
| 49  | D38999/34   | MIL-DTL-38999 Series III, Breakaway, Jam Nut Receptacle, Shell Size 25, Removable Crimp Contacts, Sockets                                       | MIL-DTL-38999           | MIL-DTL-38999/34       |
| 50  | D38999/35   | MIL-DTL-38999 Series III, Breakaway, Wall Mounting Receptacle, Shell Size 25, Removable Crimp Contacts, Sockets                                 | MIL-DTL-38999           | MIL-DTL-38999/35       |
| 51  | D38999/36   | Connectors, Electrical, Circular, Threaded, Plug, Lanyard Release, Fail-Safe, Removable Crimp Contacts, Pins, Shell Size 25, Series III, Metric | MIL-DTL-38999           | MIL-DTL-38999/36       |
| 52  | D38999/40   | MIL-DTL-38999 Series IV, Wall Mounting Receptacle, Removable Crimp Contacts                                                                     | MIL-DTL-38999           | MIL-DTL-38999/40       |
| 53  | D38999/41   | MIL-DTL-38999 Series IV, Box Mounting Receptacle, Breech Coupling, Solder Cup Contacts                                                          | MIL-DTL-38999           | MIL-DTL-38999/41       |
| 54  | D38999/42   | MIL-DTL-38999 Series IV, Box Mounting Receptacle, Breech Coupling, Removable Crimp Contacts                                                     | MIL-DTL-38999           | MIL-DTL-38999/42       |

| No. | Part Number | Description                                                                                                             | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 55  | D38999/43   | MIL-DTL-38999 Series IV, Jam Nut Receptacle, Breech Coupling, Solder Cup Contacts                                       | MIL-DTL-38999           | MIL-DTL-38999/43       |
| 56  | D38999/44   | MIL-DTL-38999 Series IV, Jam Nut Receptacle, Breech Coupling, Removable Crimp Contacts                                  | MIL-DTL-38999           | MIL-DTL-38999/44       |
| 57  | D38999/45   | MIL-DTL-38999 Series IV, Solder Mounting Receptacle, Breech Coupling, Removable Crimp Contacts                          | MIL-DTL-38999           | MIL-DTL-38999/45       |
| 58  | D38999/46   | MIL-DTL-38999 Series IV, Straight Plug, Grounding, Breech Coupling, Removable Crimp Contacts                            | MIL-DTL-38999           | MIL-DTL-38999/46       |
| 59  | D38999/47   | MIL-DTL-38999 Series IV, Straight Plug, Breech Coupling, Removable Crimp Contacts                                       | MIL-DTL-38999           | MIL-DTL-38999/47       |
| 60  | D38999/48   | MIL-DTL-38999 Series IV, Weld Mounting Receptacle, Breech Coupling, Solder Cup Contacts                                 | MIL-DTL-38999           | MIL-DTL-38999/48       |
| 61  | D38999/49   | MIL-DTL-38999 Series IV, In-Line Receptacle, Breech Coupling, Removable Crimp Contacts                                  | MIL-DTL-38999           | MIL-DTL-38999/49       |
| 62  | D38999/50   | MIL-DTL-38999 Series IV, Wall Mounting Receptacle, Breech Coupling, Dummy Stowage                                       | MIL-DTL-38999           | MIL-DTL-38999/50       |
| 63  | M24308/1    | MIL-DTL-24308 Panel Mount Connector, Class D & G, Socket, Solder Cup Contact                                            | MIL-DTL-24308           | MIL-DTL-24308/1        |
| 64  | M24308/2    | MIL-DTL-24308 Panel Mount Connector, Class D & G, Socket, Crimp Contact                                                 | MIL-DTL-24308           | MIL-DTL-24308/2        |
| 65  | M24308/3    | MIL-DTL-24308 Panel Mount Connector, Class D & G, Pin, Solder Cup Contact                                               | MIL-DTL-24308           | MIL-DTL-24308/3        |
| 66  | M24308/4    | MIL-DTL-24308 Panel Mount Connector, Class D & G, Pin, Crimp Contact                                                    | MIL-DTL-24308           | MIL-DTL-24308/4        |
| 67  | M24308/5    | MIL-DTL-24308 Panel Mount Connector, Class M & N, Socket, Solder Cup Contact                                            | MIL-DTL-24308           | MIL-DTL-24308/5        |
| 68  | M24308/6    | MIL-DTL-24308 Panel Mount Connector, Class M & N, Socket, Crimp Contact                                                 | MIL-DTL-24308           | MIL-DTL-24308/6        |
| 69  | M24308/7    | MIL-DTL-24308 Panel Mount Connector, Class M & N, Pin, Solder Cup Contact                                               | MIL-DTL-24308           | MIL-DTL-24308/7        |
| 70  | M24308/8    | MIL-DTL-24308 Panel Mount Connector, Class M & N, Pin, Crimp Contact                                                    | MIL-DTL-24308           | MIL-DTL-24308/8        |
| 71  | M24308/9    | MIL-DTL-24308 Panel Mount Connector, Class H & K, Pin, Solder Cup Contact, Eyelet                                       | MIL-DTL-24308           | MIL-DTL-24308/9        |
| 72  | M24308/23   | MIL-DTL-24308 PCB Mount Connector, Class G, Socket, Straight, Right Angle                                               | MIL-DTL-24308           | MIL-DTL-24308/23       |
| 73  | M24308/24   | MIL-DTL-24308 PCB Mount Connector, Class G, Pin, Straight, Right Angle                                                  | MIL-DTL-24308           | MIL-DTL-24308/24       |
| 74  | M24308/25   | Male Screw Lock                                                                                                         | MIL-DTL-24308           | MIL-DTL-24308/25       |
| 75  | M24308/26   | Female Screw Lock                                                                                                       | MIL-DTL-24308           | MIL-DTL-24308/26       |
| 76  | M24308/27   | MIL-DTL-24308 Panel Mount Connector, Class G, Socket, IDC                                                               | MIL-DTL-24308           | MIL-DTL-24308/27       |
| 77  | M24308/28   | MIL-DTL-24308 Panel Mount Connector, Class G, Pin, IDC                                                                  | MIL-DTL-24308           | MIL-DTL-24308/28       |
| 78  | M83513/1    | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Pin Contacts, Class M, Solder Type          | MIL-DTL-83513           | MIL-DTL-83513/1        |
| 79  | M83513/2    | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Socket Contacts, Class M, Solder Type | MIL-DTL-83513           | MIL-DTL-83153/2        |

| No. | Part Number | Description                                                                                                                                                                                      | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 80  | M83513/3    | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Pin Contacts, Class M, Crimp Type                                                                                    | MIL-DTL-83513           | MIL-DTL-83513/3        |
| 81  | M83513/4    | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Socket Contacts, Class M, Crimp Type                                                                           | MIL-DTL-83513           | MIL-DTL-83153/4        |
| 82  | M83513/5    | Connectors, Electrical, Rectangular, Microminiature, Mounting Hardware                                                                                                                           | MIL-DTL-83513           | MIL-DTL-83515/5        |
| 83  | M83513/6    | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Pin Contacts, Class P, Solder Type                                                                                   | MIL-DTL-83513           | MIL-DTL-83515/6        |
| 84  | M83513/7    | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Socket Contacts, Class P, Solder Type                                                                          | MIL-DTL-83513           | MIL-DTL-83515/7        |
| 85  | M83513/8    | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Pin Contacts, Class P, Crimp Type                                                                                    | MIL-DTL-83513           | MIL-DTL-83515/8        |
| 86  | M83513/9    | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Socket Contacts, Class P, Crimp Type                                                                           | MIL-DTL-83513           | MIL-DTL-83515/9        |
| 87  | M83513/10   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 2 Row, Solder Type, Narrow Profile, 9 through 37 Contacts, Printed Circuit Board          | MIL-DTL-83513           | MIL-DTL-83515/10       |
| 88  | M83513/11   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 3 Row, Solder Type, Narrow Profile, 51 Contacts, Printed Circuit Board                    | MIL-DTL-83513           | MIL-DTL-83515/11       |
| 89  | M83513/12   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 4 Row, Solder Type, Narrow Profile, 100 Contacts, Printed Circuit Board                   | MIL-DTL-83513           | MIL-DTL-83515/12       |
| 90  | M83513/13   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Socket Contacts, 2 Row, Solder Type, Narrow Profile, 9 Through 37 Contacts, Printed Circuit Board | MIL-DTL-83513           | MIL-DTL-83515/13       |
| 91  | M83513/14   | ectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Socket Contacts, 3 Row, Solder Type, Narrow Profile, 51 Contacts, Printed Circuit Board               | MIL-DTL-83513           | MIL-DTL-83515/14       |
| 92  | M83513/15   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Sockets Contacts, 4 Row, Solder Type, Narrow Profile, 100 Contacts, Printed Circuit Board         | MIL-DTL-83513           | MIL-DTL-83515/15       |

| No. | Part Number | Description                                                                                                                                                                                        | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 93  | M83513/16   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 2 Row, Solder Type, Standard Profile, 9 Through 37 Contacts, Printed Circuit Board          | MIL-DTL-83513           | MIL-DTL-83515/16       |
| 94  | M83513/17   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 3 Row, Solder Type, Standard Profile, 51 Contacts, Printed Circuit Board                    | MIL-DTL-83513           | MIL-DTL-83515/17       |
| 95  | M83513/18   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Right Angle, Pin Contacts, 4 Row, Solder Type, Standard Profile, 100 Contacts, Printed Circuit Board                   | MIL-DTL-83513           | MIL-DTL-83515/18       |
| 96  | M83513/19   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Socket Contacts, 2 Row, Solder Type, Standard Profile, 9 Through 37 Contacts, Printed Circuit Board | MIL-DTL-83513           | MIL-DTL-83515/19       |
| 97  | M83513/20   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Socket Contacts, 3 Row, Solder Type, Standard Profile, 51 Contacts, Printed Circuit Board           | MIL-DTL-83513           | MIL-DTL-83515/20       |
| 98  | M83513/21   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Right Angle, Socket Contacts, 4 Row, Solder Type, Standard Profile, 100 Contacts, Printed Circuit Board          | MIL-DTL-83513           | MIL-DTL-83515/21       |
| 99  | M83153/22   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 2 Row, Solder Type, 9 Through 37 Contacts, Printed Circuit Board                               | MIL-DTL-83513           | MIL-DTL-83153/22       |
| 100 | M83513/23   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 3 Row, Solder Type, 51 Contacts, Printed Circuit Board                                         | MIL-DTL-83513           | MIL-DTL-83513/23       |
| 101 | M83513/24   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 4 Row, Solder Type, 100 Contacts, Printed Circuit Board                                        | MIL-DTL-83513           | MIL-DTL-83513/24       |
| 102 | M83513/25   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 2 Row, Solder Type, 9 Through 37 Contacts, Printed Circuit Board                      | MIL-DTL-83513           | MIL-DTL-83513/25       |
| 103 | M83153/26   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 3 Row, Solder Type, 51 Contacts, Printed Circuit Board                                | MIL-DTL-83513           | MIL-DTL-83153/26       |
| 104 | M83513/27   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 4 Row, Solder Type, 100 Contacts, Printed Circuit Board                               | MIL-DTL-83513           | MIL-DTL-83513/27       |

| No. | Part Number | Description                                                                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 105 | M83153/28   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 2 Row, Solder Type, Standard Profile, 9 Through 37 Contacts, Printed Circuit Board          | MIL-DTL-83513           | MIL-DTL-83153/28       |
| 106 | M83513/29   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 3 Row, Solder Type, Standard Profile, 51 Contacts, Printed Circuit Board                    | MIL-DTL-83513           | MIL-DTL-83513/29       |
| 107 | M83153/30   | Connectors, Electrical, Rectangular, Plug, Microminiature, Polarized Shell, Straight, Pin Contacts, 4 Row, Solder Type, Standard Profile, 100 Contacts, Printed Circuit Board                   | MIL-DTL-83513           | MIL-DTL-83153/30       |
| 108 | M83153/31   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 2 Row, Solder Type, Standard Profile, 9 through 37 Contacts, Printed Circuit Board | MIL-DTL-83513           | MIL-DTL-83153/31       |
| 109 | M83153/32   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 3 Row, Solder Type, Standard Profile, 51 Contacts, Printed Circuit Board           | MIL-DTL-83513           | MIL-DTL-83153/32       |
| 110 | M83153/33   | Connectors, Electrical, Rectangular, Receptacle, Microminiature, Polarized Shell, Straight, Socket Contacts, 4 Row, Solder Type, Standard Profile, 100 Contacts, Printed Circuit Board          | MIL-DTL-83513           | MIL-DTL-83153/33       |
| 111 | MS3100      | Connector, Receptacle, Electric, Cable Connecting, Solder Contacts, AN Type                                                                                                                     | SAE-AS-50151            | SAE-AS31001            |
| 112 | MS3400      | Connector, Receptacle, Electric, Wall Mounting, Front Release, Crimp Contact, AN Type                                                                                                           | SAE-AS-50151            | SAE-AS34001            |
| 113 | MS3450      | Connectors, Receptacle, Electric, Wall Mounting, Rear Release, Crimp Contact, AN Type                                                                                                           | SAE-AS-50151            | SAE-AS34501            |
| 114 | MS3101      | Connector, Receptacle, Electric, Cable Connecting, Solder Contacts, AN Type                                                                                                                     | SAE-AS-50151            | SAE-AS31011            |
| 115 | MS3401      | Connectors, Receptacle, Electric, Cable Connecting, Front Release, Crimp Contact, AN Type                                                                                                       | SAE-AS-50151            | SAE-AS34011            |
| 116 | MS3451      | Connectors, Receptacle, Electric, Cable Connecting, Rear Release, Crimp Contact, AN Type                                                                                                        | SAE-AS-50151            | SAE-AS34511            |
| 117 | MS3102      | Connector, Receptacle, Electric, Box Mounting, Solder Contacts, AN Type                                                                                                                         | SAE-AS-50151            | SAE-AS31021            |
| 118 | MS3402      | Connector, Receptacle, Electric, Box Mounting, Front Release, Crimp Contact, AN Type With                                                                                                       | SAE-AS-50151            | SAE-AS34021            |
| 119 | MS3452      | Connector, Receptacle, Electric, Box Mounting, Rear Release, Crimp Contact, AN Type With                                                                                                        | SAE-AS-50151            | SAE-AS34521            |
| 120 | MS3404      | Connectors, Receptacle, Electric, Jam Nut Mounting, Front Release, Crimp Contact, AN Type                                                                                                       | SAE-AS-50151            | SAE-AS34041            |
| 121 | MS3412      | Connectors, Receptacle, Electric, Wall Mounting, Front Release, Crimp Contact, AN Type - With Accessory Threads                                                                                 | SAE-AS-50151            | SAE-AS34121            |

| No. | Part Number | Description                                                                                                                                                          | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 122 | MS3454      | Connectors, Receptacle, Electrical, Jam Nut Mounting, Rear Release Crimp Contact, AN Type                                                                            | SAE-AS-50151            | SAE-AS34541            |
| 123 | MS3106      | Connector, Plug, Electric, Straight, Solder Contacts, AN Type                                                                                                        | SAE-AS-50151            | SAE-AS31061            |
| 124 | MS3406      | Connectors, Plug Electric, Front Release, Crimp Contact, An Type                                                                                                     | SAE-AS-50151            | SAE-AS34061            |
| 125 | MS3409      | Connectors, Plug, Electric, 45 Degrees Assembly, Crimp Contact, AN Type                                                                                              | SAE-AS-50151            | SAE-AS34091            |
| 126 | MS3456      | Connectors, Plug, Electrical, Rear Release, Crimp Contact, AN Type                                                                                                   | SAE-AS-50151            | SAE-AS34561            |
| 127 | MS3107      | Connector Plug, Electric, Quick Disconnect                                                                                                                           | SAE-AS-50151            | SAE-AS31071            |
| 128 | MS3507      | Connector, Plug, Electric, Solder Contact, Quick Disconnect, Utility                                                                                                 | SAE-AS-50151            | SAE-AS35071            |
| 129 | MS3108      | Connectors, Plug, Electric, Solder Contact, 90 Degree, AN Type                                                                                                       | SAE-AS-50151            | SAE-AS31081            |
| 130 | MS3408      | Connectors, Plug, Electric, 90 Degree Assembly, Crimp Contact, AN Type                                                                                               | SAE-AS-50151            | SAE-AS34081            |
| 131 | MS3103      | Connector, Receptacle, Electric, Potting Seal, Solder Contacts, AN Type                                                                                              | SAE-AS-50151            | SAE-AS31031            |
| 132 | MS25183     | Connector, Plug, Electric, Potting Seal, Solder Contact, AN Type                                                                                                     | SAE-AS-50151            | SAE-AS25183            |
| 133 | MS3459      | Connector, Plug, Electrical, Self-Locking, Coupling nut, Rear Release, Crimp Contact, AN Type                                                                        | SAE-AS-50151            | SAE-AS3459             |
| 134 | M83723/16   | Connector, Electrical, Backshell, with Heat-Shrinkable Strain-Relief, Boot (Straight or Right Angle), Bayonet-Coupling, Series I and III                             | MIL-DTL-83723           | MIL-DTL-83723/16       |
| 135 | M83723/17   | Connectors Electrical, (Circular, Environment Resisting), Receptacle, (Cable Connecting, Threaded Coupling, Crimp Socket Contacts), (Series II, Classes A, G, and R) | MIL-DTL-83723           | MIL-DTL-83723/17       |
| 136 | M83723/18   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Cable connecting, Threaded Coupling, Crimp Pin Contacts), (Series II, Classes A, G, and R)   | MIL-DTL-83723           | MIL-DTL-83723/18       |
| 137 | M83723/19   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Wall Mount, Threaded Coupling, Crimp Socket Contacts), (Series II, Classes A, G, K, and R)   | MIL-DTL-83723           | MIL-DTL-83723/19       |
| 138 | M83723/20   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Wall Mount, Threaded Coupling, Crimp Pin Contacts), (Series II, Classes A, G, K, and R)      | MIL-DTL-83723           | MIL-DTL-83723/20       |
| 139 | M83723/21   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Box Mount, Threaded Coupling, Crimp Socket Contacts), (Series II, Classes A, G, and R)       | MIL-DTL-83723           | MIL-DTL-83723/21       |
| 140 | M83723/22   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Box Mount, Threaded Coupling, Crimp Pin Contacts), (Series II, Classes A, G, and R)          | MIL-DTL-83723           | MIL-DTL-83723/22       |
| 141 | M83723/23   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Crimp Socket Contacts), (Series II, Classes A, G, K, and R)                     | MIL-DTL-83723           | MIL-DTL-83723/23       |

| No. | Part Number | Description                                                                                                                                                                                         | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 142 | M83723/24   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Crimp Pin Contacts), Series II, Classes A, G, K, and R                                                         | MIL-DTL-83723           | MIL-DTL-83723/24       |
| 143 | M83723/27   | CONNECTORS, ELECTRICAL, BACKSHELL, WITH HEAT-SHRINKABLE STRAIN-RELIEF BOOT (STRAIGHT AND RIGHT ANGLE), THREADED COUPLING                                                                            | MIL-DTL-83723           | MIL-DTL-83723/27       |
| 144 | M83723/35   | CONNECTOR, ELECTRIC, BACKSHELL, STRAIGHT W/O STRAIN RELIEF, AND WITH MECHANICAL STRAIN RELIEF, STRAIGHT OR RIGHT ANGLE THREADED COUPLING SERIES II                                                  | MIL-DTL-83723           | MIL-DTL-83723/35       |
| 145 | M83723/50   | CONNECTOR, ELECTRICAL, CIRCULAR, ENVIRONMENT RESISTING, BACKSHELL, STRAIGHT, 90..., AND 45... WITH DIELECTRIC STRAIN RELIEF, FOR SERIES 2 CONNECTORS                                                | MIL-DTL-83723           | MIL-DTL-83723/50       |
| 146 | M83723/59   | Connectors, Electrical, (Circular, Environment Resisting), Protective Covers, Plugs, (for MIL-DTL-26500 and MIL-DTL-83723, Series III, Classes A, M, R, T, W, and Z)                                | MIL-DTL-83723           | MIL-DTL-83723/59       |
| 147 | M83723/60   | Connectors, Electrical, (Circular, Environment Resisting), Protective Covers, Receptacles, (for MIL-DTL-26500 and MIL-DTL-83723, Series III, Classes A, M, R, T, W and Z)                           | MIL-DTL-83723           | MIL-DTL-83723/60       |
| 148 | M83723/61   | Connectors, Electrical, (Circular, Environment Resisting), Dummy Connectors, Receptacles, (for MIL-DTL-26500 and MIL-DTL-83723, Series III, Classes A, M, R, T, W and Z)                            | MIL-DTL-83723           | MIL-DTL-83723/61       |
| 149 | M83723/65   | Connector, Electric, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Bayonet Coupling, Pin Contact), (Series III, Class H)                                                       | MIL-DTL-83723           | MIL-DTL-83723/65       |
| 150 | M83723/66   | Connectors, Electrical, (Circular, Environment Resisting), Plug, Threaded Coupling, (Push-Pull, Quick-Disconnect without Lanyard), Crimp Pin Contact, Series III, Classes A, G, M, R, T, W and Z    | MIL-DTL-83723           | MIL-DTL-83723/66       |
| 151 | M83723/67   | Connectors, Electrical, (Circular, Environment Resisting), Plug, Threaded Coupling, (Push-Pull, Quick-Disconnect without Lanyard), Crimp Socket Contact, Series III, Classes A, G, M, R, T, W and Z | MIL-DTL-83723           | MIL-DTL-83723/67       |
| 152 | M83723/68   | Connectors, Electrical, (Circular, Environment Resisting), Plug, Threaded Coupling, (Push-Pull, Quick-Disconnect with Lanyard), Crimp Pin Contact, Series III, Classes A, G, M, R, T, W and Z       | MIL-DTL-83723           | MIL-DTL-83723/68       |
| 153 | M83723/69   | Connectors, Electrical, (Circular, Environment Resisting), Plug, Threaded Coupling, (Push-Pull, Quick-Disconnect with Lanyard), Crimp Socket Contact, Series III, Classes A, G, M, R, T, W and Z    | MIL-DTL-83723           | MIL-DTL-83723/69       |
| 154 | M83723/70   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle Adapter (Push-Pull), Quick-Disconnect, Series III, Classes A, G, M, R, T, W and Z                                             | MIL-DTL-83723           | MIL-DTL-83723/70       |

| No. | Part Number | Description                                                                                                                                                                                | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 155 | M83723/71   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Flange Mount, Bayonet Coupling, Crimp Socket Contact), Series III, Classes A, G, M, R, T, W and Z                  | MIL-DTL-83723           | MIL-DTL-83723/71       |
| 156 | M83723/72   | Connector, Electric, (Circular, Environment Resisting), Receptacle, (Flange Mount, Bayonet Coupling, Crimp Pin Contact) (Series III, Classes A, G, M, R, T, W and Z)                       | MIL-DTL-83723           | MIL-DTL-83723/72       |
| 157 | M83723/73   | Connector, Electric, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Bayonet Coupling, Crimp Socket Contact) (Series III, Classes A, G, M, R, T, W and Z)               | MIL-DTL-83723           | MIL-DTL-83723/73       |
| 158 | M83723/74   | Connectors, Electric, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Bayonet Coupling, Crimp Pin Contact), (Series III, Classes A, G, M, R, T, W and Z)                | MIL-DTL-83723           | MIL-DTL-83723/74       |
| 159 | M83723/75   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Bayonet Coupling, Crimp Socket Contact), (Series III, Classes A, G, K, M, R, T, W and Z)                                 | MIL-DTL-83723           | MIL-DTL-83723/75       |
| 160 | M83723/76   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Bayonet Coupling, Crimp Pin Contact), (Series III, Classes A, G, M, R, T, W and Z)                                       | MIL-DTL-83723           | MIL-DTL-83723/76       |
| 161 | M83723/77   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (RFI, Bayonet Coupling, Crimp Socket Contact), (Series III, Classes G, M, R, T, W and Z)                                  | MIL-DTL-83723           | MIL-DTL-83723/77       |
| 162 | M83723/78   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (RFI, Bayonet Coupling, Crimp Pin Contact), (Series III, Classes G, M, R, T, W, and Z)                                    | MIL-DTL-83723           | MIL-DTL-83723/78       |
| 163 | M83723/79   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Flange Mount, Bayonet Coupling, Solder Pin Contact), (Series III, Classes H, J, L, P and Y)                        | MIL-DTL-83723           | MIL-DTL-83723/79       |
| 164 | M83723/80   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Solder or Weld Flange Mount, Bayonet Coupling, Solder Pin Contact), (Series III, Classes H, J, L, P and Y)         | MIL-DTL-83723           | MIL-DTL-83723/80       |
| 165 | M83723/81   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Bayonet Coupling, Solder Pin Contact), (Series III, Classes H, J, L, P and Y)                   | MIL-DTL-83723           | MIL-DTL-83723/81       |
| 166 | M83723/82   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Flange Mount, Threaded Coupling, Crimp Socket Contact), (Series III, Classes A, G, K, M, N, R, S, T, W and Z)      | MIL-DTL-83723           | MIL-DTL-83723/82       |
| 167 | M83723/83   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Flange Mount, Threaded Coupling, Crimp Pin Contact), (Series III, CLASSES A, G, K, M, N, R, S, T, W and Z)         | MIL-DTL-83723           | MIL-DTL-83723/83       |
| 168 | M83723/84   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Threaded Coupling, Crimp Socket Contact), (Series III, Classes A, G, K, M, N, R, S, T, W and Z) | MIL-DTL-83723           | MIL-DTL-83723/84       |

| No. | Part Number | Description                                                                                                                                                                             | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 169 | M83723/85   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Threaded Coupling, Crimp Pin Contact), (Series III, Classes A, G, K, M, N, R, S, T, W and Z) | MIL-DTL-83723           | MIL-DTL-83723/85       |
| 170 | M83723/86   | Connectors, Electrical, (Circular Environment Resisting), Plug, (Threaded Coupling, Crimp Socket Contact), (Series III, Classes A, G, K, M, R, T, W, and Z)                             | MIL-DTL-83723           | MIL-DTL-83723/86       |
| 171 | M83723/87   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Crimp Pin Contact),(Series III, Classes A, G, K, M, R, T, W and Z)                                 | MIL-DTL-83723           | MIL-DTL-83723/87       |
| 172 | M83723/88   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Flange Mount, Threaded Coupling, Solder Pin Contact), (Series III, Classes H, J, L, N, P and Y)                 | MIL-DTL-83723           | MIL-DTL-83723/88       |
| 173 | M83723/89   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Threaded Coupling, Solder Pin Contact), (Series III, Classes H, J, L, N, P, and Y)           | MIL-DTL-83723           | MIL-DTL-83723/89       |
| 174 | M83723/90   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Solder or Weld Flange Mount, Threaded Coupling, Solder Pin Contact), (Series III, Classes H, J, L, N, P and Y)  | MIL-DTL-83723           | MIL-DTL-83723/90       |
| 175 | M83723/91   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (RFI, Threaded Coupling, Crimp Socket Contact), (Series III, Classes G, M, R, T, W and Z)                              | MIL-DTL-83723           | MIL-DTL-83723/91       |
| 176 | M83723/92   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (RFI, Threaded Coupling, Crimp Pin Contact), (Series III, Classes G, M, R, T, W, and Z)                                | MIL-DTL-83723           | MIL-DTL-83723/92       |
| 177 | M83723/93   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Solder or Weld Flange Mount, Bayonet Coupling, Straight Pin Contact),(Series III, Classes H and Y)              | MIL-DTL-83723           | MIL-DTL-83723/93       |
| 178 | M83723/94   | Connectors, Electrical, (Circular, Environment Resisting), Receptacle, (Single Hole Mount, Bayonet Coupling, Straight Pin Contact), (Series III, Classes H, and Y)                      | MIL-DTL-83723           | MIL-DTL-83723/94       |
| 179 | M83723/95   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Self-Locking, Crimp Socket Contact), (Series III, Classes A, G, K, M, R, T, W and Z)               | MIL-DTL-83723           | MIL-DTL-83723/95       |
| 180 | M83723/96   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Self-Locking, Crimp Pin Contact), (Series III, Classes A, G, K, M, R, T, W and Z)                  | MIL-DTL-83723           | MIL-DTL-83723/96       |
| 181 | M83723/97   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Self-Locking, R.F.I. Grounding, Crimp Socket Contacts), (Series III, Classes N and S Firewall)     | MIL-DTL-83723           | MIL-DTL-83723/97       |
| 182 | M83723/98   | Connectors, Electrical, (Circular, Environment Resisting), Plug, (Threaded Coupling, Self-Locking, R.F.I. Grounding, Crimp Pin Contact), (Series III, Classes N and S Firewall)         | MIL-DTL-83723           | MIL-DTL-83723/98       |

| No. | Part Number | Description                                                                                                                                                                  | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 183 | M83733/1    | Connector, Electrical, Receptacle, Miniature, Rectangular Type, Rack to Panel, Standard Hole Mounting, Environment Resisting, 200 Degrees C                                  | MIL-DTL-83733           | MIL-DTL-83733/1        |
| 184 | M83733/2    | Connector, Electrical, Plug, Socket Contact, Miniature, Rectangular Type, Rack to Panel, with Guide Pins and Spring Mounting, Environment Resisting, 200 Degrees C           | MIL-DTL-83733           | MIL-DTL-83733/2        |
| 185 | M83733/3    | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, with Guide Sockets, Environment Resisting, 200 Degrees C                        | MIL-DTL-83733           | MIL-DTL-83733/3        |
| 186 | M83733/4    | Connector, Electrical, Plug, Socket Contact, Miniature, Rectangular Type, Rack to Panel, with Captive Springs, Environment Resisting, 200 Degrees C                          | MIL-DTL-83733           | MIL-DTL-83733/4        |
| 187 | M83733/5    | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Bushing Mounting, Environment Resisting, 200 Degrees C                          | MIL-DTL-83733           | MIL-DTL-83733/5        |
| 188 | M83733/6    | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Clinch Nut Mounting, Environment Resisting, 200 Degrees C                       | MIL-DTL-83733           | MIL-DTL-83733/6        |
| 189 | M83733/7    | Connectors, Electrical, Receptacle, Socket Contact, Miniature, Rectangular Type, Rack to Panel, with Guide Sockets and Spring Mounting, Environment Resisting, 200 Degrees C | MIL-DTL-83733           | MIL-DTL-83733/7        |
| 190 | M83733/8    | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, with Guide Pins, Environment Resisting, 200 Degrees C                           | MIL-DTL-83733           | MIL-DTL-83733/8        |
| 191 | M83733/9    | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Staggered Standard Hole Mounting, Environment Resisting, 200 Degrees C          | MIL-DTL-83733           | MIL-DTL-83733/9        |
| 192 | M83733/10   | Connector, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Staggered Bushing Mounting, Environment Resisting, 200 Degrees C                 | MIL-DTL-83733           | MIL-DTL-83733/10       |
| 193 | M83733/11   | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Staggered Clinch Nut Mounting, Environment Resisting, 200 Degrees C             | MIL-DTL-83733           | MIL-DTL-83733/11       |
| 194 | M83733/12   | Connectors, Electrical, Receptacle, Pin Contact, Miniature, Rectangular Type, Rack to Panel, Staggered Spring Mounting, Environment Resisting, 200 Degrees C                 | MIL-DTL-83733           | MIL-DTL-83733/12       |
| 195 | M83733/17   | Connectors, Rack and Panel, Spring Loaded, Mounting Assembly                                                                                                                 | MIL-DTL-83733           | MIL-DTL-83733/17       |
| 196 | M83517/1    | Connector, Receptacle, Electrical, Coaxial, Radio Frequency, Strip or Microstrip Transmission Line, Series SMA (Socket Contact, Flange Mounted Tab Terminal)                 | MIL-DTL-83517           | MIL-DTL-83517/1        |
| 197 | M83517/2    | CONNECTOR, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, FLANGE MOUNTED TAB TERMINAL)                    | MIL-DTL-83517           | MIL-DTL-83517/2        |

| No. | Part Number | Description                                                                                                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 198 | M83517/3    | CONNECTOR, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, FLANGE MOUNTED SLOTTED TAB TERMINAL)                                                                                  | MIL-DTL-83517           | MIL-DTL-83517/3        |
| 199 | M83517/4    | CONNECTOR, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, FLANGE MOUNTED EXTENDED DIELECTRIC)                                                                                   | MIL-DTL-83517           | MIL-DTL-83517/4        |
| 200 | M83517/5    | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, FLANGE MOUNTED EXTENDED DIELECTRIC)                                                                                     | MIL-DTL-83517           | MIL-DTL-83517/5        |
| 201 | M83517/6    | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, 8 HOLE SURFACE LAUNCH)                                                                                               | MIL-DTL-83517           | MIL-DTL-83517/6        |
| 202 | M83517/7    | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, 8 HOLE SURFACE LAUNCH)                                                                                                  | MIL-DTL-83517           | MIL-DTL-83517/7        |
| 203 | M83517/8    | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, 8 HOLE SURFACE LAUNCH RIGHT ANGLE)                                                                                   | MIL-DTL-83517           | MIL-DTL-83517/8        |
| 204 | M83517/9    | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, END LAUNCH)                                                                                                          | MIL-DTL-83517           | MIL-DTL-83517/9        |
| 205 | M83517/10   | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, FLANGE MOUNTED)                                                                                                      | MIL-DTL-83517           | MIL-DTL-83517/10       |
| 206 | M83517/11   | CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, FLANGE MOUNTED)                                                                                                         | MIL-DTL-83517           | MIL-DTL-83517/11       |
| 207 | M83517/12   | Connector, Receptacle, Electrical, Coaxial, Radio Frequency, Stripline, Series BMA (Pin Contact), Flange Mounted, Extended Dielectric                                                                                                                 | MIL-DTL-83517           | MIL-DTL-83517/12       |
| 208 | M83517/13   | Connector, Receptacle, Electrical, Coaxial, Radio Frequency, Series SMA, (Socket Contact) Feedthrough, Hermetic                                                                                                                                       | MIL-DTL-83517           | MIL-DTL-83517/13       |
| 209 | M83503/6    | Connectors, Electrical, Flat Cable, Nonenvironmental Dual-in-Line Plug for Terminating round Conductors on .050 Centers for Mating with Standard Dip Sockets, .100 X .300 Contact Spacing .100 X .400 Contact Spacing and .100 X .600 Contact Spacing | MIL-DTL-83503           | MIL-DTL-83503/6        |

| No. | Part Number | Description                                                                                                                                                                 | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 210 | M83503/7    | Connector, Electrical, Flat Cable, Nonenvironmental Plug with Dual Polarization, Round Conductor, Insulation Displacing Non-Removable Socket Contacts (.100 X .100 Spacing) | MIL-DTL-83503           | MIL-DTL-83503/7        |
| 211 | M83503/20   | Connectors, Electrical, Flat Cable, Nonenvironmental Header, Right Angle (.100 Spacing) with Polarizing Feature Solderless Wrappost or PWB Termination                      | MIL-DTL-83503           | MIL-DTL-83503/20       |
| 212 | M83503/21   | Connectors, Electrical, Flat Cable, Nonenvironmental, Header, Straight thru (.100 Inch Spacing) with Polarizing Feature Solderless Wrappost or PWB Termination              | MIL-DTL-83503           | MIL-DTL-83503/21       |
| 213 | M83503/22   | CONNECTORS, ELECTRICAL, FLAT CABLE, NONENVIRONMENTAL, SOCKET INSULATION DISPLACEMENT                                                                                        | MIL-DTL-83503           | MIL-DTL-83503/22       |
| 214 | M83503/23   | Connectors, Electrical, Flat Cable, Nonenvironmental Printed Wiring Board Solder Transition for Terminating Round Conductors on .050 Inch Centers                           | MIL-DTL-83503           | MIL-DTL-83503/23       |
| 215 | M83503/24   | Connectors, Electrical, Flat Cable, Nonenvironmental Four Wall Header, Right Angle (.100 Spacing) with Polarizing Feature Solderless Wrappost or PWB Termination            | MIL-DTL-83503           | MIL-DTL-83503/24       |
| 216 | M83503/25   | Connectors, Electrical, Flat Cable, Nonenvironmental Four Wall Header, Straight thru (.100 Spacing) with Polarizing Feature, Solderless Wrappost or PWB Termination         | MIL-DTL-83503           | MIL-DTL-83503/25       |
| 217 | M55302/1    | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Printed Wiring Boards (.150 Spacing)                                          | MIL-DTL-55302           | MIL-DTL-55302/1        |
| 218 | M55302/2    | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Printed Wiring Boards (.150 Spacing)                               | MIL-DTL-55302           | MIL-DTL-55302/2        |
| 219 | M55302/4    | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Multilayered Printed Wiring Boards (.100 Spacing)                             | MIL-DTL-55302           | MIL-DTL-55302/4        |
| 220 | M55302/5    | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing)                           | MIL-DTL-55302           | MIL-DTL-55302/5        |
| 221 | M55302/6    | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, SOCKET CONTACTS, STRAIGHT-THRU, FOR MULTILAYERED PRINTED WIRING BOARDS (.100 SPACING)                  | MIL-DTL-55302           | MIL-DTL-55302/6        |
| 222 | M55302/7    | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Multilayered Printed Wiring Boards (.100 Spacing)                             | MIL-DTL-55302           | MIL-DTL-55302/7        |
| 223 | M55302/8    | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing)                  | MIL-DTL-55302           | MIL-DTL-55302/8        |

| No. | Part Number | Description                                                                                                                                                               | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 224 | M55302/16   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PIN, RIGHT-ANGLE, FOR PRINTED WIRING BOARDS (.200 SPACING)                                                       | MIL-DTL-55302           | MIL-DTL-55302/16       |
| 225 | M55302/17   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: SOCKET, STRAIGHT-THRU, FOR PRINTED WIRING BOARDS (.200 SPACING)                                                  | MIL-DTL-55302           | MIL-DTL-55302/17       |
| 226 | M55302/18   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PIN, STRAIGHT-THRU, FOR PRINTED WIRING BOARDS (.200 SPACING)                                                     | MIL-DTL-55302           | MIL-DTL-55302/18       |
| 227 | M55302/19   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, PIN CONTACTS RIGHT-ANGLE, 41 COMPOSITE CONTACT, FOR PRINTED WIRING BOARDS (.150 SPACING)                   | MIL-DTL-55302           | MIL-DTL-55302/19       |
| 228 | M55302/20   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, SOCKET CONTACT, STRAIGHT-THRU, FOR PRINTED WIRING BOARDS (.150 SPACING)                              | MIL-DTL-55302           | MIL-DTL-55302/20       |
| 229 | M55302/21   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, PIN CONTACT, RIGHT-ANGLE, 92 COMPOSITE CONTACT, FOR MULTILAYERED PRINTED WIRING BOARDS (.100 SPACING)      | MIL-DTL-55302           | MIL-DTL-55302/21       |
| 230 | M55302/22   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, SOCKET CONTACTS, STRAIGHT-THRU, FOR MULTILAYERED PRINTED WIRING BOARDS (.100 SPACING)                | MIL-DTL-55302           | MIL-DTL-55302/22       |
| 231 | M55302/23   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, DECADE INCREMENT 10 THRU 120, 150, 160 AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING) | MIL-DTL-55302           | MIL-DTL-55302/23       |
| 232 | M55302/24   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, DECADE INCREMENT 10 THRU 110, CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING)            | MIL-DTL-55302           | MIL-DTL-55302/24       |
| 233 | M55302/25   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, 120, 150, 160, AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING)                   | MIL-DTL-55302           | MIL-DTL-55302/25       |
| 234 | M55302/26   | Connectors, Printed Circuit Subassembly and Accessories: Plug, 30 thru 140 Contact Positions, for Printed Wiring Boards (.100 Sq. Grid)                                   | MIL-DTL-55302           | MIL-DTL-55302/26       |
| 235 | M55302/27   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, 30 thru 140 Contact Positions, for Printed Wiring Boards (.100 Sq. Grid)                             | MIL-DTL-55302           | MIL-DTL-55302/27       |
| 236 | M55302/31   | Connectors, Printed Circuit Subassembly and Accessories: Keying Accessories                                                                                               | MIL-DTL-55302           | MIL-DTL-55302/31       |

| No. | Part Number | Description                                                                                                                                                                                                                                   | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 237 | M55302/38   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Electrical, Polarized Shell, Male, .100 Inch Contact Spacing Pin Terminal                                                                                                      | MIL-DTL-55302           | MIL-DTL-55302/38       |
| 238 | M55302/42   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Electrical, Polarized Shell, Female, .100 Inch Contact Spacing, Removable Crimp Contacts                                                                                 | MIL-DTL-55302           | MIL-DTL-55302/42       |
| 239 | M55302/52   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, STRAIGHT-THRU, HERMAPHRODITIC CONTACT FOR PRINTED WIRING BOARDS (.100 SPACING)                                                                                           | MIL-DTL-55302           | MIL-DTL-55302/52       |
| 240 | M55302/53   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, RIGHT-ANGLE, HERMAPHRODITIC CONTACT FOR PRINTED WIRING BOARDS (.100 SPACING)                                                                                                   | MIL-DTL-55302           | MIL-DTL-55302/53       |
| 241 | M55302/54   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, STRAIGHT-THRU, HERMAPHRODITIC CONTACT FORPRINTED WIRING BOARDS (.100 SPACING)                                                                                                  | MIL-DTL-55302           | MIL-DTL-55302/54       |
| 242 | M55302/55   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing)       | MIL-DTL-55302           | MIL-DTL-55302/55       |
| 243 | M55302/56   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Pin Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing)    | MIL-DTL-55302           | MIL-DTL-55302/56       |
| 244 | M55302/57   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/57       |
| 245 | M55302/58   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/58       |
| 246 | M55302/59   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 90, 100 and 120 Contact Positions for Printed Wiring Boards (.100 Spacing)                                                                     | MIL-DTL-55302           | MIL-DTL-55302/59       |
| 247 | M55302/60   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 90, 100 and 120 Contact Positions (.100 Spacing)                                                                                      | MIL-DTL-55302           | MIL-DTL-55302/60       |
| 248 | M55302/61   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, and 66 for Printed Wiring Boards (.100 Spacing)      | MIL-DTL-55302           | MIL-DTL-55302/61       |

| No. | Part Number | Description                                                                                                                                                                                                                                   | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 249 | M55302/62   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/62       |
| 250 | M55302/63   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/63       |
| 251 | M55302/64   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/64       |
| 252 | M55302/65   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/65       |
| 253 | M55302/66   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/66       |
| 254 | M55302/67   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PIN, RIGHT ANGLE PLUG, ELECTRICAL, POLARIZED FOR PRINTED WIRING BOARDS (.090 SPACING)                                                                                                | MIL-DTL-55302           | MIL-DTL-55302/67       |
| 255 | M55302/68   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: SOCKET, RECEPTACLE, ELECTRICAL, POLARIZED (.090 SPACING) REMOVABLE CRIMP CONTACTS                                                                                                    | MIL-DTL-55302           | MIL-DTL-55302/68       |
| 256 | M55302/69   | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PIN PLUG, ELECTRICAL, POLARIZED (.090 SPACING) REMOVABLE CRIMP CONTACTS                                                                                                              | MIL-DTL-55302           | MIL-DTL-55302/69       |
| 257 | M55302/70   | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle Plug, Electrical, Polarized for Printed Wiring Boards (.100 Spacing)                                                                                                | MIL-DTL-55302           | MIL-DTL-55302/70       |
| 258 | M55302/71   | Connectors, Printed Circuit Subassembly and Accessories, Socket Receptacle, Electrical, Polarized Composite Contact (.100 Spacing)                                                                                                            | MIL-DTL-55302           | MIL-DTL-55302/71       |
| 259 | M55302/72   | Connectors, Printed Circuit Subassembly and Accessories: Socket Environmental Resistant, Receptacle, Electrical, Polarized (.150 Spacing), Removable Crimp Contacts                                                                           | MIL-DTL-55302           | MIL-DTL-55302/72       |
| 260 | M55302/73   | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, Environmental Resistant, Plug, Electrical, Polarized for Printed Wiring Boards (.150 Spacing)                                                                      | MIL-DTL-55302           | MIL-DTL-55302/73       |

| No. | Part Number | Description                                                                                                                                                                        | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 261 | M55302/74   | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, Plug, Electrical, Polarized for Printed Wiring Boards (.100 Spacing)                                    | MIL-DTL-55302           | MIL-DTL-55302/74       |
| 262 | M55302/75   | Connectors, Printed Circuit Subassembly and Accessories: Socket Receptacle, Electrical, Polarized (.100 Spacing), Removable Crimp Contacts                                         | MIL-DTL-55302           | MIL-DTL-55302/75       |
| 263 | M55302/76   | Connectors, Printed Circuit Subassembly and Accessories, Socket Straight-Thru, Polarized for Multilayered Printed Wiring Boards (.100 Spacing)                                     | MIL-DTL-55302           | MIL-DTL-55302/76       |
| 264 | M55302/77   | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, for Multilayered Printed Wiring Boards (.100 Spacing)                                                   | MIL-DTL-55302           | MIL-DTL-55302/77       |
| 265 | M55302/78   | Connectors, Printed Circuit Subassembly and Accessories: Key, Polarizing, Connectors, Electrical Printed Wiring Boards                                                             | MIL-DTL-55302           | MIL-DTL-55302/78       |
| 266 | M55302/82   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, 41, 66, 114 Contact Positions: for Printed Wiring Boards (.100 X .050 Offset Grid)           | MIL-DTL-55302           | MIL-DTL-55302/82       |
| 267 | M55302/83   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 41, 66, 114 Contact Positions: for Printed Wiring Boards (.100 X .050 Offset Grid)                    | MIL-DTL-55302           | MIL-DTL-55302/83       |
| 268 | M55302/84   | Connectors, Printed Circuit Subassembly and Accessories: Contacts - Crimp, Dip Solder Tail, Solder Turret, and Wirewrap                                                            | MIL-DTL-55302           | MIL-DTL-55302/84       |
| 269 | M55302/89   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Hermaphroditic Contacts (.100 Spacing)                                                                 | MIL-DTL-55302           | MIL-DTL-55302/89       |
| 270 | M55302/90   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Right Angle, Hermaphroditic Contact (.100 Inch Spacing)                                                       | MIL-DTL-55302           | MIL-DTL-55302/90       |
| 271 | M55302/91   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, Hermaphroditic Contacts (.100 Inch Spacing)                                                          | MIL-DTL-55302           | MIL-DTL-55302/91       |
| 272 | M55302/92   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight-thru, Hermaphroditic Contacts (.100 Inch Spacing)                                                    | MIL-DTL-55302           | MIL-DTL-55302/92       |
| 273 | M55302/93   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Insert (Insulator), Rectangular, Polarized, Removable Crimp Type, Hermaphroditic Contacts (.100 Inch Spacing)       | MIL-DTL-55302           | MIL-DTL-55302/93       |
| 274 | M55302/94   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Insert (Insulator), Rectangular, Polarized, Removable. Crimp Type Hermaphroditic Contacts (.100 Inch Spacing) | MIL-DTL-55302           | MIL-DTL-55302/94       |

| No. | Part Number | Description                                                                                                                                                                               | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 275 | M55302/95   | Connectors, Printed Circuit Subassembly and Accessories: Plug, Composite Wrappost, Hermaphroditic Contacts (.100 Inch Spacing)                                                            | MIL-DTL-55302           | MIL-DTL-55302/95       |
| 276 | M55302/96   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Wrappost (Removable) Hermaphroditic Contacts (.100 Inch Spacing)                                                     | MIL-DTL-55302           | MIL-DTL-55302/96       |
| 277 | M55302/97   | Connectors, Printed Circuit Subassembly and Accessories: Contacts, Hermaphroditic, Crimp Removable for Wire (Stranded)                                                                    | MIL-DTL-55302           | MIL-DTL-55302/97       |
| 278 | M55302/98   | Connectors, Printed Circuit Subassembly and Accessories: Contact, Wrappost Removable Type                                                                                                 | MIL-DTL-55302           | MIL-DTL-55302/98       |
| 279 | M55302/99   | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight Through, Hermaphroditic Contact, Wrappost Removable, for Printed Wiring Boards (.100 Inch Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/99       |
| 280 | M55302/100  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Hermaphroditic Contact, Wrappost Removable, For Printed Wiring Boards (.100 Inch Spacing) No S/S Document)    | MIL-DTL-55302           | MIL-DTL-55302/100      |
| 281 | M55302/101  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, Hermaphroditic Contact, Wrappost Removable, for Printed Wiring Boards (.100 Inch Spacing) (No S/S Document) | MIL-DTL-55302           | MIL-DTL-55302/101      |
| 282 | M55302/102  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight-Thru, Hermaphroditic Contact, Crimp Removable, for Printed Wiring Boards (.100 Inch Spacing)                | MIL-DTL-55302           | MIL-DTL-55302/102      |
| 283 | M55302/103  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Hermaphroditic Contact, Crimp Removable, for Printed Wiring Boards (.100 Inch Spacing)                        | MIL-DTL-55302           | MIL-DTL-55302/103      |
| 284 | M55302/104  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, Hermaphroditic Contact, Crimp Removable, for Printed Wiring Boards (.100 Inch Spacing)                      | MIL-DTL-55302           | MIL-DTL-55302/104      |
| 285 | M55302/107  | Connectors, Printed Circuit Subassembly and Accessories: Support Pin, for Connector Mounting Bracket                                                                                      | MIL-DTL-55302           | MIL-DTL-55302/107      |
| 286 | M55302/109  | Connectors, Electrical, Printed Wiring Board General Purpose Composite, Receptacle, Contact Spacing (.100) Single Row, Type C                                                             | MIL-DTL-55302           | MIL-DTL-55302/109      |
| 287 | M55302/110  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, 30 Thru 140 Contact Positions, For Printed Wiring Boards (.100 Sq. Grid)                                      | MIL-DTL-55302           | MIL-DTL-55302/110      |

| No. | Part Number | Description                                                                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 288 | M55302/111  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards, (.100 Spacing)                                                           | MIL-DTL-55302           | MIL-DTL-55302/111      |
| 289 | M55302/113  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, 30 thru 140 Contact Positions, Crimp Removable Contacts (.100 Sq. Grid)                                                                 | MIL-DTL-55302           | MIL-DTL-55302/113      |
| 290 | M55302/114  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, for Printed Circuit Boards and Solderless Wrap (.100 Inch Contact Spacing) 12, 16, 20, 28, 40, 60, 80, and 100 Contact Positions | MIL-DTL-55302           | MIL-DTL-55302/114      |
| 291 | M55302/115  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right-Angle, Pin Contacts, for Printed Circuit Boards, (.100 Inch Contact Spacing), 12, 16, 20, 28, 40, 60, 80, and 100 Contact Positions              | MIL-DTL-55302           | MIL-DTL-55302/115      |
| 292 | M55302/117  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, RIGHT ANGLE, DECADE INCREMENT 20 THROUGH 110 AND 128 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.050 SPACING)                                       | MIL-DTL-55302           | MIL-DTL-55302/117      |
| 293 | M55302/118  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, DECADE INCREMENT 20 THROUGH 110 AND 128 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.050 SPACING)                                                    | MIL-DTL-55302           | MIL-DTL-55302/118      |
| 294 | M55302/119  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Decade Increment 20 Through 110 and 128 Contact Positions, For Printed Wiring Boards (.050 Spacing)                                              | MIL-DTL-55302           | MIL-DTL-55302/119      |
| 295 | M55302/120  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 128 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing)                                                                     | MIL-DTL-55302           | MIL-DTL-55302/120      |
| 296 | M55302/121  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, 128 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing)                                                             | MIL-DTL-55302           | MIL-DTL-55302/121      |
| 297 | M55302/122  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 184 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing)                                                                     | MIL-DTL-55302           | MIL-DTL-55302/122      |
| 298 | M55302/123  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, 184 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing)                                                             | MIL-DTL-55302           | MIL-DTL-55302/123      |
| 299 | M55302/124  | Connectors, Printed Circuit Subassembly and Accessories: Keying Accessories                                                                                                                                           | MIL-DTL-55302           | MIL-DTL-55302/124      |
| 300 | M55302/125  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, 80 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.050 INCH SPACING)                                                                                    | MIL-DTL-55302           | MIL-DTL-55302/125      |

| No. | Part Number | Description                                                                                                                                                                      | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 301 | M55302/126  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, 80 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.050 INCH SPACING)                                         | MIL-DTL-55302           | MIL-DTL-55302/126      |
| 302 | M55302/127  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, SINGLE ROW, 2 THROUGH 65 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.062 , .093 , .125 ) (.100 SPACING)  | MIL-DTL-55302           | MIL-DTL-55302/127      |
| 303 | M55302/128  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, DOUBLE ROW, 4 THROUGH 130 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.062 , .093 , .125 ) (.100 SPACING) | MIL-DTL-55302           | MIL-DTL-55302/128      |
| 304 | M55302/130  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLES, 90 THROUGH 240 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SPACING)                                 | MIL-DTL-55302           | MIL-DTL-55302/130      |
| 305 | M55302/131  | Connectors, Plug, Electrical, Printed Circuit Subassembly and Accessories: Right Angle, Pin Contacts, 64 or 96 Contact Position for Printed Wiring Boards (.100 Spacing)         | MIL-DTL-55302           | MIL-DTL-55302/131      |
| 306 | M55302/132  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle Socket Contacts, Straight Thru, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing)    | MIL-DTL-55302           | MIL-DTL-55302/132      |
| 307 | M55302/133  | CONNECTORS, PLUG, ELECTRICAL, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RIGHT ANGLE, PIN CONTACTS, 32 OR 64 CONTACT POSITION FOR PRINTED WIRING BOARDS (.100 SPACING)         | MIL-DTL-55302           | MIL-DTL-55302/133      |
| 308 | M55302/134  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE SOCKET CONTACTS, STRAIGHT THRU 32 OR 64 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SPACING)          | MIL-DTL-55302           | MIL-DTL-55302/134      |
| 309 | M55302/138  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, PIN, 160 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SPACING)                                              | MIL-DTL-55302           | MIL-DTL-55302/138      |
| 310 | M55302/139  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLES, 90 THROUGH 240 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SPACING)                                 | MIL-DTL-55302           | MIL-DTL-55302/139      |
| 311 | M55302/140  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH PIN CONTACTS, 2 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                                    | MIL-DTL-55302           | MIL-DTL-55302/140      |
| 312 | M55302/141  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG WITH PIN CONTACTS, 3 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                                    | MIL-DTL-55302           | MIL-DTL-55302/141      |
| 313 | M55302/142  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE WITH SOCKET CONTACTS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                                          | MIL-DTL-55302           | MIL-DTL-55302/142      |

| No. | Part Number | Description                                                                                                                                                                                | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 314 | M55302/143  | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Socket Contacts, 3 Keying Guides, for Printed Wiring Boards (.100 Inch Spacing)                                   | MIL-DTL-55302           | MIL-DTL-55302/143      |
| 315 | M55302/144  | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Pin Contacts, 2 Female Keying Guides, 1.516 Inches Length, for Printed Wiring Boards (.100 Inch Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/144      |
| 316 | M55302/145  | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Pin Contacts, 2 Female Keying Guides, 2.114 Inches Length, for Printed Wiring Boards (.100 Inch Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/145      |
| 317 | M55302/146  | Connectors, Printed Circuit Subassembly and Receptacle with Pin Contacts, 2 Female Keying Guides, 2.717 Inches Length, for Printed Wiring Boards (.100 Inch Spacing)                       | MIL-DTL-55302           | MIL-DTL-55302/146      |
| 318 | M55302/147  | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Pin Contacts, 2 Female Keying Guides, 3.315 Inches Length, for Printed Wiring Boards (.100 Inch Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/147      |
| 319 | M55302/148  | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Pin Contacts, 2 Female Keying Guides, 3.917 Inches Length, for Printed Wiring Boards (.100 Inch Spacing)          | MIL-DTL-55302           | MIL-DTL-55302/148      |
| 320 | M55302/149  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH SOCKET CONTACTS, 1.516 INCHES LENGTH, 2 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                      | MIL-DTL-55302           | MIL-DTL-55302/149      |
| 321 | M55302/150  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH SOCKET CONTACTS, 2.114 INCHES LENGTH, 2 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                      | MIL-DTL-55302           | MIL-DTL-55302/150      |
| 322 | M55302/151  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH SOCKET CONTACTS, 2.717 INCHES LENGTH, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                                     | MIL-DTL-55302           | MIL-DTL-55302/151      |
| 323 | M55302/152  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH SOCKET CONTACTS, 3.315 INCHES LENGTH, 2 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                      | MIL-DTL-55302           | MIL-DTL-55302/152      |
| 324 | M55302/153  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG WITH SOCKET CONTACTS, 3.917 INCHES LENGTH, 2 KEYING PINS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)                      | MIL-DTL-55302           | MIL-DTL-55302/153      |
| 325 | M55302/155  | Connectors, Printed Circuit Subassembly and Accessories, Hood for Printed Wiring Boards                                                                                                    | MIL-DTL-55302           | MIL-DTL-55302/155      |
| 326 | M55302/156  | Connectors, Printed Circuit Subassembly and Accessories; Plug, Right Angle, Decade Increments 10 Through 120, 150, 160 and 180 Contact Positions, for Printed Wiring Boards (.075 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/156      |

| No. | Part Number | Description                                                                                                                                                                         | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 327 | M55302/157  | Connectors, Printed Circuit Subassembly and Accessories; {Plug, Straight Thru Contacts, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing)                   | MIL-DTL-55302           | MIL-DTL-55302/157      |
| 328 | M55302/158  | Connectors, Printed Circuit Subassembly and Accessories; Receptacle Socket Contacts, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing)                      | MIL-DTL-55302           | MIL-DTL-55302/158      |
| 329 | M55302/159  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, 17, 29, 33, 41, 53, AND 65 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC | MIL-DTL-55302           | MIL-DTL-55302/159      |
| 330 | M55302/160  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, 72, 84, 96, AND 120 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC        | MIL-DTL-55302           | MIL-DTL-55302/160      |
| 331 | M55302/161  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, 160 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC                        | MIL-DTL-55302           | MIL-DTL-55302/161      |
| 332 | M55302/162  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG, 17, 29, 33, 41, 53, AND 65 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC       | MIL-DTL-55302           | MIL-DTL-55302/162      |
| 333 | M55302/163  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG, 72, 84, 96, AND 120 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC              | MIL-DTL-55302           | MIL-DTL-55302/163      |
| 334 | M55302/164  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG AND/OR RECEPTACLE, 160 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC            | MIL-DTL-55302           | MIL-DTL-55302/164      |
| 335 | M55302/166  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: LOW MATING FORCE, MALE BRUSH, STRAIGHT-THROUGH, POLARIZED, FOR MULTILAYERED PRINTING WIRING BOARDS (.100 SPACING)          | MIL-DTL-55302           | MIL-DTL-55302/166      |
| 336 | M55302/167  | CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: LOW MATING FORCE, MALE BRUSH, STRAIGHT-THROUGH, POLARIZED, WITH WRAPPOST TERMINATION (.100 SPACING)                        | MIL-DTL-55302           | MIL-DTL-55302/167      |
| 337 | M55302/168  | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Male Brush, Right Angle, Polarized, for Multilayered Printed Wiring Boards (.100 Spacing)                | MIL-DTL-55302           | MIL-DTL-55302/168      |

| No. | Part Number | Description                                                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 338 | M55302/169  | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Female Brush, Straight-Through, Polarized, (.100 Spacing)                                            | MIL-DTL-55302           | MIL-DTL-55302/169      |
| 339 | M55302/170  | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Female Brush, Right Angle, Polarized, For Multilayered Printed Wiring Board (.100 Spacing)           | MIL-DTL-55302           | MIL-DTL-55302/170      |
| 340 | M55302/173  | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Pin Assemblies, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing)                      | MIL-DTL-55302           | MIL-DTL-55302/173      |
| 341 | M55302/174  | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Receptacle Assemblies, Right Angel, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing)  | MIL-DTL-55302           | MIL-DTL-55302/174      |
| 342 | M55302/175  | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Pin Assemblies, Right Angle, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing)         | MIL-DTL-55302           | MIL-DTL-55302/175      |
| 343 | M55302/176  | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Pin Assemblies, 75 Through 405 Contact Positions, For Printed Wiring Boards (.100 Spacing)                      | MIL-DTL-55302           | MIL-DTL-55302/176      |
| 344 | M55302/177  | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Receptacle Assemblies, Right Angle, 75 Through 405 Contact Positions, for Printed Wiring Boards (.100 Spacing)  | MIL-DTL-55302           | MIL-DTL-55302/177      |
| 345 | M55302/178  | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Pin Assemblies, Right Angle, 75 Through 405 Contact Positions, for Printed Wiring Boards (.100 Spacing)         | MIL-DTL-55302           | MIL-DTL-55302/178      |
| 346 | M55302/179  | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Pin Assemblies, 100 Through 684 Contact Positions, for Printed Wiring Boards(.100 Spacing)                      | MIL-DTL-55302           | MIL-DTL-55302/179      |
| 347 | M55302/180  | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Receptacle Assemblies, Right Angle, 100 Through 684 Contact Positions, for Printed Wiring Boards (.100 Spacing) | MIL-DTL-55302           | MIL-DTL-55302/180      |
| 348 | M55302/181  | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Pin Assemblies, Right Angle, 100 Through 684 Contact Positions, for Printed Wiring Boards (.100 Spacing)        | MIL-DTL-55302           | MIL-DTL-55302/181      |
| 349 | M55302/190  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 thru 100 Positions, Printed Wiring Boards (.075 Spacing)             | MIL-DTL-55302           | MIL-DTL-55302/190      |
| 350 | M55302/191  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 thru 100 Positions, Printed Wiring Board (.075 Spacing)                       | MIL-DTL-55302           | MIL-DTL-55302/191      |
| 351 | M55302/192  | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, 122 and 152 Positions, Printed Wiring Board (.075 Spacing)                                | MIL-DTL-55302           | MIL-DTL-55302/192      |
| 352 | M55302/193  | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 122 and 152 Position, Printed Wiring Board (.075 Spacing)                                          | MIL-DTL-55302           | MIL-DTL-55302/193      |

| No. | Part Number | Description                                                                                                                   | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 353 | M28754/6    | Connector, Electrical, Modular, Type IV 40 Pin, Straight Through                                                              | MIL-C-28754             | MIL-C-28754/6          |
| 354 | M28754/7    | Connectors, Electrical, Modular, Type IV, Single Span, Connector Assembly                                                     | MIL-C-28754             | MIL-C-28754/7          |
| 355 | M28754/8    | Connectors Electrical, Modular, Type IV, 40 Contact, Right Angle (for Die Cast Frame)                                         | MIL-C-28754             | MIL-C-28754/8          |
| 356 | M28754/9    | Connectors, Electrical, Modular, Type IV, Double Span, Connector Assembly, (Dip Frame)                                        | MIL-C-28754             | MIL-C-28754/9          |
| 357 | M28754/10   | Connectors, Electrical, Modular, Connector, Type IV, 40 Pin, Contact Tails on 0.050 Centers                                   | MIL-C-28754             | MIL-C-28754/10         |
| 358 | M28754/11   | Connectors, Electrical, Modular, Type IV, 40 Contact, Right Angle (for Solid or Dip Frame)                                    | MIL-C-28754             | MIL-C-28754/11         |
| 359 | M28754/12   | Connectors, Electrical, Modular, Connector Assembly, Type IV, Single Span (for Solid or Dip Frame)                            | MIL-C-28754             | MIL-C-28754/12         |
| 360 | M28754/13   | Connectors, Electrical, Modular, Connector Assembly, Type IV, Single Span (without Guide Ribs)                                | MIL-C-28754             | MIL-C-28754/13         |
| 361 | M28754/14   | Connectors, Electrical, Modular, Connector, Type IV, 20 Contact, Right Angle (for Die Cast Frame)                             | MIL-C-28754             | MIL-C-28754/14         |
| 362 | M28754/15   | Connectors, Electrical, Modular, Crimp, Contact, Type V                                                                       | MIL-C-28754             | MIL-C-28754/15         |
| 363 | M28754/16   | Connectors, Electrical, Modular, Block, 40 Pin, Type V, Straight Through                                                      | MIL-C-28754             | MIL-C-28754/16         |
| 364 | M28754/17   | Connectors, Electrical, Modular, Connector Assembly, Type V, Style I, Contact Tails on .100 Centers                           | MIL-C-28754             | MIL-C-28754/17         |
| 365 | M28754/18   | Connectors, Electrical, Modular, Spacer, Pin, Type IV, Single Span                                                            | MIL-C-28754             | MIL-C-28754/18         |
| 366 | M28754/19   | Connectors, Electrical, Modular, Spacer, Pin, Type IV, Single Span                                                            | MIL-C-28754             | MIL-C-28754/19         |
| 367 | M28754/20   | Connectors, Electrical, Modular, Spacer, Pin, Type IV, Double Span                                                            | MIL-C-28754             | MIL-C-28754/20         |
| 368 | M28754/21   | Connectors, Electrical, Modular, Frame, Casting, Type IV, Double Span                                                         | MIL-C-28754             | MIL-C-28754/21         |
| 369 | M28754/22   | Connectors, Electrical, Modular, Frame, Casting, Type IV, Single Span                                                         | MIL-C-28754             | MIL-C-28754/22         |
| 370 | M28754/23   | Connectors, Electrical, Modular, Connector Assembly, Type IV, Single Span                                                     | MIL-C-28754             | MIL-C-28754/23         |
| 371 | M28754/24   | Connectors, Electrical, Modular, Pin, Keying                                                                                  | MIL-C-28754             | MIL-C-28754/24         |
| 372 | M28754/25   | ectors, Electrical, Modular, Guide, Retaining                                                                                 | MIL-C-28754             | MIL-C-28754/25         |
| 373 | M28754/31   | Connectors, Electrical, Modular, Connector Assembly, Type V, 40-Pin, Two Piece Insert, and 20-Pin, One Half, One Piece Insert | MIL-C-28754             | MIL-C-28754/31         |
| 374 | M28754/32   | Connectors, Electrical, Modular, Connector Assembly, Type V, Style I, Slip Lock Cover Plate                                   | MIL-C-28754             | MIL-C-28754/32         |
| 375 | M28754/33   | Connectors, Electrical, Modular, Connector Assembly, Type V, Style III Slip Lock Cover Plate                                  | MIL-C-28754             | MIL-C-28754/33         |

| No. | Part Number | Description                                                                                                                             | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 376 | M28754/39   | Connectors, Electrical, Modular, Connector, Type III, Keying Pegs                                                                       | MIL-C-28754             | MIL-C-28754/39         |
| 377 | M28754/40   | Connectors, Electrical, Modular, Type IV, Connector Assembly, Screw                                                                     | MIL-C-28754             | MIL-C-28754/40         |
| 378 | M28754/41   | Connectors, Electrical, Modular, Type IV, Connector Assembly, Screw, Insert                                                             | MIL-C-28754             | MIL-C-28754/41         |
| 379 | M28754/42   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Offset Contact Tails on .050 Centers                                      | MIL-C-28754             | MIL-C-28754/42         |
| 380 | M28754/43   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 100 Pin, Double Span contact Tails on .050 Centers                        | MIL-C-28754             | MIL-C-28754/43         |
| 381 | M28754/44   | Connectors, Electrical, Modular, Type IV, 100 Pin, Straight, Contact Tails on .100 Centers                                              | MIL-C-28754             | MIL-C-28754/44         |
| 382 | M28754/45   | Connectors, Electrical, Modular, Connector Frame, Type VI, Double Span                                                                  | MIL-C-28754             | MIL-C-28754/45         |
| 383 | M28754/46   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 100 Pin, Double Span                                                      | MIL-C-28754             | MIL-C-28754/46         |
| 384 | M28754/47   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Right Angle Contact Tails on .100 Centers                                 | MIL-C-28754             | MIL-C-28754/47         |
| 385 | M28754/48   | Connectors, Electrical, Modular, Type IV, Connector Assembly, Single Span                                                               | MIL-C-28754             | MIL-C-28754/48         |
| 386 | M28754/49   | Connectors, Electrical, Modular, Housing                                                                                                | MIL-C-28754             | MIL-C-28754/49         |
| 387 | M28754/50   | Connectors, Electrical, Modular, Insert, Top                                                                                            | MIL-C-28754             | MIL-C-28754/50         |
| 388 | M28754/51   | Connectors, Electrical, Modular, Insert, Bottom                                                                                         | MIL-C-28754             | MIL-C-28754/51         |
| 389 | M28754/52   | Connector, Electrical, Modular, Housing, Connector Assembly, Style I                                                                    | MIL-C-28754             | MIL-C-28754/52         |
| 390 | M28754/53   | Connector, Electrical, Modular, Housing Connector Assembly, Style II                                                                    | MIL-C-28754             | MIL-C-28754/53         |
| 391 | M28754/55   | Connectors, Electrical, Modular, Connector Assembly, Type V, Cable Connector, 100 Pin, Contacts on .100 Centers                         | MIL-C-28754             | MIL-C-28754/55         |
| 392 | M28754/56   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Offset Contact Tails, on .050 Centers (Ceramic Compatible)                | MIL-C-28754             | MIL-C-28754/56         |
| 393 | M28754/57   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Offset Contact Tails on .050 Centers (Modified Frame, Ceramic Compatible) | MIL-C-28754             | MIL-C-28754/57         |
| 394 | M28754/58   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Offset Contact Tails on .050 Centers (Modified Frame)                     | MIL-C-28754             | MIL-C-28754/58         |
| 395 | M28754/59   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Center Contact Tails on .100 Centers (Ceramic Compatible)                 | MIL-C-28754             | MIL-C-28754/59         |
| 396 | M28754/60   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Center Contact Tails on .100 Centers                                      | MIL-C-28754             | MIL-C-28754/60         |

| No. | Part Number | Description                                                                                                                             | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 397 | M28754/61   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Center, Crossover, Contact Tails on .050 Centers (Ceramic Compatible)     | MIL-C-28754             | MIL-C-28754/61         |
| 398 | M28754/62   | Connectors, Electrical, Modular, Type IV, Connector, 100 Pin, Center Crossover, Contact Tails on .050 Centers                           | MIL-C-28754             | MIL-C-28754/62         |
| 399 | M28754/63   | Connectors, Electrical, Modular, Type IV, Connector, 40 Pin, Offset, Contact Tails on .050 Centers (Ceramic Compatible)                 | MIL-C-28754             | MIL-C-28754/63         |
| 400 | M28754/64   | Connectors, Electrical, Modular, Type IV, Connector, 40 Pin, Offset, Contact Tails on .050 Centers (Modified Frame, Ceramic Compatible) | MIL-C-28754             | MIL-C-28754/64         |
| 401 | M28754/65   | Connectors, Electrical, Modular, Type IV, Connector, 40 Pin, Center Contact Tails on .100 Centers (Ceramic Compatible)                  | MIL-C-28754             | MIL-C-28754/65         |
| 402 | M28754/66   | nectors, Electrical, Modular, Type IV, Connector, 40 Pin, Crossover, Contact Tails on .050 Centers (Ceramic Compatible)                 | MIL-C-28754             | MIL-C-28754/66         |
| 403 | M28754/67   | Connectors, Electrical, Modular, Connector Frame, Type IV, Double Span, Center                                                          | MIL-C-28754             | MIL-C-28754/67         |
| 404 | M28754/68   | Connectors, Electrical, Modular, Connector Frame, Type IV, Double Span, T-Dip                                                           | MIL-C-28754             | MIL-C-28754/68         |
| 405 | M28754/69   | Connectors, Electrical, Modular, Connector Frame, Type IV, Double Span, Offset                                                          | MIL-C-28754             | MIL-C-28754/69         |
| 406 | M28754/70   | Connectors, Electrical, Modular, Connector Frame, Type IV, Single Span, Center                                                          | MIL-C-28754             | MIL-C-28754/70         |
| 407 | M28754/71   | Connectors, Electrical, Modular, Connector Frame, Type IV, Single Span, Offset                                                          | MIL-C-28754             | MIL-C-28754/71         |
| 408 | M28754/72   | Connectors, Electrical, Modular, Connector Frame, Type IV, Single Span, T-Dip                                                           | MIL-C-28754             | MIL-C-28754/72         |
| 409 | M28754/73   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 100 Contact, Double Span, Dip                                             | MIL-C-28754             | MIL-C-28754/73         |
| 410 | M28754/74   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 100 Contact, Double Span, Center                                          | MIL-C-28754             | MIL-C-28754/74         |
| 411 | M28754/75   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 100 Contact, Double Span, Offset                                          | MIL-C-28754             | MIL-C-28754/75         |
| 412 | M28754/76   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 40 Contact, Single Span, Center                                           | MIL-C-28754             | MIL-C-28754/76         |
| 413 | M28754/77   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 40 Contact, Single Span, Offset                                           | MIL-C-28754             | MIL-C-28754/77         |
| 414 | M28754/78   | Connectors, Electrical, Modular, Connector Assembly, Type IV, 40 Contact, Single Span , Dual Inline Package (DIP)                       | MIL-C-28754             | MIL-C-28754/78         |

| No. | Part Number | Description                                                                                                                                       | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 415 | M28754/79   | Connectors, Electrical, Modular, Type III, Female Contact and Insulator Bushing Set, Low Insertion Force (LIF), Removable Wire Wrappost Terminal  | MIL-C-28754             | MIL-C-28754/79         |
| 416 | M28754/80   | Connectors, Electrical, Modular, Type III, Female Contact and Grounding Bushing Set, Low Insertion Force (LIF), Removable Wire Wrappost Terminal  | MIL-C-28754             | MIL-C-28754/80         |
| 417 | M28754/81   | Connectors, Electrical, Modular, Type III, Female Contact and Polarizing Bushing Set, Low Insertion Force (LIF), Removable Wire Wrappost Terminal | MIL-C-28754             | MIL-C-28754/81         |
| 418 | M28754/82   | Connectors, Electrical, Modular, Type IV, Connector Assembly, Fastener                                                                            | MIL-C-28754             | MIL-C-28754/82         |
| 419 | M28754/83   | Connectors, Electrical, Modular, Type IV, Connector, 0.6 Pitch, 250 Contact, Center                                                               | MIL-C-28754             | MIL-C-28754/83         |
| 420 | M28754/84   | Connectors, Electrical, Modular, Type IV, Connector, 0.3 Pitch, 100 Contact, Offset                                                               | MIL-C-28754             | MIL-C-28754/84         |
| 421 | M28754/85   | Connectors, Electrical, Modular, Type IV, Connector, 0.3 Pitch, 100 Contact, Dual Inline Package (DIP)                                            | MIL-C-28754             | MIL-C-28754/85         |
| 422 | M28754/86   | Connectors, Electrical, Modular, Connector Frame, Type IV, Dual Inline Package (DIP)                                                              | MIL-C-28754             | MIL-C-28754/86         |
| 423 | M28754/87   | Connectors, Electrical, Modular, Connector Frame, Type IV, Center                                                                                 | MIL-C-28754             | MIL-C-28754/87         |
| 424 | M28754/88   | Connectors, Electrical, Modular, Connector Frame, Type IV, Offset,(0.050 Thickness)                                                               | MIL-C-28754             | MIL-C-28754/88         |
| 425 | M28754/89   | Connectors, Electrical, Modular, Connector Frame, Type IV, Offset,(0.071 Thickness)                                                               | MIL-C-28754             | MIL-C-28754/89         |
| 426 | M28754/90   | Connectors, Electrical, Modular, Connector Frame, Type IV, Center Fin, 0.4 Pitch, Format C                                                        | MIL-C-28754             | MIL-C-28754/90         |
| 427 | M28754/91   | Connectors, Electrical, Modular, Connector Frame, Type IV, Center Fin, 0.5 Pitch, Format C and E                                                  | MIL-C-28754             | MIL-C-28754/91         |
| 428 | M28754/92   | Connectors, Electrical, Modular, Connector Frame, Type IV, Center Fin, 0.6 Pitch, Format C and E                                                  | MIL-C-28754             | MIL-C-28754/92         |
| 429 | M28754/93   | Connectors, Electrical, Modular, Connector Frame, Type IV, DIP, 0.3 Pitch, Format C                                                               | MIL-C-28754             | MIL-C-28754/93         |
| 430 | M28754/94   | Connectors, Electrical, Modular, Connector Frame, Type IV, DIP, 0.4 Pitch, Format C, D and E                                                      | MIL-C-28754             | MIL-C-28754/94         |
| 431 | M28754/95   | Connectors, Electrical, Modular, Connector Frame, Type IV, Offset Fin, 0.3 Pitch, Format C                                                        | MIL-C-28754             | MIL-C-28754/95         |
| 432 | M28754/96   | Connectors, Electrical, Modular, Connector Frame, Type IV, Center Fin, 0.4 Pitch, Format C and E                                                  | MIL-C-28754             | MIL-C-28754/96         |
| 433 | M28754/97   | Connectors, Electrical, Modular, Type IV, Connector, 150 Contact, Angle, Contact Tails on 0.100 Centers                                           | MIL-C-28754             | MIL-C-28754/97         |
| 434 | M28754/98   | Connectors, Electrical, Modular, Type IV, Connector, 150 Contact, Center, Contact Tails on 0.100 Centers                                          | MIL-C-28754             | MIL-C-28754/98         |

| No. | Part Number | Description                                                                                                                                                            | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 435 | M28754/99   | Connectors, Electrical, Modular, Type IV, Connector, 150 Contact, Offset                                                                                               | MIL-C-28754             | MIL-C-28754/99         |
| 436 | M28754/100  | Connectors, Electrical, Modular, Type IV, Connector, 200 Contact, Center                                                                                               | MIL-C-28754             | MIL-C-28754/100        |
| 437 | M28754/101  | Connectors, Electrical, Modular, Type IV, Connector, 0.6 Pitch, 250                                                                                                    | MIL-C-28754             | MIL-C-28754/101        |
| 438 | MS17343     | Connector, Receptacle, Electrical, Wall Mounting                                                                                                                       | MIL-DTL-22992           | MS17343                |
| 439 | MS17344     | Connector, Plug, Electrical, Straight                                                                                                                                  | MIL-DTL-22992           | MS17344                |
| 440 | MS17345     | Connector, Plug, Electrical, Cable Connecting, Female                                                                                                                  | MIL-DTL-22992           | MS17345                |
| 441 | MS17346     | Connector, Receptacle, Electrical, Box Mounting                                                                                                                        | MIL-DTL-22992           | MS17346                |
| 442 | MS17347     | Connector, Receptacle, Electrical, Jamnut                                                                                                                              | MIL-DTL-22992           | MS17347                |
| 443 | MS17348     | Connector, Receptacle, Electrical, Jamnut (Box)                                                                                                                        | MIL-DTL-22992           | MS17348                |
| 444 | MS17349     | Cover, Protective, Electrical Connector, Receptacle                                                                                                                    | MIL-DTL-22992           | MS17349                |
| 445 | MS17350     | Cover, Protective, Connector, Plug                                                                                                                                     | MIL-DTL-22992           | MS17350                |
| 446 | MS18062     | Connector, Receptacle, Dummy Stowage                                                                                                                                   | MIL-DTL-22992           | MS18062                |
| 447 | MS90555     | Connector, Receptacle, Electrical, Wall Mounting, Class L (Power Source Receptacle)                                                                                    | MIL-DTL-22992           | MS90555                |
| 448 | MS90556     | Connector, Plug, Electrical, Straight, Class L                                                                                                                         | MIL-DTL-22992           | MS90556                |
| 449 | MS90557     | Connector, Receptacle, Electrical, Cable Connecting, (without Coupling Ring), Class L                                                                                  | MIL-DTL-22992           | MS90557                |
| 450 | MS90558     | Connector, Plug, Electrical, Wall Mounting, (with Coupling Ring) Class L, (Equipment)                                                                                  | MIL-DTL-22992           | MS90558                |
| 451 | MS90563     | Cover, Electrical Connector, Receptacle, Class L                                                                                                                       | MIL-DTL-22992           | MS90563                |
| 452 | MS90564     | Cover, Electrical, Connector, Plug, Class L                                                                                                                            | MIL-DTL-22992           | MS90564                |
| 453 | M25516/16   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type Coaxial Pressurized Receptacle, Series IV, Class G, Type 4                                       | MIL-DTL-25516           | MIL-C-25516/16         |
| 454 | M25516/17   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Hermetically Sealed Receptacle, Series IV, Class H, Type 4                              | MIL-DTL-25516           | MIL-C-25516/17         |
| 455 | M25516/18   | Connectors, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Straight, Hermetically Sealed Panel Adapter, Two Jack Ends, Series III, Class Y Type 5 | MIL-DTL-25516           | MIL-C-25516/18         |
| 456 | M25516/19   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Pressurized Receptacle, Series I, Class G, Type 1                                       | MIL-DTL-25516           | MIL-C-25516/19         |
| 457 | M25516/20   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial, Plug, Series I, Class G, Type 1                                                        | MIL-DTL-25516           | MIL-C-25516/20         |
| 458 | M25516/21   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Isolated Hermetically Sealed Receptacle, Series IV, Class H, Type 2                             | MIL-DTL-25516           | MIL-C-25516/21         |

| No. | Part Number | Description                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 459 | M25516/22   | Connectors, Electrical, Miniature, Coaxial, Environment Resistant Type, Triaxial Hermetic Adapter, Isolated Ground, Series III, Class Y, Type 6 | MIL-DTL-25516           | MIL-C-25516/22         |
| 460 | M25516/24   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type Coaxial Pressurized Receptacle, Type 25516/24                             | MIL-DTL-25516           | MIL-C-25516/24         |
| 461 | M25516/25   | Connectors, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Hermetically Sealed Receptacle Series I, Class H, Type 1        | MIL-DTL-25516           | MIL-C-25516/25         |
| 462 | M25516/26   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Plug, Series I, Class G, Type 3                                  | MIL-DTL-25516           | MIL-C-25516/26         |
| 463 | M25516/27   | Connector, Electrical, Miniature, Coaxial, Environment Resistant Type, Coaxial Hermetically Sealed Receptacle, Series IV, Class H, Type 4       | MIL-DTL-25516           | MIL-C-25516/27         |
| 464 | M25516/28   | Connectors, Electrical, Miniature, Coaxial, Environment Resistant Type, Plug (Lanyard Release), Series I, Class G, Type 1                       | MIL-DTL-25516           | MIL-C-25516/28         |
| 465 | M25516/29   | Connectors, Electrical, Miniature, Coaxial, Environment Resistant Type, Hermetically Sealed Receptacle, Series IV, Class G, Type 4              | MIL-DTL-25516           | MIL-C-25516/29         |
| 466 | MS3110      | Connectors, Receptacle, Electrical, Solder Type, Wall Mounting, Bayonet Coupling, Series 1, Classes E, F, J and P                               | MIL-DTL-26482           | MS3110                 |
| 467 | MS3111      | Connectors, Plug, Electrical, Solder Type, Cable Connecting, Bayonet Coupling, Classes E, F, J, and P                                           | MIL-DTL-26482           | MS3111                 |
| 468 | MS3112      | Connectors, Receptacle, Electrical, Box Mounting, Flange, Bayonet Coupling, Solder Contact, Series 1                                            | MIL-DTL-26482           | MS3112                 |
| 469 | MS3113      | Connectors, Receptacle, Electrical, Series I, Solder Type, Solder Mounting, Bayonet Coupling, Class H                                           | MIL-DTL-26482           | MS3113                 |
| 470 | MS3114      | Connectors, Receptacle, Electrical, Series 1, Solder Type, Jam Nut Mounting, Bayonet Coupling, Classes E, F, H and P                            | MIL-DTL-26482           | MS3114                 |
| 471 | MS3115      | CONNECTOR, ELECTRIC, CIRCULAR, MINIATURE, QUICK,DISCONNECT, ENVIRONMENT RESISTING                                                               | MIL-DTL-26482           | MS3115                 |
| 472 | MS3116      | CONNECTORS, PLUG, ELECTRIC, SERIES 1, SOLDER TYPE, STRAIGHT, BAYONET COUPLING                                                                   | MIL-DTL-26482           | MS3116                 |
| 473 | MS3119      | Adapter, Connectors, Receptacle, Electrical, Thru-Bulkhead Mounting, Flange, Bayonet Coupling, Series 1                                         | MIL-DTL-26482           | MS3119                 |

| No. | Part Number | Description                                                                                                                        | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 474 | MS3120      | Connectors, Receptacle, Electrical, Crimp Type, Wall Mounting, Flange, No. 4 Holes, Bayonet Coupling, Series 1, Classes E, F and P | MIL-DTL-26482           | MS3120                 |
| 475 | MS2121      | Connectors, Plug, Electrical, Crimp Type, Cable-Connecting, Bayonet Coupling, Series 1, Classes E, F and P                         | MIL-DTL-26482           | MS2121                 |
| 476 | MS3122      | Connectors, Receptacle, Electrical, Crimp Type, Box Mounting, Flange, No. 4 Holes, Bayonet Coupling, Series 1                      | MIL-DTL-26482           | MS3122                 |
| 477 | MS3124      | Connectors, Receptacle, Electric, Crimp Type, Rear Mounting, Jam Nut, Bayonet Coupling, Series 1, Classes E, F and P               | MIL-DTL-26482           | MS3124                 |
| 478 | MS3126      | Connectors, Plug, Electrical, Crimp Type, Straight, Bayonet Coupling, Series 1, Classes E, F and P                                 | MIL-DTL-26482           | MS3126                 |
| 479 | MS3127      | Connectors, Receptacle, Electrical, Series 1, Crimp Type, Box Mounting, Flange, No. 4/6 Holes, Bayonet Coupling, Class E           | MIL-DTL-26482           | MS3127                 |
| 480 | MS3128      | Connector, Receptacle, Electrical, Crimp Type, Wall Mounting, No. 4/6 Holes, Bayonet Coupling, Series 1, Classes E, F and P        | MIL-DTL-26482           | MS3128                 |
| 481 | MS3440      | Connectors, Receptacle, Electrical, Narrow Flange Mount, Bayonet Coupling, Solder Pin Contact, Class H, Series 2                   | MIL-DTL-26482           | MS3440                 |
| 482 | MS3442      | Connectors, Receptacle, Electrical, Wide Flange Mount, Bayonet Coupling, Solder Pin Contact, Class H, Series 2                     | MIL-DTL-26482           | MS3442                 |
| 483 | MS3443      | Connectors, Receptacle, Electrical, Solder or Welded Flange Mount, Bayonet Coupling, Solder Pin Contact, Class H, Series 2         | MIL-DTL-26482           | MS3443                 |
| 484 | MS3449      | Connectors, Receptacle, Electrical, Series II, Single Hole Mount, Bayonet Coupling, Solder Pin Contact, Class H                    | MIL-DTL-26482           | MS3449                 |
| 485 | MS3470      | Connectors, Receptacle, Electrical, Series 2, Crimp Type, Narrow Flange Mount, Bayonet Coupling, Classes A, D, L, T, W and Z       | MIL-DTL-26482           | MS3470                 |
| 486 | MS3471      | Connectors, Receptacle, Electrical, Series 2, Crimp Type, Cable Connecting, Bayonet Coupling, Classes A, D, L, T, W and Z          | MIL-DTL-26482           | MS3471                 |
| 487 | MS3472      | Connectors, Receptacle, Electrical, Series 2, Crimp Type, Wide Flange Mounting, Bayonet Coupling, Classes A, D, L, T, W and Z      | MIL-DTL-26482           | MS3472                 |
| 488 | MS3473      | Connectors, Receptacle, Electrical, Series II, Hermetic, Solderless, Solder Mounting, Bayonet Coupling, Class N                    | MIL-DTL-26482           | MS3473                 |

| No. | Part Number | Description                                                                                                                              | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 489 | MS3474      | Connectors, Receptacle, Electrical, Series 2, Crimp Type, Rear Mounting Jam Nut, Bayonet Coupling, Classes A, D, L, T, W and Z           | MIL-DTL-26482           | MS3474                 |
| 490 | MS3475      | Connectors, Plug, Electrical, RFI Shielded, Series 2, Crimp Type, Bayonet Coupling, Classes D, L, T, W and Z                             | MIL-DTL-26482           | MS3475                 |
| 491 | MS3476      | Connectors, Plug, Electrical, Series 2, Crimp Type, Bayonet Coupling, Classes A, D, L, T, W and Z                                        | MIL-DTL-26482           | MS3476                 |
| 492 | MS3477      | Connectors, Receptacle, Electrical, Series II, Hermetic, Solderless, Box Mounting, Bayonet Coupling, Class N                             | MIL-DTL-26482           | MS3477                 |
| 493 | MS3479      | Connectors, Receptacle, Electrical, Series II, Hermetic, Solderless, Rear Mounting, Jam Nut, Bayonet Coupling, Class N                   | MIL-DTL-26482           | MS3479                 |
| 494 | MS3115      | Connectors, Receptacle, Electrical, Dummy Stowage, Bayonet Coupling, for MIL-DTL-26482 Connectors, Series 1 and 2                        | MIL-DTL-26482           | MS3115                 |
| 495 | MS3180      | Cover, Protective, Electrical Connector Plug, Bayonet Coupling for, MIL-C-26482 Connectors                                               | MIL-DTL-26482           | MS3180                 |
| 496 | MS3181      | Cover, Protective, Electrical Connector Receptacle, Bayonet Coupling for, MIL-C-26482 Connectors                                         | MIL-DTL-26482           | MS3181                 |
| 497 | MS24285     | CONNECTOR, ELECTRICAL, STYLE S, RACK AND PANEL, MINIATURE                                                                                | MIL-DTL-26518           | MS24285                |
| 498 | MS24286     | CONNECTORS, ELECTRICAL, MINIATURE                                                                                                        | MIL-DTL-26518           | MS24286                |
| 499 | MS27399     | CONNECTOR, ELECTRICAL, STYLE S, RACK AND PANEL, MINIATURE, CLOSED ENTRY                                                                  | MIL-DTL-26518           | MS27399                |
| 500 | M28731/1    | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 75 Removable Contacts (No S/S Document)   | MIL-DTL-28731           | MIL-C-28731/1          |
| 501 | M28731/2    | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 75 Removable Contacts (No S/S Document) | MIL-DTL-28731           | MIL-C-28731/2          |
| 502 | M28731/3    | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 100 Removable Contacts                    | MIL-DTL-28731           | MIL-C-28731/3          |
| 503 | M28731/4    | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 100 Removable Contacts                  | MIL-DTL-28731           | MIL-C-28731/4          |
| 504 | M28731/5    | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 130 Removable Contacts (No S/S Document)  | MIL-DTL-28731           | MIL-C-28731/5          |

| No. | Part Number | Description                                                                                                                                   | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 505 | M28731/6    | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 130 Removable Contacts (No S/S Document)     | MIL-DTL-28731           | MIL-C-28731/6          |
| 506 | M28731/7    | Connector, Electrical, Shield, Rectangular for 75, 100 or 130 Removable Contacts (No S/S Document)                                            | MIL-DTL-28731           | MIL-C-28731/7          |
| 507 | M28731/9    | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 20 Removable Contacts                          | MIL-DTL-28731           | MIL-C-28731/9          |
| 508 | M28731/10   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 20 Removable Contacts                        | MIL-DTL-28731           | MIL-C-28731/10         |
| 509 | M28731/11   | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 38 Removable Contacts                          | MIL-DTL-28731           | MIL-C-28731/11         |
| 510 | M28731/12   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 38 Removable Contacts                        | MIL-DTL-28731           | MIL-C-28731/12         |
| 511 | M28731/13   | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 56 Removable Contacts                          | MIL-DTL-28731           | MIL-C-28731/13         |
| 512 | M28731/14   | Connector, Electrical, Insert (Insulator), Female rectangular, Polarized, Center Screw Lock, for 56 Removable Contacts                        | MIL-DTL-28731           | MIL-C-28731/14         |
| 513 | M28731/15   | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 90 Removable Contacts                          | MIL-DTL-28731           | MIL-C-28731/15         |
| 514 | M28731/16   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 90 Removable Contacts                        | MIL-DTL-28731           | MIL-C-28731/16         |
| 515 | M28731/17   | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock for 120 Removable Contacts                          | MIL-DTL-28731           | MIL-C-28731/17         |
| 516 | M28731/18   | Connector, electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 120 Removable Contacts                       | MIL-DTL-28731           | MIL-C-28731/18         |
| 517 | M28731/19   | Connector, Electrical, Rectangular Shield for 20, 38, 56, 90 or 120 Removable Contacts                                                        | MIL-DTL-28731           | MIL-C-28731/19         |
| 518 | M28731/24   | Connector, Electrical, Rectangular Shield, for 120 Removable Contacts                                                                         | MIL-DTL-28731           | MIL-C-28731/24         |
| 519 | M28731/27   | Connector, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 33 Removable Type Contacts (No S/S Document)   | MIL-DTL-28731           | MIL-C-28731/27         |
| 520 | M28731/28   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 33 Removable Type Contacts (No S/S Document) | MIL-DTL-28731           | MIL-C-28731/28         |

| No. | Part Number | Description                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 521 | M28731/29   | Connectors, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 75 Removable Type Contacts                      | MIL-DTL-28731           | MIL-C-28731/29         |
| 522 | M28731/30   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 75 Removable Type Contacts                     | MIL-DTL-28731           | MIL-C-28731/30         |
| 523 | M28731/31   | Connectors, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 117 Removable Type Contacts                     | MIL-DTL-28731           | MIL-C-28731/31         |
| 524 | M28731/32   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 117 Removable Type Contacts                    | MIL-DTL-28731           | MIL-C-28731/32         |
| 525 | M28731/33   | Connectors, Electrical, Insert (Insulator), Male Rectangular, Polarized, Center Screw Lock, for 165 Removable Type Contacts                     | MIL-DTL-28731           | MIL-C-28731/33         |
| 526 | M28731/34   | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 165 Removable Type Contacts                    | MIL-DTL-28731           | MIL-C-28731/34         |
| 527 | M28731/37   | Connector, Electrical, Rectangular Shield, for Female Rectangular 165 Removable Type Contacts                                                   | MIL-DTL-28731           | MIL-C-28731/37         |
| 528 | M28731/38   | Connector, Electrical, Rectangular Shield, for use with MIL-C-28731/32                                                                          | MIL-DTL-28731           | MIL-C-28731/38         |
| 529 | M28748/1    | Connectors, Electrical, Rectangular, Rack and Panel, Solder Type Pin Contacts, Size 16                                                          | MIL-DTL-28748           | MIL-DTL-28748/1        |
| 530 | M28748/2    | Connectors, Electrical, Rectangular, Rack and Panel, Solder Type Socket Contacts, Size 16                                                       | MIL-DTL-28748           | MIL-DTL-28748/2        |
| 531 | M28748/3    | Connectors, Electrical, Rectangular, Rack and Panel, Crimp Type Removable Pin Contacts, Sizes 16 and 20                                         | MIL-DTL-28748           | MIL-DTL-28748/3        |
| 532 | M28748/4    | Connector, Electrical, Rectangular, Rack and Panel, Crimp Type Removable Socket Contacts, Sizes 16 and 20                                       | MIL-DTL-28748           | MIL-DTL-28748/4        |
| 533 | M28748/5    | Connectors, Electrical Rectangular, Rack and Panel, Solder Type Pin Contacts, Size 20                                                           | MIL-DTL-28748           | MIL-DTL-28748/5        |
| 534 | M28748/6    | Connectors, Electrical Rectangular, Rack and Panel, Solder Type Contacts, Size 20                                                               | MIL-DTL-28748           | MIL-DTL-28748/6        |
| 535 | M28748/7    | Connectors, Electrical, Rectangular, Rack and Panel, Solder Type Pin Contacts, Size 22                                                          | MIL-DTL-28748           | MIL-DTL-28748/7        |
| 536 | M28748/8    | Connectors, Electrical, Rectangular, Rack and Panel, Solder Type Socket Contacts, Size 22                                                       | MIL-DTL-28748           | MIL-DTL-28748/8        |
| 537 | M28748/9    | Connectors, Electrical, Rectangular, Rack and Panel, Polarized Center Jackscrew or Guidepin Style Crimp Type Removable Pin Contacts, Size 16    | MIL-DTL-28748           | MIL-DTL-28748/9        |
| 538 | M28748/10   | Connectors, Electrical, Rectangular, Rack and Panel, Polarized Center Jackscrew or Guidepin Style Crimp Type Removable Socket Contacts, Size 16 | MIL-DTL-28748           | MIL-DTL-28748/10       |

| No. | Part Number | Description                                                                                                                                       | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 539 | M28748/13   | Connectors, Plug, Electrical, Rectangular, Rack and Panel, Crimp Type Removable Pin Contacts, Size 22                                             | MIL-DTL-28748           | MIL-DTL-28748/13       |
| 540 | M28748/14   | Connector, Electrical, Rectangular, Rack and Panel, Crimp Type Removable Socket Contacts, Size 22                                                 | MIL-DTL-28748           | MIL-DTL-28748/14       |
| 541 | M28748/15   | CONNECTORS, ELECTRICAL, HEXAGONAL, RACK AND PANEL, MINIATURE, PLUG-RECEPTACLE, FEMALE SOLDER CUP OR PRINTED WIRING BOARD SOCKET CONTACTS, SIZE 20 | MIL-DTL-28748           | MIL-DTL-28748/15       |
| 542 | M28748/16   | Connectors, Electrical, Hexagonal, Rack and Panel, Miniature, Plug-Receptacle, Female Solder Cup Pin Contacts, Size 20                            | MIL-DTL-28748           | MIL-DTL-28748/16       |
| 543 | M28748/17   | Connectors, Electrical, Rectangular, Rack and Panel, Hardware for Sizes 16 and 20                                                                 | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 544 | M18173      | Flat Washer                                                                                                                                       | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 545 | MS18192     | Shield 7, 9, 14, 20, 26, 34, 42, 50, and 75 contact positions                                                                                     | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 546 | MS18193     | Shields for 66 and 104 contact connector                                                                                                          | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 547 | MS18194     | Jackscrews                                                                                                                                        | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 548 | MS18195     | Jackscrews                                                                                                                                        | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 549 | MS18196     | Jackscrews                                                                                                                                        | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 550 | MS18197     | Jackscrews                                                                                                                                        | MIL-DTL-28748           | MIL-DTL-28748/17       |
| 551 | MS18198     | Retaining plate                                                                                                                                   | MIL-DTL-28748           | M28748/17              |
| 552 | MS18199     | Retaining plate                                                                                                                                   | MIL-DTL-28748           | M28748/17              |
| 553 | MS18200     | Retaining plate                                                                                                                                   | MIL-DTL-28748           | M28748/17              |
| 554 | MS18203     | Plug shell configurations                                                                                                                         | MIL-DTL-28748           | M28748/17              |
| 555 | MS18204     | Receptacle shell, polarizing                                                                                                                      | MIL-DTL-28748           | M28748/17              |
| 556 | MS18205     | Pin polarizing configuration                                                                                                                      | MIL-DTL-28748           | M28748/17              |
| 557 | MS24132     | Shields for 7, 9, 14, 20, 26, 34, 42, 50, and 75                                                                                                  | MIL-DTL-28748           | M28748/17              |
| 558 | MS24133     | Shields for 7, 9, 14, 20, 26, 34, 42, 50, and 75                                                                                                  | MIL-DTL-28748           | M28748/17              |
| 559 | M28748/18   | Connectors, Electrical, Rectangular, Rack and Panel, Printed Wiring Board (PWB) Mount, Straight through, Pin Contacts, Size 22                    | MIL-DTL-28748           | M28748/18              |
| 560 | M28748/19   | Connectors, Electrical, Rectangular, Rack and Panel, Printed Wiring Board (PWB) Mount, Straight Through, Socket Contacts, Size 22                 | MIL-DTL-28748           | M28748/19              |
| 561 | M28748/20   | Connectors, Electrical, Rectangular, Rack and Panel, Printed Wiring Board (PWB) Mount, Right Angle, Pin Contacts, Size 22                         | MIL-DTL-28748           | M28748/20              |

| No. | Part Number | Description                                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 562 | M28748/21   | Connectors, Electrical, Rectangular, Rack and Panel, Printed Wiring Board (PWB) Mount, Right Angle, Socket Contacts, Size 22                                    | MIL-DTL-28748           | M28748/21              |
| 563 | M28840/1    | Connector Accessories, Electrical, Circular, Threaded, High Shock, Density, Shipboard, Clamps, Strain Relief, Straight, Open, for Electrical Connectors         | MIL-DTL-28840           | MIL-DTL-28840/1        |
| 564 | M28840/2    | Connector Accessories, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Clamps, Strain Relief, 90 Degrees, Open, for Electrical Connectors  | MIL-DTL-28840           | MIL-DTL-28840/2        |
| 565 | M28840/3    | Connector Accessories, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Clamps, Strain Relief, 45 Degrees, Open, for Electrical Connectors  | MIL-DTL-28840           | MIL-DTL-28840/3        |
| 566 | M28840/4    | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Metal Conduit, for EMI Shielding                                               | MIL-DTL-28840           | MIL-DTL-28840/4        |
| 567 | M28840/5    | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, Straight, Metal Conduit for EMI Shielding                           | MIL-DTL-28840           | MIL-DTL-28840/5        |
| 568 | M28840/6    | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, Straight, Cable Sealing and Shield Termination, Connector, Electric | MIL-DTL-28840           | MIL-DTL-28840/6        |
| 569 | M28840/7    | Connectors, Electrical, Circular, Screw Threads, High Shock, High Density, Shipboard, Crimp Contacts, Dummy Receptacle, Wall Mounting                           | MIL-DTL-28840           | MIL-DTL-28840/7        |
| 570 | M28840/8    | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, 90 Degrees, Cable Sealing and Shield Termination                    | MIL-DTL-28840           | MIL-DTL-28840/8        |
| 571 | M28840/9    | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, 45 Degrees, Cable Sealing and Shield Termination                    | MIL-DTL-28840           | MIL-DTL-28840/9        |
| 572 | M28840/10   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Receptacle, Wall Mounting, Classes D, DS, P, T, and Z     | MIL-DTL-28840           | MIL-DTL-28840/10       |
| 573 | M28840/11   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Receptacle, Cable Connecting, Classes D, DS, P, T, and Z  | MIL-DTL-28840           | MIL-DTL-28840/11       |
| 574 | M28840/12   | Connectors, Electrical, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts Receptacle, Box Mounting, Classes D, DS, P, T, and Z                 | MIL-DTL-28840           | MIL-DTL-28840/12       |
| 575 | M28840/13   | Connector Accessories, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Cover, Receptacle                                                   | MIL-DTL-28840           | MIL-DTL-28840/13       |
| 576 | M28840/14   | Connectors, Electrical, Circular, Screw Threads, High Shock, High Density, Shipboard, Crimp Contacts, Receptacle, Jam Nut Mounting, Classes D, DS, P, T and Z   | MIL-DTL-28840           | MIL-DTL-28840/14       |

| No. | Part Number | Description                                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 577 | M28840/15   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Dust Cover, Plug                                                                                     | MIL-DTL-28840           | MIL-DTL-28840/15       |
| 578 | M28840/16   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug, Classes D, DS, P, T, and Z                                                | MIL-DTL-28840           | MIL-DTL-28840/16       |
| 579 | M28840/17   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, Open Wire, Classes D, DS, P, T, and Z                            | MIL-DTL-28840           | MIL-DTL-28840/17       |
| 580 | M28840/18   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, Open Wire, 90 Degrees, Classes D, DS, P, T, and Z                | MIL-DTL-28840           | MIL-DTL-28840/18       |
| 581 | M28840/19   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, Open Wire, 45 degrees, Classes D, DS, P, T, and Z                | MIL-DTL-28840           | MIL-DTL-28840/19       |
| 582 | M28840/20   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Receptacle, Wall Mounting Assembly, Straight, Classes DJ, DJS, PJ, TJ and ZJ    | MIL-DTL-28840           | MIL-DTL-28840/20       |
| 583 | M28840/21   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Receptacle, Cable Connecting Assembly, Straight, Classes DJ, DJS, PJ, TJ and ZJ | MIL-DTL-28840           | MIL-DTL-28840/21       |
| 584 | M28840/22   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Metal Conduit Bushing                                                                                | MIL-DTL-28840           | MIL-DTL-28840/22       |
| 585 | M28840/23   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, Gland Nut, Wiring                                                                         | MIL-DTL-28840           | MIL-DTL-28840/23       |
| 586 | M28840/24   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Screw Threads, Crimp Contacts, Gasket, flange Mounting                                               | MIL-DTL-28840           | MIL-DTL-28840/24       |
| 587 | M28840/25   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, 90 Degrees, Metal Conduit for EMI Shielding                                               | MIL-DTL-28840           | MIL-DTL-28840/25       |
| 588 | M28840/26   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, Straight, Classes DJ, DJS, PJ, TJ and ZJ                         | MIL-DTL-28840           | MIL-DTL-28840/26       |
| 589 | M28840/27   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Backshell, 45 Degrees, Metal Conduit for EMI Shielding                                               | MIL-DTL-28840           | MIL-DTL-28840/27       |
| 590 | M28840/28   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, 90 Degrees, Classes DJ, DJS, PJ, TJ and ZJ                       | MIL-DTL-28840           | MIL-DTL-28840/28       |

| No. | Part Number | Description                                                                                                                                                     | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 591 | M28840/29   | Connectors, Electrical, Circular, Screw Threads, High Density, High Shock, Shipboard, Crimp Contacts, Plug Assembly, 45 Degrees, Classes DJ, DJS, PJ, TJ and ZJ | MIL-DTL-28840           | MIL-DTL-28840/29       |
| 592 | M28840/30   | Connectors, Electrical, Circular, Threaded, High Shock, High Density, Shipboard, Metal Conduit Coupling                                                         | MIL-DTL-28840           | MIL-DTL-28840/30       |
| 593 | M22249/1    | Connector Sets, Plug Assembly, 15-Pin, Compartment Side                                                                                                         | MIL-C-22249             | M22249/1               |
| 594 | M22249/2    | Connector Sets, Plug Assembly, 15-Pin, Missile Side                                                                                                             | MIL-C-22249             | M22249/2               |
| 595 | M22249/3    | Connector Sets, Header Assembly, 15-Pin                                                                                                                         | MIL-C-22249             | M22249/3               |
| 596 | M22249/4    | Connector Sets, Plug Assembly, 44-Pin, Compartment Side                                                                                                         | MIL-C-22249             | M22249/4               |
| 597 | M22249/5    | Connector Sets, Plug Assembly, 44-Pin, Missile Side                                                                                                             | MIL-C-22249             | M22249/5               |
| 598 | M22249/6    | Connector Sets, Header Assembly, 44-Pin                                                                                                                         | MIL-C-22249             | M22249/6               |
| 599 | M22249/7    | Connector Sets, Plug Assembly, 72-Pin, Compartment Side                                                                                                         | MIL-C-22249             | M22249/7               |
| 600 | M22249/8    | Connector Sets, Plug Assembly, 72-Pin, Compartment Side                                                                                                         | MIL-C-22249             | M22249/8               |
| 601 | M22249/9    | Connector Sets, Plug Assembly, 72-Pin, Compartment Side                                                                                                         | MIL-C-22249             | M22249/9               |
| 602 | M22249/10   | Connector Sets, Plug Assembly, 72-Pin, Missile Side                                                                                                             | MIL-C-22249             | M22249/10              |
| 603 | M22249/11   | Connector Sets, Plug Assembly, 72-Pin, Missile Side                                                                                                             | MIL-C-22249             | M22249/11              |
| 604 | M22249/12   | Connector Sets, Plug Assembly, 72-Pin, Missile Side                                                                                                             | MIL-C-22249             | M22249/12              |
| 605 | M22249/13   | Connector Sets, Header Assembly, 72-Pin                                                                                                                         | MIL-C-22249             | M22249/13              |
| 606 | M22249/14   | Connector Sets, Plug Assembly, 138-Pin, Compartment Side                                                                                                        | MIL-C-22249             | M22249/14              |
| 607 | M22249/15   | Connector Sets, Plug Assembly, 138-Pin, Compartment Side                                                                                                        | MIL-C-22249             | M22249/15              |
| 608 | M22249/16   | Connector Sets, Plug Assembly, 138-Pin, Missile Side                                                                                                            | MIL-C-22249             | M22249/16              |
| 609 | M22249/17   | Connector Sets, Plug Assembly, 138-Pin, Missile Side                                                                                                            | MIL-C-22249             | M22249/17              |
| 610 | M22249/18   | Connector Sets, Header Assembly, 138-Pin                                                                                                                        | MIL-C-22249             | M22249/18              |
| 611 | M22249/19   | Connector Sets, Plug Assembly, 175-Pin, Compartment Side                                                                                                        | MIL-C-22249             | M22249/19              |
| 612 | M22249/20   | Connector Sets, Plug Assembly, 175-Pin, Missile Side                                                                                                            | MIL-C-22249             | M22249/20              |
| 613 | M22249/21   | Connector Sets, Header Assembly, 175-Pin                                                                                                                        | MIL-C-22249             | M22249/21              |
| 614 | M22249/23   | Connector Sets, Spanner Wrench Assembly for 44- and 72-Pin Umbilical Plug Coupling Nuts                                                                         | MIL-C-22249             | M22249/23              |
| 615 | M22249/24   | Connector Sets, Spanner Wrench Assembly for 138- and 175-Pin Umbilical Plug Coupling Nuts                                                                       | MIL-C-22249             | M22249/24              |
| 616 | M22249/25   | Connector Sets, Watertight Header Cover Assembly for 15-Pin Umbilical Plug                                                                                      | MIL-C-22249             | M22249/25              |

| No. | Part Number | Description                                                                                                                                                                         | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 617 | M22249/26   | Connector Sets, Plug Assembly, 208-Pin, Compartment Side                                                                                                                            | MIL-C-22249             | M22249/26              |
| 618 | M22249/27   | Connector Sets, Header Assembly, 208-Pin (45 degrees Orientation)                                                                                                                   | MIL-C-22249             | M22249/27              |
| 619 | M22249/28   | Connector Sets, Header Assembly, 208-Pin (310 Degrees Orientation)                                                                                                                  | MIL-C-22249             | M22249/28              |
| 620 | M22249/29   | Connector Sets, Plug Assembly, 208-Pin, Missile Side (45 Degrees Orientation)                                                                                                       | MIL-C-22249             | M22249/29              |
| 621 | M22249/30   | Connector Sets, Plug Assembly, 208-Pin, Missile Side, (310 Degrees Orientation)                                                                                                     | MIL-C-22249             | M22249/30              |
| 622 | M22249/31   | Connector Sets, Plug Assembly, 3-Pin, Compartment Side                                                                                                                              | MIL-C-22249             | M22249/31              |
| 623 | M22249/32   | Connector Sets, Header Assembly, 3-Pin                                                                                                                                              | MIL-C-22249             | M22249/32              |
| 624 | M22249/33   | Connector Sets, Plug Assembly, 3-Pin, Missile Side                                                                                                                                  | MIL-C-22249             | M22249/33              |
| 625 | M22249/34   | Connector Sets, Plug Assembly, 19-Pin, Compartment Side                                                                                                                             | MIL-C-22249             | M22249/34              |
| 626 | M22249/35   | Connector Sets, Header Assembly, 19-Pin                                                                                                                                             | MIL-C-22249             | M22249/35              |
| 627 | M22249/36   | Connector Sets, Plug Assembly, 19-Pin, Missile Side                                                                                                                                 | MIL-C-22249             | M22249/36              |
| 628 | M22249/37   | Connector Sets, Header Assembly, 12-Pin, Compartment Side                                                                                                                           | MIL-C-22249             | M22249/37              |
| 629 | M22249/38   | Connector Sets, Header Assembly, 12-Pin                                                                                                                                             | MIL-C-22249             | M22249/38              |
| 630 | M22249/39   | Connector Sets, Plug Assembly, 12-Pin, Missile Side                                                                                                                                 | MIL-C-22249             | M22249/39              |
| 631 | M22249/40   | Connector Sets, Plug Assembly, 6-Pin, Compartment Side                                                                                                                              | MIL-C-22249             | M22249/40              |
| 632 | M22249/41   | Connector Sets, Header Assembly, 6-Pin                                                                                                                                              | MIL-C-22249             | M22249/41              |
| 633 | M22249/42   | Connector Sets, Plug Assembly, 6-Pin, Missile Side                                                                                                                                  | MIL-C-22249             | M22249/42              |
| 634 | M22249/43   | Connector Sets, Plug Assembly, 6-Pin, Missile Side, Right Angle                                                                                                                     | MIL-C-22249             | M22249/43              |
| 635 | M22249/44   | Connector Sets, Spanner Wrench for 208-Pin Plug                                                                                                                                     | MIL-C-22249             | M22249/44              |
| 636 | M22249/45   | Connector Sets, Spanner Wrench, for 3-, 6-, 12-, and 19-Pin Plug Missile Side                                                                                                       | MIL-C-22249             | M22249/45              |
| 637 | M22249/46   | Connector Sets, Watertight Cover Assembly, 208-Pin, Header Assembly                                                                                                                 | MIL-C-22249             | M22249/46              |
| 638 | M22249/47   | Connector Sets, Plug Assembly, 208-Pin, Compartment Side, Three-Cable Type                                                                                                          | MIL-C-22249             | M22249/47              |
| 639 | M22249/48   | Connector Sets, Plug Assembly, 6-Pin, Missile Side, Right Angle                                                                                                                     | MIL-C-22249             | M22249/48              |
| 640 | M22249/49   | Connector Sets, Plug Assembly, 12-Pin, Missile Side, Right Angle                                                                                                                    | MIL-C-22249             | M22249/49              |
| 641 | M22249/50   | Connector Sets, Plug Assembly, 208-Pin, Compartment Side, Five Cable Type                                                                                                           | MIL-C-22249             | M22249/50              |
| 642 | M81511/1    | Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: and Accessories, Receptacle, Flange Mount Crimp Type Contacts, Class A, F and E (Series 2) | MIL-C-81511             | MIL-C-81511/1          |

| No. | Part Number | Description                                                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 643 | M81511/3    | Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories and Accessories, Receptacle, Jam Nut Mount, Crimp-Type Contacts, Class A, F and E (Series 2) | MIL-C-81511             | MIL-C-81511/3          |
| 644 | M81511/5    | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories, Plug, Cable Connecting, Crimp-Type Contacts, Class A, F and E (Series 2)                     | MIL-C-81511             | MIL-C-81511/5          |
| 645 | M81511/6    | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting and Accessories, Plug, Crimp Type Contacts, Class A, F and E (Series 2)                                        | MIL-C-81511             | MIL-C-81511/6          |
| 646 | M81511/13   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories, F Adapter, Rotable, Type I (Series 1 or 2)                                                   | MIL-C-81511             | MIL-C-81511/13         |
| 647 | M81511/14   | Connector, Adapter, Straight, Electric                                                                                                                                                                | MIL-C-81511             | MIL-C-81511/14         |
| 648 | M81511/15   | Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Plug, Sealing Contact (Series 1 or 2)                                                       | MIL-C-81511             | MIL-C-81511/15         |
| 649 | M81511/16   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories, Cap, Protective Locking                                                                      | MIL-C-81511             | MIL-C-81511/16         |
| 650 | M81511/17   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories Cover, Protective, Plug (Series 2)                                                            | MIL-C-81511             | MIL-C-81511/17         |
| 651 | M81511/18   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories, Cover, Protective, Receptacle (Series 1 or 2)                                                | MIL-C-81511             | MIL-C-81511/18         |
| 652 | M81511/19   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories Receptacle, Dummy Stowage, for Series 2 Connectors                                            | MIL-C-81511             | MIL-C-81511/19         |
| 653 | M81511/20   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories Nut, Slotted Hexagon, Connector Mounting, for Series 1 and 2 Connectors                       | MIL-C-81511             | MIL-C-81511/20         |
| 654 | M81511/21   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories: Receptacle, Flange Mount, Crimp-Type Contacts, Class A, F and E (Series 1)                   | MIL-C-81511             | MIL-C-81511/21         |
| 655 | M81511/23   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories: Receptacle, Jam Nut Mount, Crimp-Type Contacts, Class A, F, and E (Series 1)                 | MIL-C-81511             | MIL-C-81511/23         |

| No. | Part Number | Description                                                                                                                                                                                | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 656 | M81511/25   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories: Receptacle, Cable Connecting, Crimp-Type Contacts, Class A, F, and E (Series 1)   | MIL-C-81511             | MIL-C-81511/25         |
| 657 | M81511/26   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories: Plug, Crimp-Type Contacts, Class A, F, and E (Series 1)                           | MIL-C-81511             | MIL-C-81511/26         |
| 658 | M81511/41   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Flange Mount, Individual Release, Crimp Type Contacts, Class A, F and W (Series 3)     | MIL-C-81511             | MIL-C-81511/41         |
| 659 | M81511/45   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Cable Connecting, Individual Release, Crimp Type Contacts, Class A, F and W (Series 3) | MIL-C-81511             | MIL-C-81511/45         |
| 660 | M81511/46   | Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Plug, Individual, Release, Crimp-Type Contacts, Class A, F, and W (Series 3)                      | MIL-C-81511             | MIL-C-81511/46         |
| 661 | M81511/49   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Jam Nut Mount, Individual Release, Crimp Type Contacts Class A, F and W (Series 3)     | MIL-C-81511             | MIL-C-81511/49         |
| 662 | M81511/51   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Flange, Mount, Individual Release, Crimp Type Contacts Class A, F and W (Series 4)     | MIL-C-81511             | MIL-C-81511/51         |
| 663 | M81511/52   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Solder Mount, Solder Type Contacts, Pins Only, Class D (Series 4)                      | MIL-C-81511             | MIL-C-81511/52         |
| 664 | M81511/53   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Jam Nut Mount, Individual Release, Crimp-Type Contacts, Class A, F and W (Series 4)    | MIL-C-81511             | MIL-C-81511/53         |
| 665 | M81511/54   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Jam Nut Mount, Solder Type Contacts, Pins Only, Class D (Series 4)                     | MIL-C-81511             | MIL-C-81511/54         |
| 666 | M81511/55   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Receptacle, Cable Connecting, Individual Release, Crimp Type Contacts, Class A, F and W (Series 4) | MIL-C-81511             | MIL-C-81511/55         |

| No. | Part Number | Description                                                                                                                                                        | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 667 | M81511/56   | Connector, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, Plug, Individual Release, Crimp-Type Contacts, Class A, F and W (Series 4) | MIL-C-81511             | MIL-C-81511/56         |
| 668 | M2726/1     | Receptacle, Plug, Electrical, 2-Pin, 40-Ampere, 125-Volt, Direct Current (Symbol No. 715.1)                                                                        | MIL-DTL-2726            | MIL-DTL-2726/1         |
| 669 | M2726/2     | Receptacle, Plug, Electrical, 3 - Pin Grounded, 50 - Ampere, 250 - Volt, Direct Current (Symbol No. 716.1)                                                         | MIL-DTL-2726            | MIL-DTL-2726/2         |
| 670 | M2726/3     | Receptacle, Plug, Electrical, 4-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current, 60-Hertz (Symbol No. 717.1)                                                | MIL-DTL-2726            | MIL-DTL-2726/3         |
| 671 | M2726/4     | RECEPTACLE, PLUG, ELECTRICAL, 12-PIN, 5-AMPERE 125-VOLT, DIRECT CURRENT (SYMBOL NO. 718.1)                                                                         | MIL-DTL-2726            | MIL-DTL-2726/4         |
| 672 | M2726/5     | Receptacle, Plug, Electrical, 3 Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol No. 1140.1)                                                         | MIL-DTL-2726            | MIL-DTL-2726/5         |
| 673 | M2726/6     | Receptacle, Plug, Electrical, 3 - Pin Grounded, 40 - Ampere, 125 - Volt, Alternating Current (Symbol No. 1143.1)                                                   | MIL-DTL-2726            | MIL-DTL-2726/6         |
| 674 | M2726/7     | Receptacle, Electrical, 2-Pin, 40-Ampere, 125-Volt Direct Current (Symbol Nos. 756.1 and 756.2)                                                                    | MIL-DTL-2726            | MIL-DTL-2726/7         |
| 675 | M2726/8     | Receptacle, Electrical, 3-Pin Grounded, 50-Ampere, 250-Volt Direct Current (Symbol Nos. 757.1 and 757.2)                                                           | MIL-DTL-2726            | MIL-DTL-2726/8         |
| 676 | M2726/9     | Receptacle, Electrical, 4 - Pin Grounded, 40 - Ampere, 450 - Volt, Alternating Current (Symbol Nos. 758.1 and 758.2)                                               | MIL-DTL-2726            | MIL-DTL-2726/9         |
| 677 | M2726/10    | RECEPTACLE, PLUG, ELECTRICAL, 12-PIN, 5-AMPERE 125-VOLT, DIRECT CURRENT (SYMBOL NO. 759.1)                                                                         | MIL-DTL-2726            | MIL-DTL-2726/10        |
| 678 | M2726/11    | Receptacle, Electrical, 3 - Pin Grounded, 40 - Ampere, 450 - Volt, Alternating Current (Symbol Nos. 1141.1 and 1141.2)                                             | MIL-DTL-2726            | MIL-DTL-2726/11        |
| 679 | M2726/12    | Receptacle, Electrical, 3 - Pin Grounded, 40 - Ampere, 450 - Volt, Alternating Current (Symbol Nos. 1141.1 and 1141.2)                                             | MIL-DTL-2726            | MIL-DTL-2726/12        |
| 680 | M2726/13    | Receptacle, Cap Assembly, Electrical (Symbol No. 1142.1)                                                                                                           | MIL-DTL-2726            | MIL-DTL-2726/13        |
| 681 | M2726/14    | Receptacle, Electrical, Enclosed, 3-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol Nos. 1145.1, 1145.2 and 1145.3)                                 | MIL-DTL-2726            | MIL-DTL-2726/14        |
| 682 | M2726/15    | Receptacle, Electrical, Enclosed, 3 - Pin Grounded, 50 - Ampere, 250-Volt, Direct Current (Symbol Nos. 1146.1, 1146.2 and 1146.3)                                  | MIL-DTL-2726            | MIL-DTL-2726/15        |

| No. | Part Number | Description                                                                                                                              | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 683 | M2726/16    | Receptacle, Electrical, Enclosed, 4 - Pin Grounded, 40 - Ampere, 450 - Volt, Alternating Current (Symbol Nos. 1147.1, 1147.2 and 1147.3) | MIL-DTL-2726            | MIL-DTL-2726/16        |
| 684 | M2726/17    | Receptacle, Electrical, Enclosed, 3 - Pin Grounded, 40 - Ampere, 125 - Volt, Alternating Current (Symbol Nos. 1148.1, 1148.2 and 1148.3) | MIL-DTL-2726            | MIL-DTL-2726/17        |
| 685 | M2726/18    | Receptacle, Electrical, Triple, 50 - Ampere, 250 - Volt, Direct Current, 3 - Pole Grounded (Symbol No. 1105.1)                           | MIL-DTL-2726            | MIL-DTL-2726/18        |
| 686 | M2726/19    | Receptacle with Switch, Electrical, 30-Ampere, 450-Volt, Alternating Current, 60-Hertz, 3-Phase, Interlocking, Ground (Symbol No. 915.1) | MIL-DTL-2726            | MIL-DTL-2726/19        |
| 687 | M2726/20    | Receptacle with Switch, Electrical, 30-Ampere, 450-Volt, 1-Phase, Interlocking, Grounded (Symbol No. 916.1)                              | MIL-DTL-2726            | MIL-DTL-2726/20        |
| 688 | M2726/21    | Receptacle with Switch, Electrical, 30 - Ampere, 250 - Volt, Direct Current, Interlocking, Grounded (Symbol No. 917.1)                   | MIL-DTL-2726            | MIL-DTL-2726/21        |
| 689 | M2726/22    | Receptacle, Outlet, Electrical, Welding, 200 - Ampere, Direct Current, Constant Potential (Symbol No. 770.2)                             | MIL-DTL-2726            | MIL-DTL-2726/22        |
| 690 | M2726/23    | Receptacle, Electrical, enclosed, 100 - Ampere, 250 - Volt, Direct Current, Bulkhead Mounted (Symbol No. 726.1)                          | MIL-DTL-2726            | MIL-DTL-2726/23        |
| 691 | M2726/24    | Receptacle, Plug, Electrical, Connector, 25 - Ampere, 500 - Volt, 3- Phase Grounded (Symbol No. 707.1)                                   | MIL-DTL-2726            | MIL-DTL-2726/24        |
| 692 | M2726/25    | Receptacle, Electrical, Connector, 25-Ampere, 500-Volt, 3-Phase Grounded (Symbol No. 722.1)                                              | MIL-DTL-2726            | MIL-DTL-2726/25        |
| 693 | M2726/26    | Receptacle, Plug, Electrical 4 - Pin, 60 - Ampere, 208/117 - Volt, 3 - Phase Grounded (Symbol No. 728.1)                                 | MIL-DTL-2726            | MIL-DTL-2726/26        |
| 694 | M2726/27    | Receptacle with Switch, Electrical, 60 - Ampere, 208/117 - Volt, 3- Phase, Interlocking, Grounded (Symbol No. 776.1)                     | MIL-DTL-2726            | MIL-DTL-2726/27        |
| 695 | M2726/28    | Receptacle, Electrical, 4 - Pole Grounded, 100 - Ampere, 450 - Volt, 3 - Phase (Symbol No. 1221)                                         | MIL-DTL-2726            | MIL-DTL-2726/28        |
| 696 | M2726/29    | Receptacle, Plug, Electrical, 4 Pole Grounded, 100 - Ampere, 450 Volt, 3 - Phase (Symbol No. 1222)                                       | MIL-DTL-2726            | MIL-DTL-2726/29        |
| 697 | M2726/30    | Receptacle, Plug, Electrical, 10-Ampere, 125-Volt, Single Pole, Male (Symbol No. 727.1 - Red; Symbol No. 727.2 - Black)                  | MIL-DTL-2726            | MIL-DTL-2726/30        |

| No. | Part Number | Description                                                                                                                               | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 698 | M2726/31    | Receptacle, Plug, Electrical 10 - Ampere, 125 - Volt, Double Pole, Male (Symbol No. 729.1)                                                | MIL-DTL-2726            | MIL-DTL-2726/31        |
| 699 | M2726/32    | Receptacle, Electrical, 10-Ampere, 125-Volt, Single Pole, Panel Mounted (Symbol No. 775.1 - Black; Symbol No. 775.2 - Red)                | MIL-DTL-2726            | MIL-DTL-2726/32        |
| 700 | M2726/33    | Receptacle, Plug, Electrical, 40-ampere, 125-Volt, Single Pole, Male (Symbol No. 1214.2 - Red; Symbol No. 1214.5 - Black)                 | MIL-DTL-2726            | MIL-DTL-2726/33        |
| 701 | M2726/34    | Receptacle, Plug, Electrical, 40 - Ampere, 125 Volt, Single Pole, Female Type (Symbol No. 1214.3 - Red; Symbol No. 1214.4 - Black)        | MIL-DTL-2726            | MIL-DTL-2726/34        |
| 702 | M2726/35    | Receptacle, Electrical, 40 - Ampere, 125 - Volt Single Pole, Panel Mounted, Female (Symbol No. 1213.2 - Red; Symbol No. 1213.4 - Black)   | MIL-DTL-2726            | MIL-DTL-2726/35        |
| 703 | M2726/36    | Receptacle, Electrical, 40 - Ampere, 125 - Volt, Single Pole, Panel Mounted, Male Type (Symbol No. 1213.3 Red; Symbol No. 1213.5 - Black) | MIL-DTL-2726            | MIL-DTL-2726/36        |
| 704 | M2726/37    | Receptacle, Electrical, 15 - Ampere, 125 - Volt, 60 Hertz, Bladed Type, Grounded (Symbol No. 1099.1)                                      | MIL-DTL-2726            | MIL-DTL-2726/37        |
| 705 | M2726/38    | Receptacle, Plug, Electrical, 15 - Ampere, 125 - Volt, Bladed Type, Grounded (Symbol No. 1218.3)                                          | MIL-DTL-2726            | MIL-DTL-2726/38        |
| 706 | M2726/39    | Receptacle and Switch, Electrical, 15 - Ampere, 125 - Volt, Bladed Types, Grounded (Symbol No. 919)                                       | MIL-DTL-2726            | MIL-DTL-2726/39        |
| 707 | M2726/40    | Receptacle Channel, Electrical, 15 - Ampere, 125 - Volt, Bladed Type, Grounded (Symbol No. 730.4)                                         | MIL-DTL-2726            | MIL-DTL-2726/40        |
| 708 | M2726/41    | Receptacle, Electrical, Enclosed, 15-Ampere, 125-Volt, (Symbol No. 1098.1)                                                                | MIL-DTL-2726            | MIL-DTL-2726/41        |
| 709 | M2726/42    | Receptacle, Electrical, Enclosed, 60 - Ampere, 500 - Volt, 3 - Phase, Grounded (Symbol No. 746.2)                                         | MIL-DTL-2726            | MIL-DTL-2726/42        |
| 710 | M2726/43    | Receptacle, Electrical, (Bladed) 15-Ampere with 3-Ampere Switch, Type DPST, 125-Volt, Grounded, Totally Enclosed (Symbol 918.1)           | MIL-DTL-2726            | MIL-DTL-2726/43        |
| 711 | M2726/44    | Receptacle, Portable Triple Outlet, Electrical, 60 - Ampere, 500 - Volt, 3 - Phase Grounded (Symbol No. 765.3)                            | MIL-DTL-2726            | MIL-DTL-2726/44        |
| 712 | M2726/45    | Receptacle, Outlet Switch, Electrical, 100 - Ampere, 125 - Volt, 60 -Ampere, 250 - Volt, Interlocking, Grounded (Symbol No. 772.1)        | MIL-DTL-2726            | MIL-DTL-2726/45        |
| 713 | M2726/46    | Receptacle, Plug, Electrical, 100-Ampere, 250 - Volt, Direct Current, 3-Pole (Symbol No. 721.1)                                           | MIL-DTL-2726            | MIL-DTL-2726/46        |

| No. | Part Number | Description                                                                                                                                                               | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 714 | M2726/47    | Receptacle, Electrical, Enclosed, 15-Ampere, 125-Volt 2-Pole, Grounded (Symbol No. 735.3)                                                                                 | MIL-DTL-2726            | MIL-DTL-2726/47        |
| 715 | M2726/48    | Receptacle and Switch, Electrical, Enclosed, 15-Ampere, 125-Volt, Interlocking, Grounded (Symbol No. 900.1)                                                               | MIL-DTL-2726            | MIL-DTL-2726/48        |
| 716 | M2726/49    | Receptacle, Outlet, Triple, Electrical, 40 - Ampere, 450 - Volt, 60 Hertz, Alternating Current, 4 - Pole, Portable, Plastic Grounded (Symbol Nos. 765.6, 765.7 and 765.8) | MIL-DTL-2726            | MIL-DTL-2726/49        |
| 717 | M2726/50    | Receptacle, Plug, Electrical, 15-Ampere, 125/250-Volts, 2-Pole, Grounded (Symbol No. 720.3)                                                                               | MIL-DTL-2726            | MIL-DTL-2726/50        |
| 718 | M2726/51    | Receptacle, Adapter, Electrical, 15-Ampere, 125-Volt, Alternating Current, Grounded (Symbol No. 2440.2)                                                                   | MIL-DTL-2726            | MIL-DTL-2726/51        |
| 719 | M2726/52    | Receptacle, Plug, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Single Phase (Symbol No. 1257)                                                               | MIL-DTL-2726            | MIL-DTL-2726/52        |
| 720 | M2726/53    | Receptacle, Plug, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, 3-Phase (Symbol No. 1258)                                                                    | MIL-DTL-2726            | MIL-DTL-2726/53        |
| 721 | M2726/54    | Receptacle, Plug, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 400 Hertz, Single Phase (Symbol No. 1259)                                                              | MIL-DTL-2726            | MIL-DTL-2726/54        |
| 722 | M2726/55    | Receptacle, Plug, Electrical, 4-Pin Grounded, 10-Ampere,, 450-Volt, 400-Hertz, 3-Phase (Symbol No.1260)                                                                   | MIL-DTL-2726            | MIL-DTL-2726/55        |
| 723 | M2726/56    | Receptacle, Plug, Electrical, 4-Pole Grounded, 60-Ampere, 450-Volt, 3-Phase (Symbol No. 1261)                                                                             | MIL-DTL-2726            | MIL-DTL-2726/56        |
| 724 | M2726/57    | Receptacle, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Single Phase (Symbol No. 1262)                                                                     | MIL-DTL-2726            | MIL-DTL-2726/57        |
| 725 | M2726/58    | Receptacle, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Alternating Current (Symbol No. 1263)                                                              | MIL-DTL-2726            | MIL-DTL-2726/58        |
| 726 | M2726/59    | Receptacle, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 400 Hertz, Single Phase (Symbol No. 1264)                                                                    | MIL-DTL-2726            | MIL-DTL-2726/59        |
| 727 | M2726/60    | Receptacle, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 400 Hertz, 3-Phase (Symbol No. 1265)                                                                         | MIL-DTL-2726            | MIL-DTL-2726/60        |
| 728 | M2726/61    | Receptacle, Electrical, 4-Pole Grounded, 60-Ampere, 450-Volt, 3-Phase (Symbol No. 1266)                                                                                   | MIL-DTL-2726            | MIL-DTL-2726/61        |

| No. | Part Number | Description                                                                                                                                                | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 729 | M2726/62    | Receptacle, Electrical, Enclosed 3-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz Single Phase (Symbol No. 1267)                                              | MIL-DTL-2726            | MIL-DTL-2726/62        |
| 730 | M2726/63    | Receptacle, Electrical, Enclosed 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz Alternating Current (Symbol No. 1268)                                       | MIL-DTL-2726            | MIL-DTL-2726/63        |
| 731 | M2726/64    | Receptacle, Electrical, Enclosed, 3-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz Single-Phase (Symbol No. 1269)                                            | MIL-DTL-2726            | MIL-DTL-2726/64        |
| 732 | M2726/65    | Receptacle, Electrical, Enclosed, 4-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, 3-Phase (Symbol No. 1272)                                                | MIL-DTL-2726            | MIL-DTL-2726/65        |
| 733 | M2726/66    | RECEPTACLE, ELECTRICAL, TOTALLY ENCLOSED, 15-AMPERE, 125-VOLT, 60-HERTZ, BLADED TYPE, GROUNDED (SYMBOL NO. 730.1)                                          | MIL-DTL-2726            | MIL-DTL-2726/66        |
| 734 | M2726/67    | Receptacle, Electrical, Enclosed, 10-Ampere, 125-Volt, 3-Phase, Grounded (Symbol No. 741.2)                                                                | MIL-DTL-2726            | MIL-DTL-2726/67        |
| 735 | M2726/68    | Receptacle, Plug, Connector, Electrical, 10-Ampere, 125-Volt, 3-Phase, Grounded (Symbol No. 706.1)                                                         | MIL-DTL-2726            | MIL-DTL-2726/68        |
| 736 | M2726/69    | Receptacle, Outlet, Triple, Electrical, Portable, 15-Ampere, 125-Volt Alternating Current, Double Pole, Grounded, 25-Foot Cable Extension (Symbol No. 779) | MIL-DTL-2726            | MIL-DTL-2726/69        |
| 737 | M2726/70    | Receptacle, Electrical, Totally Enclosed, 15-Ampere, 125-Volt, 400-Hertz, Bladed Type, Single Phase, Grounded (Symbol No. 1100)                            | MIL-DTL-2726            | MIL-DTL-2726/70        |
| 738 | M2726/71    | RECEPTACLE, ELECTRICAL, WATERTIGHT, 15-AMPERE, 125 VOLT, 400-HERTZ, BLADED TYPE, SINGLE PHASE, GROUNDED (SYMBOL NO. 1101)                                  | MIL-DTL-2726            | MIL-DTL-2726/71        |
| 739 | M2726/72    | Receptacle, Adapter, Electrical, 15-Ampere, 125-Volt, Alternating Current, 60 to 400-Hertz Grounded (Symbol No. 2439)                                      | MIL-DTL-2726            | MIL-DTL-2726/72        |
| 740 | M2726/73    | Receptacle, Electrical, 15-Ampere, 125-Volt, Bladed Type, Grounded (Portable) (Symbol No. 1215)                                                            | MIL-DTL-2726            | MIL-DTL-2726/73        |
| 741 | M3655/1     | Connector, Plug, Electrical, Class I (Coaxial, Series Twin) Type UG-421B/U                                                                                 | MIL-DTL-3655            | MIL-DTL-3655/1         |
| 742 | M3655/2     | Connector, Receptacle, Electrical, Class I (Coaxial, Series Twin) Type UG-422/U                                                                            | MIL-DTL-3655            | MIL-DTL-3655/2         |
| 743 | M3655/3     | Connector, Receptacle, Electrical, Class I (Coaxial, Series Twin) Type UG-423B/U                                                                           | MIL-DTL-3655            | MIL-DTL-3655/3         |
| 744 | M3655/4     | Connector, Adapter, Electrical, Class I (Coaxial, Series Twin) Type UG-493A/U                                                                              | MIL-DTL-3655            | MIL-DTL-3655/4         |
| 745 | M3655/5     | Connector, Adapter, Electrical, Class I (Coaxial, Series Twin) Type UG-981/U                                                                               | MIL-DTL-3655            | MIL-DTL-3655/5         |
| 746 | M3655/6     | Connector, Receptacle, Electrical, Class II (Coaxial, Series Twin) Type UG-1057/U                                                                          | MIL-DTL-3655            | MIL-DTL-3655/6         |

| No. | Part Number | Description                                                                                                                 | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 747 | M3655/7     | Connector Adapter, Class II (Coaxial, Series Twin), Type UG-1058/U                                                          | MIL-DTL-3655            | MIL-DTL-3655/7         |
| 748 | M3655/8     | Connector, Adapter, Electrical, Class II (Coaxial, Series Twin) Type UG-1059/U                                              | MIL-DTL-3655            | MIL-DTL-3655/8         |
| 749 | M3655/9     | Connector, Plug, Electrical, Class I (Coaxial, Series Twin) Type UG-1060A/U                                                 | MIL-DTL-3655            | MIL-DTL-3655/9         |
| 750 | M3655/10    | Connector, Shield, Electrical, Class I (Coaxial, Series Twin) Type MX-1556/U                                                | MIL-DTL-3655            | MIL-DTL-3655/10        |
| 751 | M3655/11    | Connector, Shield, Electrical, Class I (Coaxial, Series Twin) Type UG-106/U                                                 | MIL-DTL-3655            | MIL-DTL-3655/11        |
| 752 | M3655/12    | Connector, Plug, Electrical, Class I (Coaxial, Series Twin), Type UG-1253/U                                                 | MIL-DTL-3655            | MIL-DTL-3655/12        |
| 753 | M3655/13    | Connector, Receptacle, Electrical, Class I (Coaxial, Series Twin, TWTNC, Jam Nut Mounted)                                   | MIL-DTL-3655            | MIL-DTL-3655/13        |
| 754 | M3655/14    | Connector, Plug, Electrical, Class I (Coaxial, Series Twin, TWTNC)                                                          | MIL-DTL-3655            | MIL-DTL-3655/14        |
| 755 | M3655/15    | Connector, Plug, Electrical, Class I (Coaxial, Series Twin, TWBNC)                                                          | MIL-DTL-3655            | MIL-DTL-3655/15        |
| 756 | M3655/16    | Connector, Receptacle, Electrical, Class I (Coaxial, Series Twin, TWBNC)                                                    | MIL-DTL-3655            | MIL-DTL-3655/16        |
| 757 | M3655/17    | Connector, Plug, Electrical, Class I (Coaxial, Series Twin, TWTNC, Right Angle)                                             | MIL-DTL-3655            | MIL-DTL-3655/17        |
| 758 | M3655/18    | Connector, Plug Electrical, Class 1, (Coaxial, Series Twin, TWSMC)                                                          | MIL-DTL-3655            | MIL-DTL-3655/18        |
| 759 | M3655/19    | Connector, Plug, Electrical, Class 1, (Coaxial, Series Twin, TWSMC)                                                         | MIL-DTL-3655            | MIL-DTL-3655/19        |
| 760 | M3655/20    | Connector, Plug, Electrical, Class 1, (Coaxial, Series Twin, TWSM)                                                          | MIL-DTL-3655            | MIL-DTL-3655/20        |
| 761 | M3655/21    | Connector, Plug, Electrical, Class 1, (Coaxial, Series Twin TWSM)                                                           | MIL-DTL-3655            | MIL-DTL-3655/21        |
| 762 | M3655/22    | Connector, Receptacle, Electrical, Class I (Coaxial, Series Twin, TWTNC, Bulkhead)                                          | MIL-DTL-3655            | MIL-DTL-3655/22        |
| 763 | M3655/23    | Connector, Receptacle, Electrical, Class I, (Coaxial, Series Twin, TWBNC, Bulkhead)                                         | MIL-DTL-3655            | MIL-DTL-3655/23        |
| 764 | M21617/1    | Connector, Female Plug Electrical, Rectanglar, Polarized Shell, Miniature Type, Socket Contacts (Style 004A)                | MIL-DTL-21617           | MIL-DTL-21617/1        |
| 765 | M21617/2    | Connector, Male Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Pin Contacts (Style 004A)               | MIL-DTL-21617           | MIL-DTL-21617/2        |
| 766 | M21617/3    | Connector, Male Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 004A)  | MIL-DTL-21617           | MIL-DTL-21617/3        |
| 767 | M21617/4    | Connector, Female Plug Electrical, Rectangular, POLARIZED Shell, Miniature Type, Socket Contacts (Style 008A)               | MIL-DTL-21617           | MIL-DTL-21617/4        |
| 768 | M21617/5    | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 008A)              | MIL-DTL-21617           | MIL-DTL-21617/5        |
| 769 | M21617/6    | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 008A) | MIL-DTL-21617           | MIL-DTL-21617/6        |

| No. | Part Number | Description                                                                                                                      | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 770 | M21617/7    | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Socket Contacts (Style 013A)                    | MIL-DTL-21617           | MIL-DTL-21617/7        |
| 771 | M21617/8    | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 013A)                   | MIL-DTL-21617           | MIL-DTL-21617/8        |
| 772 | M21617/9    | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 013A)      | MIL-DTL-21617           | MIL-DTL-21617/9        |
| 773 | M21617/10   | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Socket Contacts (Style 017A)                    | MIL-DTL-21617           | MIL-DTL-21617/10       |
| 774 | M21617/11   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 017A)                   | MIL-DTL-21617           | MIL-DTL-21617/11       |
| 775 | M21617/12   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized Type (Style 017A) | MIL-DTL-21617           | MIL-DTL-21617/12       |
| 776 | M21617/13   | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Socket Contacts (Style 023A)                    | MIL-DTL-21617           | MIL-DTL-21617/13       |
| 777 | M21617/14   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 023A)                   | MIL-DTL-21617           | MIL-DTL-21617/14       |
| 778 | M21617/15   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 023A)      | MIL-DTL-21617           | MIL-DTL-21617/15       |
| 779 | M21617/16   | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Socket Contacts (Style 026A)                    | MIL-DTL-21617           | MIL-DTL-21617/16       |
| 780 | M21617/17   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 026A)                   | MIL-DTL-21617           | MIL-DTL-21617/17       |
| 781 | M21617/18   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 026A)      | MIL-DTL-21617           | MIL-DTL-21617/18       |
| 782 | M21617/19   | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Socket Contacts (Style 032A)                    | MIL-DTL-21617           | MIL-DTL-21617/19       |
| 783 | M21617/20   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts (Style 032A)                   | MIL-DTL-21617           | MIL-DTL-21617/20       |
| 784 | M21617/21   | Connector, Male Receptacle Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 032A)      | MIL-DTL-21617           | MIL-DTL-21617/21       |

| No. | Part Number | Description                                                                                                                         | Governing Specification | Detailed Specification |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 785 | M21617/22   | Connector, Female Plug Electrical, Rectanglar, Polarized Shell, Miniature Type, Socket Contacts (Style 040A)                        | MIL-DTL-21617           | MIL-DTL-21617/22       |
| 786 | M21617/23   | Connector, Male Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Pin Contacts (Style 040A)                       | MIL-DTL-21617           | MIL-DTL-21617/23       |
| 787 | M21617/24   | Connector, Male Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Pin Contacts, Pressurized (Style 040A)          | MIL-DTL-21617           | MIL-DTL-21617/24       |
| 788 | M21617/25   | Connector, Female Plug Electrical, Rectanglar, Polarized Shell, Miniature Type, Socket Coaxial Contacts (STYLE 007C)                | MIL-DTL-21617           | MIL-DTL-21617/25       |
| 789 | M21617/26   | Connector, Male Electrical, Rectangular, Polarized Shell, Miniature Type, Pin Coaxial Contacts (Style 007C)                         | MIL-DTL-21617           | MIL-DTL-21617/26       |
| 790 | M21617/27   | Connector, Female Plug Electrical, Rectangular, Polarized Shell, Miniature Type, Mixed Socket Contacts (Style 016C)                 | MIL-DTL-21617           | MIL-DTL-21617/27       |
| 791 | M21617/28   | Connector, Male Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Mixed Pin Contacts (Style 016C)                 | MIL-DTL-21617           | MIL-DTL-21617/28       |
| 792 | M21617/29   | Connector, Receptacle Electrical, Rectanglar, Polarized Shell, Miniature Type, Back Shells                                          | MIL-DTL-21617           | MIL-DTL-21617/29       |
| 793 | M32139/1    | Connectors, Electrical, Rectangular, Nanominiature, Single Row, Plug, Polarized Shell, Pin Contacts, Crimp Type                     | MIL-DTL-32139           | MIL-DTL-32139/1        |
| 794 | M32139/2    | Connectors, Electrical, Rectangular, Nanominiature, Single Row, Receptacle, Polarized Shell, Socket Contacts, Crimp Type            | MIL-DTL-32139           | MIL-DTL-32139/2        |
| 795 | M32139/3    | Connectors, Electrical, Rectangular, Nanominiature, Dual Row, Plug, Polarized Shell, Pin Contacts, Crimp Type                       | MIL-DTL-32139           | MIL-DTL-32139/3        |
| 796 | M32139/4    | Connectors, Electrical, Rectangular, Nanominiature, Dual Row, Receptacle, Polarized Shell, Socket Contacts, Crimp Type              | MIL-DTL-32139           | MIL-DTL-32139/4        |
| 797 | M31031/1    | CONNECTOR, RECEPTACLE, ELECTRICAL, RADIO FREQUENCY, SERIES BMA, FLANGE MOUNT, FOR FLEXIBLE CABLE, SOCKET CONTACT, HIGH RELIABILITY  | MIL-PRF-31031           | MIL-PRF-31031/1        |
| 798 | M31031/2    | CONNECTOR, RECEPTACLE, ELECTRICAL, RADIO FREQUENCY, SERIES BMA, JAMNUT MOUNT, FOR FLEXIBLE CABLE, PIN CONTACT, HIGH RELIABILITY     | MIL-PRF-31031           | MIL-PRF-31031/2        |
| 799 | M31031/11   | CONNECTOR, RECEPTACLE, ELECTRICAL, RADIO FREQUENCY, SERIES BMA, FLANGE MOUNT, FOR SEMIRIGID CABLE, SOCKET CONTACT, HIGH RELIABILITY | MIL-PRF-31031           | MIL-PRF-31031/11       |

| No. | Part Number | Description                                                                                                                              | Governing Specification | Detailed Specification |
|-----|-------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 800 | M31031/12   | Connector, Receptacle, Electrical, Radio Frequency, Series BMA, Jamnut Mount, for Semirigid Cable, Pin Contact, High Reliability         | MIL-PRF-31031           | MIL-PRF-31031/12       |
| 801 | M31031/30   | Connector, Electrical, Coaxial, Radio Frequency, Socket Contact, Series SMP to SMP, Shroud, 2 Hole Flange                                | MIL-PRF-31031           | MIL-PRF-31031/30       |
| 802 | M31031/31   | Connector, Electrical, Coaxial, Radio Frequency, Socket Contact, Series SMP, for .047 and .086 Semirigid Cable                           | MIL-PRF-31031           | MIL-PRF-31031/31       |
| 803 | M31031/32   | Connector, Electrical, Coaxial, Radio Frequency, Socket Contact, Series SMP, for .047 and .086 Semirigid Cable, Right Angle              | MIL-PRF-31031           | MIL-PRF-31031/32       |
| 804 | M31031/40   | Connector, Electrical, Receptacle, Radio Frequency, High Reliability, Coaxial, Series BMZ, Socket Contact, for Flexible Cable            | MIL-PRF-31031           | MIL-PRF-31031/40       |
| 805 | M31031/41   | Connector, Electrical, Receptacle, Radio Frequency, High Reliability, Coaxial, Series BMZ, Pin Contact, for Flexible Cable               | MIL-PRF-31031           | MIL-PRF-31031/41       |
| 806 | M31031/42   | Connector, Electrical, Receptacle, Radio Frequency, High Reliability, Coaxial, Series BMZ, Socket Contact, for Semirigid Cable           | MIL-PRF-31031           | MIL-PRF-31031/42       |
| 807 | M31031/43   | Connector, Electrical, Receptacle, Radio Frequency, High Reliability, Coaxial, Series BMZ, Right Angle, Pin Contact, for Semirigid Cable | MIL-PRF-31031           | MIL-PRF-31031/43       |
| 808 | M31031/44   | Connector, Electrical, Receptacle, Radio Frequency, High Reliability, Coaxial, Series BMZ, Pin Contact, for Semirigid Cable              | MIL-PRF-31031           | MIL-PRF-31031/44       |
| 809 | M39012/1    | Connectors, Plug, Electrical, Coaxial, Radio Frequency, (Series N (Cabled), Pin Contact, Class 2)                                        | MIL-PRF-39012           | MIL-PRF-39012/1        |
| 810 | M39012/2    | Connectors, Plugs and Receptacles, Electrical, Coaxial, Radio Frequency, (Series TNC (Cabled), Flange Mounted, Socket Contact, Class 2)  | MIL-PRF-39012           | MIL-PRF-39012/2        |
| 811 | M39012/3    | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency (Series N (Cabled), Jam Nut Mounted, Socket Contact, Class 2)              | MIL-PRF-39012           | MIL-PRF-39012/3        |
| 812 | M39012/4    | Connectors, Coaxial, Radio Frequency (Series N (Uncabled) - Receptacles - Jam Nut and Flange Mounted, Socket Contact, Class 2)           | MIL-PRF-39012           | MIL-PRF-39012/4        |
| 813 | M39012/5    | Connectors, Plug, Electrical, Coaxial, Radio Frequency (Series N (Cabled), Right Angle, Pin Contact, Class 2)                            | MIL-PRF-39012           | MIL-PRF-39012/5        |
| 814 | M39012/6    | Connectors, Plug, Electrical, Coaxial, Radio Frequency, (Series C, (Cabled), Male, Class 2)                                              | MIL-PRF-39012           | MIL-PRF-39012/6        |

| No. | Part Number | Description                                                                                                                            | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 815 | M39012/7    | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (SERIES C (CABLED), FEMALE, CLASS 2 )                                          | MIL-PRF-39012           | MIL-PRF-39012/7        |
| 816 | M39012/8    | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (SERIES C, (CABLED), FEMALE, FLANGE MOUNTED, REAR MOUNTED, CLASS 2 )     | MIL-PRF-39012           | MIL-PRF-39012/8        |
| 817 | M39012/9    | Connector, Coaxial, Radio Frequency Series C (Cabled Receptacle, Female, Jam Nut, Front Mounted, Class 2)                              | MIL-PRF-39012           | MIL-PRF-39012/9        |
| 818 | M39012/10   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, (Series C, (Cabled), Male, Right Angle, Class 2)                               | MIL-PRF-39012           | MIL-PRF-39012/10       |
| 819 | M39012/11   | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (SERIES C, (CABLE) FEMALE, JAM NUT, REAR MOUNTED, PRESSURIZED, CLASS 2 ) | MIL-PRF-39012           | MIL-PRF-39012/11       |
| 820 | M39012/12   | CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES C (UNCABLED-RECEPTACLE, FEMALE, FLANGE MOUNTED, REAR MOUNTED, CLASS 2)                    | MIL-PRF-39012           | MIL-PRF-39012/12       |
| 821 | M39012/13   | CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES C (UNCABLED-RECEPTACLE, FEMALE, JAM NUT MOUNTED, FRONT MOUNTED, PRESSURIZED, CLASS 2)     | MIL-PRF-39012           | MIL-PRF-39012/13       |
| 822 | M39012/14   | CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES C (UNCABLED-RECEPTACLE, FEMALE, JAM NUT MOUNTED, HERMETIC SEAL, CLASS 2)                  | MIL-PRF-39012           | MIL-PRF-39012/14       |
| 823 | M39012/15   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, (Series C, (Cabled) Male, Class 2 )                                            | MIL-PRF-39012           | MIL-PRF-39012/15       |
| 824 | M39012/16   | Connectors, Plugs, Electrical, Coaxial Radio Frequency, (Series BNC (Cabled), Pin Contact, Class 2)                                    | MIL-PRF-39012           | MIL-PRF-39012/16       |
| 825 | M39012/17   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, (Series BNC, (Cabled), Socket Contact, Class 2)                               | MIL-PRF-39012           | MIL-PRF-39012/17       |
| 826 | M39012/18   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, (Series BNC, (Cabled), Socket Contact, Flange Mounted, Class 2)          | MIL-PRF-39012           | MIL-PRF-39012/18       |
| 827 | M39012/19   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, (Series BNC (Cabled), Socket Contact, Jam Nut Mounted, Class 2)          | MIL-PRF-39012           | MIL-PRF-39012/19       |
| 828 | M39012/20   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, (Series BNC (Cabled), Pin Contact, Right Angle, Class 2)                       | MIL-PRF-39012           | MIL-PRF-39012/20       |
| 829 | M39012/21   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, (Series BNC (Uncabled), Socket Contact, Jam Nut Mounted, Class 2)        | MIL-PRF-39012           | MIL-PRF-39012/21       |

| No. | Part Number | Description                                                                                                                                      | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 830 | M39012/22   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, (Series BNC (Uncabled), Socket Contact, Flange Mounted, Class 2)                  | MIL-PRF-39012           | MIL-PRF-39012/22       |
| 831 | M39012/23   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, (Series BNC (Uncabled), Socket Contact, Right Angle, Class 2)                     | MIL-PRF-39012           | MIL-PRF-39012/23       |
| 832 | M39012/24   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, (Series BNC (Uncabled), Socket Contact, Hermetic Sealed, Jam Nut Mounted, Class 2) | MIL-PRF-39012           | MIL-PRF-39012/24       |
| 833 | M39012/25   | Connectors, Coaxial, Radio Frequency, (Hardware for Radio Frequency Coaxial Connectors)                                                          | MIL-PRF-39012           | MIL-PRF-39012/25       |
| 834 | M39012/26   | Connectors, Plugs, Electrical, Coaxial Radio Frequency, (Series TNC (Cabled), Pin Contact, Class 2)                                              | MIL-PRF-39012           | MIL-PRF-39012/26       |
| 835 | M39012/27   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, (Series TNC, (Cabled), Socket Contact, Class 2)                                         | MIL-PRF-39012           | MIL-PRF-39012/27       |
| 836 | M39012/28   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, (Series TNC, (Cabled), Socket Contact, Jam Nut Mounted, Class 2)                  | MIL-PRF-39012           | MIL-PRF-39012/28       |
| 837 | M39012/29   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, (Series TNC, (Cabled), Socket Contact, Flange Mounted, Class 2)                    | MIL-PRF-39012           | MIL-PRF-39012/29       |
| 838 | M39012/30   | Connectors, Plugs, Electrical, Coaxial Radio Frequency, (Series TNC (Cabled), Pin Contact, Right Angle, Class 2)                                 | MIL-PRF-39012           | MIL-PRF-39012/30       |
| 839 | M39012/31   | Connectors, Coaxial, Radio Frequency (Series TNC (Uncabled - Receptacles, Socket, Jam Nut Mounted, Class 2)                                      | MIL-PRF-39012           | MIL-PRF-39012/31       |
| 840 | M39012/32   | CONNECTORS, COAXIAL, RADIO FREQUENCY SERIES TNC (UNCABLED - RECEPTACLE, SOCKET, FLANGE MOUNTED, CLASS 2)                                         | MIL-PRF-39012           | MIL-PRF-39012/32       |
| 841 | M39012/33   | Connectors, Coaxial, Radio Frequency, Series TNC (Uncabled-Receptacle, Socket, Right Angle, Class 2)                                             | MIL-PRF-39012           | MIL-PRF-39012/33       |
| 842 | M39012/34   | Connectors, Coaxial, Radio Frequency Series INC (Uncabled - Receptacle, Socket, Hermetic Sealed, Jam Nut Mounted, Class 2)                       | MIL-PRF-39012           | MIL-PRF-39012/34       |
| 843 | M39012/35   | Connectors, Plug, Electrical, Coaxial, Radio Frequency (Series SC (Cabled), Pin Contact, Class 2)                                                | MIL-PRF-39012           | MIL-PRF-39012/35       |
| 844 | M39012/36   | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES SC, (CABLED), SOCKET CONTACT, CLASS 2) (NO S/S DOCUMENT)                          | MIL-PRF-39012           | MIL-PRF-39012/36       |

| No. | Part Number | Description                                                                                                                                      | Governing Specification | Detailed Specification |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 845 | M39012/37   | Connector, Coaxial, Radio Frequency Series SC (Cabled-Receptacle, Female, Jam Nut, Front Mounted, Class 2) (No S/S Document)                     | MIL-PRF-39012           | MIL-PRF-39012/37       |
| 846 | M39012/38   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency (Series SC (Cabled), Socket Contact, Flange Mounted, Rear Mounted, Class 2)         | MIL-PRF-39012           | MIL-PRF-39012/38       |
| 847 | M39012/39   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency (Series SC (Cabled), Pin Contact, Right Angle, Class 2)                                  | MIL-PRF-39012           | MIL-PRF-39012/39       |
| 848 | M39012/40   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency (Series SC (Cabled), Socket Contact, Jam Nut, Rear Mounted, Class 2)                | MIL-PRF-39012           | MIL-PRF-39012/40       |
| 849 | M39012/41   | Connectors, Coaxial, Radio Frequency, Series SC (Uncabled-Receptacle, Female, Flange, Rear Mounted, Class 2) (No S/S Document)                   | MIL-PRF-39012           | MIL-PRF-39012/41       |
| 850 | M39012/42   | Connectors, Coaxial, Radio Frequency, Series SC (Uncabled - Receptacle, Female, Jam Nut Mounted, Front Mounted, Class 2) (No S/S Document)       | MIL-PRF-39012           | MIL-PRF-39012/42       |
| 851 | M39012/43   | Connector, Coaxial, Radio Frequency Series SC (Uncabled - Receptacle, Female, Jam Nut Mounted, Rear Mounted, Class 2)                            | MIL-PRF-39012           | MIL-PRF-39012/43       |
| 852 | M39012/44   | Connector, Plug, Electrical, Coaxial, Radio Frequency, (Series QL (Cabled), Male, Class 2) (No S/S Document)                                     | MIL-PRF-39012           | MIL-PRF-39012/44       |
| 853 | M39012/45   | Connector, Receptacle, Electrical, Coaxial, Radio Frequency, (Series QL, (Cabled), Female, Jam Nut Mounted, Class 2) (No S/S Document)           | MIL-PRF-39012           | MIL-PRF-39012/45       |
| 854 | M39012/46   | Connector, Plug, Electrical, Coaxial, Radio Frequency, (Series QL (Cabled), Male, Right Angle, Class 2) (No S/S Document)                        | MIL-PRF-39012           | MIL-PRF-39012/46       |
| 855 | M39012/47   | Connector, Coaxial, Radio Frequency, Series QL, (Uncabled Receptacle, Female, Jam Nut Mounted, with Solder Terminals, Class 2) (No S/S Document) | MIL-PRF-39012           | MIL-PRF-39012/47       |
| 856 | M39012/48   | Connector, Coaxial, Radio Frequency, Series QM, (Cabled Plug, Male, Class 2) (No S/S Document)                                                   | MIL-PRF-39012           | MIL-PRF-39012/48       |
| 857 | M39012/49   | Connector, Coaxial, Radio Frequency Series QM, (Cabled Receptacle, Female, Bulkhead, Class 2) (No S/S Document)                                  | MIL-PRF-39012           | MIL-PRF-39012/49       |
| 858 | M39012/55   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency (Series SMA (Cabled) - Plug, Pin Contact, Class 2)                                       | MIL-PRF-39012           | MIL-PRF-39012/55       |
| 859 | M39012/56   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency (Series SMA (Cabled) - Plug, Pin Contact, Right Angle, Class 2)                          | MIL-PRF-39012           | MIL-PRF-39012/56       |

| No. | Part Number | Description                                                                                                                                   | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 860 | M39012/57   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, (Series SMA (Cabled) - Socket Contact, Class 2)                                      | MIL-PRF-39012           | MIL-PRF-39012/57       |
| 861 | M39012/58   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, (Series SMA (Cabled) - Socket Contact, Flange Mounted Class 2)                 | MIL-PRF-39012           | MIL-PRF-39012/58       |
| 862 | M39012/59   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, (Series SMA (Cabled) - Socket Contact, Jam Nut Mounted Class 2)                | MIL-PRF-39012           | MIL-PRF-39012/59       |
| 863 | M39012/60   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency Series SMA (Uncabled, Socket Contact, Flange Mounted, Class 2)                  | MIL-PRF-39012           | MIL-PRF-39012/60       |
| 864 | M39012/61   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, Series SMA (Uncabled, Socket Contact, Jam Nut Mounted, Class 2)                | MIL-PRF-39012           | MIL-PRF-39012/61       |
| 865 | M39012/62   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, Series SMA (Uncabled, Socket Contact, Jam Nut Mounted, Hermetic Seal, Class 2) | MIL-PRF-39012           | MIL-PRF-39012/62       |
| 866 | M39012/63   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series QSC (Cabled, Pin Contact, Class 2) (No S/S Document)                          | MIL-PRF-39012           | MIL-PRF-39012/63       |
| 867 | M39012/64   | Connector, Plug, Electrical, Coaxial, Radio Frequency, Series QSC (Cabled, Socket Contact, Class 2) (No S/S Document)                         | MIL-PRF-39012           | MIL-PRF-39012/64       |
| 868 | M39012/65   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series QNC, (Cabled, Pin Contact, Class 2) (No S/S Document)                         | MIL-PRF-39012           | MIL-PRF-39012/65       |
| 869 | M39012/66   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series QNC, (Cabled, Socket Contact, Class 2) (No S/S Document)                      | MIL-PRF-39012           | MIL-PRF-39012/66       |
| 870 | M39012/67   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMB (Cabled, Socket Contact, Class 2)                                         | MIL-PRF-39012           | MIL-PRF-39012/67       |
| 871 | M39012/68   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMB (Cabled, Pin Contact, Class 2)                                            | MIL-PRF-39012           | MIL-PRF-39012/68       |
| 872 | M39012/69   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMB (Cabled, Socket Contact, Right Angle, Class 2)                            | MIL-PRF-39012           | MIL-PRF-39012/69       |
| 873 | M39012/70   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SMB (Cabled, Pin Contact, Jamnut Mounted, Rear Mounted, Class 2)         | MIL-PRF-39012           | MIL-PRF-39012/70       |
| 874 | M39012/71   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, Series SMB (Uncabled, Male, Jamnut Mounted, Class 2)                           | MIL-PRF-39012           | MIL-PRF-39012/71       |

| No. | Part Number | Description                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 875 | M39012/73   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMC (Cabled, Socket Contact, Class 2)                                                                 | MIL-PRF-39012           | MIL-PRF-39012/73       |
| 876 | M39012/74   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMC (Cabled, Pin Contact, Class 2)                                                                    | MIL-PRF-39012           | MIL-PRF-39012/74       |
| 877 | M39012/75   | Connectors, Plugs, Electrical, Coaxial, Radio Frequency, Series SMC (Cabled, Socket Contact, Right Angle, Class 2)                                                    | MIL-PRF-39012           | MIL-PRF-39012/75       |
| 878 | M39012/76   | Connectors, Receptacles, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled, Pin contact. Jamnut Mounted Rear Mounted, Class 2)                                 | MIL-PRF-39012           | MIL-PRF-39012/76       |
| 879 | M39012/77   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SMC (Uncabled, Male, Jam Nut Mounted, Class 2)                                                   | MIL-PRF-39012           | MIL-PRF-39012/77       |
| 880 | M39012/79   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled) Pin Contact, Class 2, Semirigid Cable                                                     | MIL-PRF-39012           | MIL-PRF-39012/79       |
| 881 | M39012/80   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled) Pin Contact, Right Angle, Class 2, Semirigid Cable                                        | MIL-PRF-39012           | MIL-PRF-39012/80       |
| 882 | M39012/81   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled, Semirigid) - Socket Contact, Class 2                                                      | MIL-PRF-39012           | MIL-PRF-39012/81       |
| 883 | M39012/82   | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled, Semirigid), Flange Mounted - Socket Contact, Class 2                                | MIL-PRF-39012           | MIL-PRF-39012/82       |
| 884 | M39012/83   | Connectors, Plug, Electrical, Coaxial, Radio Frequency, Series SMA (Cabled, Semirigid) - Jam Nut Mounted, Socket Contact, Class 2                                     | MIL-PRF-39012           | MIL-PRF-39012/83       |
| 885 | M39012/84   | CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QSC, (CABLED, PIN CONTACT, RIGHT ANGLE, CLASS2) (NO S/S DOCUMENT)                                     | MIL-PRF-39012           | MIL-PRF-39012/84       |
| 886 | M39012/85   | CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QSC, (CABLED, SOCKET CONTACT, JAM NUT MOUNTED, REAR MOUNTED, CLASS 2) (NO S/S DOCUMENT)         | MIL-PRF-39012           | MIL-PRF-39012/85       |
| 887 | M39012/86   | CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QSC, (CABLED, SOCKET CONTACT, JAM NUT, FRONT MOUNTED, CLASS 2) (NO S/S DOCUMENT)                | MIL-PRF-39012           | MIL-PRF-39012/86       |
| 888 | M39012/87   | CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES QSC (UNCABLED - RECEPTACLE, SOCKET CONTACT, HERMETIC SEALED, JAM NUT, FRONT AND REAR MOUNTED, CLASS 2) (NO S/S DOCUMENT) | MIL-PRF-39012           | MIL-PRF-39012/87       |

| No. | Part Number | Description                                                                                                                                                           | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 889 | M39012/88   | CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QNC, (CABLED, PIN CONTACT, RIGHT ANGLE, CLASS2) (NO S/S DOCUMENT)                                     | MIL-PRF-39012           | MIL-PRF-39012/88       |
| 890 | M39012/89   | CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QNC, (CABLED, SOCKET CONTACT, JAM NUT MOUNTED, CLASS 2) (NO S/S DOCUMENT)                       | MIL-PRF-39012           | MIL-PRF-39012/89       |
| 891 | M39012/90   | CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES QNC (UNCABLED) - RECEPTACLE, SOCKET CONTACT, JAM NUT, FRONT AND REAR MOUNTED, CLASS 2) (NO S/S DOCUMENT)                 | MIL-PRF-39012           | MIL-PRF-39012/90       |
| 892 | M39012/91   | Connectors, Coaxial, Radio Frequency, Series QNC,(Uncabled - Receptacle, Socket Contact, Hermetic Sealed, Jam Nut, Front and Rear Mounted, Class 2) (No S/S Document) | MIL-PRF-39012           | MIL-PRF-39012/91       |
| 893 | M39012/92   | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (CABLED, CLASS 2, WITHOUT CONTACT, .141 SEMIRIGID CABLE)                                           | MIL-PRF-39012           | MIL-PRF-39012/92       |
| 894 | M39012/93   | CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (UNCABLED, FEMALE, PRINTED CIRCUIT, CLASS 2)                                                | MIL-PRF-39012           | MIL-PRF-39012/93       |
| 895 | M39012/94   | CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (UNCABLED, FEMALE, PRINTED CIRCUIT, RIGHT ANGLE, CLASS 2)                                   | MIL-PRF-39012           | MIL-PRF-39012/94       |
| 896 | M39012/95   | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMB (UNCABLED, MALE, PRINTED CIRCUIT, CLASS 2)                                                   | MIL-PRF-39012           | MIL-PRF-39012/95       |
| 897 | M39012/96   | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMB (UNCABLED, MALE, PRINTED CIRCUIT, RIGHT ANGLE, CLASS 2)                                      | MIL-PRF-39012           | MIL-PRF-39012/96       |
| 898 | M39012/100  | Connectors, Plug, Electrical, Coaxial, Radio Frequency, High Voltage (Series MHV (Cabled), Pin Contact, Class 2)                                                      | MIL-PRF-39012           | MIL-PRF-39012/100      |
| 899 | M39012/101  | Connectors, Coaxial, Radio Frequency, (Series MHV (Cabled) - Plug, Socket Contact, Class 2) (No S/S Document)                                                         | MIL-PRF-39012           | MIL-PRF-39012/101      |
| 900 | M39012/102  | Connectors, Coaxial, Radio Frequency, (Series MHV (Cabled) - Receptacles, Socket Contact, Flange Mounted, Class 2) (No S/S Document)                                  | MIL-PRF-39012           | MIL-PRF-39012/102      |
| 901 | M39012/103  | Connectors, Coaxial, Radio Frequency, (Series MHV (Uncabled) Receptacles, Female, Flange Mounted, Class 2) (No S/S Document)                                          | MIL-PRF-39012           | MIL-PRF-39012/103      |
| 902 | M39012/104  | Connectors, Coaxial, Radio Frequency, High Voltage (Series MHV (Uncabled) - Receptacles, Socket Contact, Jam Nut Mounted, Class 2) (No S/S Document)                  | MIL-PRF-39012           | MIL-PRF-39012/104      |
| 903 | M39012/105  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (CABLED) - PLUG, SOCKET CONTACT, CLASS 2) (NO S/S DOCUMENT)                                             | MIL-PRF-39012           | MIL-PRF-39012/105      |

| No. | Part Number | Description                                                                                                                                                          | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 904 | M39012/106  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (CABLED) PLUG, SOCKET CONTACT, RIGHT ANGLE, CLASS 2) (NO S/S DOCUMENT)                                 | MIL-PRF-39012           | MIL-PRF-39012/106      |
| 905 | M39012/107  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (CABLED) - RECEPTACLES, PIN CONTACT, CLASS 2) (NO S/S DOCUMENT)                                        | MIL-PRF-39012           | MIL-PRF-39012/107      |
| 906 | M39012/108  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (CABLED) RECEPTACLES, PIN CONTACT, FLANGE MOUNTED, CLASS 2) (NO S/S DOCUMENT)                          | MIL-PRF-39012           | MIL-PRF-39012/108      |
| 907 | M39012/109  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (UNCABLED) - RECEPTACLES, PIN CONTACT, FLANGE MOUNTED, CLASS 2) (NO S/S DOCUMENT)                      | MIL-PRF-39012           | MIL-PRF-39012/109      |
| 908 | M39012/110  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (UNCABLED) RECEPTACLES, PIN CONTACT, JAM NUT MOUNTED, CLASS 2) (NO S/S DOCUMENT)                       | MIL-PRF-39012           | MIL-PRF-39012/110      |
| 909 | M39012/111  | CONNECTOR, COAXIAL, RADIO FREQUENCY, HIGH VOLTAGE (SERIES SHV (CABLED) - RECEPTACLES, PIN CONTACT, JAM NUT MOUNTED, CLASS 2) (NO S/S DOCUMENT)                       | MIL-PRF-39012           | MIL-PRF-39012/111      |
| 910 | M39012/112  | CONNECTOR, COAXIAL, RADIO FREQUENCY (SERIES TNC (CABLED) - PLUG, PIN CONTACT, CLASS 2) FOR SEMI-RIGID CABLE (NO S/S DOCUMENT)                                        | MIL-PRF-39012           | MIL-PRF-39012/112      |
| 911 | M39012/113  | CONNECTOR, COAXIAL, RADIO FREQUENCY (SERIES INC (CABLED)-PLUG, SOCKET CONTACT, CLASS 2) FOR SEMI-RIGID CABLE (NO S/S DOCUMENT)                                       | MIL-PRF-39012           | MIL-PRF-39012/113      |
| 912 | M39012/114  | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES TNC (CABLED) - PIN CONTACT, RIGHT ANGLE, CLASS 2) FOR SEMI-RIGID CABLE (NO S/S DOCUMENT)              | MIL-PRF-39012           | MIL-PRF-39012/114      |
| 913 | M39012/115  | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES TNC (CABLED) - SOCKET CONTACT, JAM NUT MOUNTED, CLASS 2) FOR SEMI-RIGID CABLE (NO S/S DOCUMENT) | MIL-PRF-39012           | MIL-PRF-39012/115      |
| 914 | M39012/116  | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES TNC (CABLED) - SOCKET CONTACT, FLANGE MOUNTED, CLASS 2) FOR SEMI-RIGID CABLE (NO S/S DOCUMENT)  | MIL-PRF-39012           | MIL-PRF-39012/116      |
| 915 | M39012/117  | CONNECTOR, COAXIAL, RADIO FREQUENCY SERIES N (PLUGS & JACKS, SEMIRIGID CABLE, MALE, CLASS 2) (FOR USE WITH MIL-C-28830/3) (NO S/S DOCUMENT)                          | MIL-PRF-39012           | MIL-PRF-39012/117      |
| 916 | M39012/118  | CONNECTOR PLUG, ELEC, COAXIAL, RADIO FREQUENCY, SER.N (SOCKET CONTACT, SEMIRIGID, CABLE, CLASS 2) USE WITH MIL-C-28830/3) (NO S/S DOCUMENT)                          | MIL-PRF-39012           | MIL-PRF-39012/118      |
| 917 | M39012/119  | CONNECTOR, COAXIAL, RADIO FREQUENCY SERIES N (PLUGS AND JACKS, SEMIRIGID CABLE, MALE, CLASS 2) (FOR USE WITH MIL-C-28830/4) (NO S/S DOCUMENT)                        | MIL-PRF-39012           | MIL-PRF-39012/119      |

| No. | Part Number | Description                                                                                                                                                                 | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 918 | M39012/120  | CONNECTOR, COAXIAL, RADIO FREQUENCY SERIES N (PLUG & JACKS, SEMIRIGID CABLE, FEMALE, CLASS 2) (FOR USE WITH MIL-C-28830/4) (NO S/S DOCUMENT)                                | MIL-PRF-39012           | MIL-PRF-39012/120      |
| 919 | M39012/121  | CONNECTOR, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES N (SOCKET CONTACT, SEMIRIGID CABLE, CLASS 2) (FOR USE WITH MIL-C-28830/5) (NO S/S DOCUMENT)                   | MIL-PRF-39012           | MIL-PRF-39012/121      |
| 920 | M39012/122  | Connector, Receptacle, Electrical, Coaxial, Radio Frequency, Series EIA Flange (Semirigid Cable, Class 2) (For Use with MIL-C-28830/3) (No S/S Document)                    | MIL-PRF-39012           | MIL-PRF-39012/122      |
| 921 | M39012/123  | Connectors, Coaxial, Radio Frequency, Series EIA Flange (Semirigid Cable, Class 2) (For Use with MIL-C-28830/4) (No S/S Document)                                           | MIL-PRF-39012           | MIL-PRF-39012/123      |
| 922 | M39012/124  | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series EIA Flange (Semirigid Cable, Class 2) (For Use with MIL-C-28830/5) (No S/S Document)                   | MIL-PRF-39012           | MIL-PRF-39012/124      |
| 923 | M39012/128  | Connectors, Receptacle, Electrical Coaxial, Radio Frequency (Series BNC, Solder Pocket, Socket Contact Jam Nut Mounted, Isolated, Class 2)                                  | MIL-PRF-39012           | MIL-PRF-39012/128      |
| 924 | M39012/129  | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES N (CABLED) - PIN CONTACT, CLASS 2) FOR SEMIRIGID CABLE (NO S/S DOCUMENT)                                     | MIL-PRF-39012           | MIL-PRF-39012/129      |
| 925 | M39012/130  | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES N (CABLED) - RIGHT ANGLE, PIN CONTACT, CLASS 2) FOR SEMIRIGID CABLE (NO S/S DOCUMENT)                        | MIL-PRF-39012           | MIL-PRF-39012/130      |
| 926 | M39012/131  | CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES N (CABLES) - SOCKET CONTACT, CLASS 2) FOR SEMIRIGID CABLE (S/S BY DSCC DRAWING 89008)                        | MIL-PRF-39012           | MIL-PRF-39012/131      |
| 927 | M39012/132  | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY (SERIES N (CABLED) - JAM NUT MOUNTED, SOCKET CONTACT, CLASS 2) FOR SEMIRIGID CABLE (S/S BY DSCC DRAWING 86106) | MIL-PRF-39012           | MIL-PRF-39012/132      |
| 928 | M39012/133  | CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMC, PRINTED CIRCUIT BOARD MOUNT                                                                       | MIL-PRF-39012           | MIL-PRF-39012/133      |
| 929 | M39012/134  | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SMC, Printed Circuit Board Mount, Right Angle                                                          | MIL-PRF-39012           | MIL-PRF-39012/134      |
| 930 | M39012/135  | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SSMB, Printed Circuit Board Mount, Right Angle                                                         | MIL-PRF-39012           | MIL-PRF-39012/135      |
| 931 | M39012/136  | Connectors, Plug, Electrical, Series SSMA, Pin Contact, for Semirigid Cable, Class 2                                                                                        | MIL-PRF-39012           | MIL-PRF-39012/136      |
| 932 | M39012/137  | Connectors, Plug, Electrical, Series SSMA, Right Angle, Pin Contact, for Semirigid Cable, Class 2                                                                           | MIL-PRF-39012           | MIL-PRF-39012/137      |

| No. | Part Number | Description                                                                                                                                             | Governing Specification | Detailed Specification |
|-----|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 933 | M39012/138  | CONNECTOR, RECEPTACLE, ELECTRICAL, SERIES SSMA, SOCKET CONTACT, FOR SEMIRIGID CABLE                                                                     | MIL-PRF-39012           | MIL-PRF-39012/138      |
| 934 | M39012/139  | Connector, Plug, Electrical, Series SSMA, Pin Contact, for Flexible Cable, Class 2                                                                      | MIL-PRF-39012           | MIL-PRF-39012/139      |
| 935 | M39012/140  | Connector, Plug, Electrical, Series SSMA, Pin Contact, Right Angle, for Flexible Cable, Class 2                                                         | MIL-PRF-39012           | MIL-PRF-39012/140      |
| 936 | M39012/141  | Connectors, Receptacle, Electrical, Coaxial, Radio Frequency, Series SSMB, Printed Circuit Board Mount, Straight                                        | MIL-PRF-39012           | MIL-PRF-39012/141      |
| 937 | M49142/3    | CONNECTOR, PLUG, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY (SERIES TRB, PIN CONTACT, CLASS 2)                                                               | MIL-PRF-49142           | MIL-PRF-49142/3        |
| 938 | M49142/4    | CONNECTORS, RECEPTACLE, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY, UNCABLED, (SERIES TRB, SOCKET CONTACT, JAMNUT MOUNTED, CLASS 2) HERMETIC AND NONHERMETIC | MIL-PRF-49142           | MIL-PRF-49142/4        |
| 939 | M49142/5    | CONNECTOR, RECEPTACLE, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY (SERIES TRB (CABLED), SOCKET CONTACT, JAM NUT MOUNTED, CLASS 2)                            | MIL-PRF-49142           | MIL-PRF-49142/5        |
| 940 | M49142/6    | CONNECTOR, PLUG, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY (SERIES TRB (CABLED), SOCKET CONTACT, CLASS 2)                                                   | MIL-PRF-49142           | MIL-PRF-49142/6        |
| 941 | M49142/7    | CONNECTOR, PLUG, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY (SERIES TRB (CABLED), PIN CONTACT, RIGHT ANGLE, CLASS 2)                                         | MIL-PRF-49142           | MIL-PRF-49142/7        |
| 942 | M49142/8    | Connectors, Triaxial, Radio Frequency (Series TRT (Cabled), Plug, Pin Contact, (Class 2)                                                                | MIL-PRF-49142           | MIL-PRF-49142/8        |
| 943 | M49142/9    | CONNECTOR, TRIAXIAL, RADIO FREQUENCY, (SERIES TRT (CABLED) RECEPTACLE, SOCKET CONTACT, JAMNUT MOUNTED, CLASS 2)                                         | MIL-PRF-49142           | MIL-PRF-49142/9        |
| 944 | M49142/10   | CONNECTORS, RECEPTACLE, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY, UNCABLED (SERIES TRT, SOCKET CONTACT, JAMNUT MOUNTED, CLASS 2) HERMETIC AND NONHERMETIC  | MIL-PRF-49142           | MIL-PRF-49142/10       |
| 945 | M49142/11   | CONNECTORS, TRIAXIAL, RADIO FREQUENCY, (SERIES TRT (CABLED) RECEPTACLE, SOCKET CONTACT, CLASS 2)                                                        | MIL-PRF-49142           | MIL-PRF-49142/11       |
| 946 | M49142/12   | CONNECTORS, PLUG, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY, (SERIES TRT (CABLED), PIN CONTACT, RIGHT ANGLE, CLASS 2)                                       | MIL-PRF-49142           | MIL-PRF-49142/12       |
| 947 | M55339/1    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES BNC JACK TO SERIES N JACK), CLASS 2                                              | MIL-PRF-55339           | MIL-PRF-55339/01       |

| No. | Part Number | Description                                                                                                                                               | Governing Specification | Detailed Specification |
|-----|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 948 | M55339/2    | ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, (SERIES SMA), CLASS 2, RIGHT ANGLE, MALE TO FEMALE                                                         | MIL-PRF-55339           | MIL-PRF-55339/02       |
| 949 | M55339/3    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, RIGHT ANGLE, (WITHIN SERIES N PLUG TO SERIES N JACK), CLASS 2                                               | MIL-PRF-55339           | MIL-PRF-55339/03       |
| 950 | M55339/4    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES N JACK TO SERIES N JACK, (HERMETIC AND NON-HERMETIC)), CLASS 2                               | MIL-PRF-55339           | MIL-PRF-55339/04       |
| 951 | M55339/5    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (WITHIN SERIES N PLUG TO SERIES N PLUG), CLASS 2                                                   | MIL-PRF-55339           | MIL-PRF-55339/05       |
| 952 | M55339/6    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES N), CLASS 2, T PLUG                                                                          | MIL-PRF-55339           | MIL-PRF-55339/06       |
| 953 | M55339/7    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES N), CLASS 2, STRAIGHT PLUG                                                                   | MIL-PRF-55339           | MIL-PRF-55339/07       |
| 954 | M55339/8    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (WITHIN SERIES C JACK TO SERIES C JACK), CLASS 2                                                   | MIL-PRF-55339           | MIL-PRF-55339/08       |
| 955 | M55339/9    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES C), CLASS 2, STRAIGHT PLUG                                                                   | MIL-PRF-55339           | MIL-PRF-55339/09       |
| 956 | M55339/10   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES C), CLASS 2, RIGHT ANGLE PLUG                                                                | MIL-PRF-55339           | MIL-PRF-55339/10       |
| 957 | M55339/11   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES C), CLASS 2, "T" PLUG                                                                        | MIL-PRF-55339           | MIL-PRF-55339/11       |
| 958 | M55339/12   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, JAMNUT MOUNTED, (WITHIN SERIES C JACK TO SERIES C JACK (HERMETIC)), CLASS 2                        | MIL-PRF-55339           | MIL-PRF-55339/12       |
| 959 | M55339/13   | ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, JAMNUT MOUNTED, (WITHIN SERIES BNC JACK TO SERIES BNC JACK, (HERMETIC AND NON-HERMETIC)), CLASS 2 | MIL-PRF-55339           | MIL-PRF-55339/13       |
| 960 | M55339/14   | Adapter, Connector, Coaxial, Radio Frequency, Right Angle (Within Series BNC Jack to Series BNC Plug), Class 2                                            | MIL-PRF-55339           | MIL-PRF-55339/14       |
| 961 | M55339/15   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY (WITHIN SERIES BNC), CLASS 2, STRAIGHT PLUG                                                                  | MIL-PRF-55339           | MIL-PRF-55339/15       |
| 962 | M55339/16   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY. IN-LINE, (WITHIN SERIES BNC JACK TO SERIES BNC JACK), CLASS 2                                               | MIL-PRF-55339           | MIL-PRF-55339/16       |

| No. | Part Number | Description                                                                                                                            | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 963 | M55339/17   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, T , (WITHIN SERIES BNC JACK TO JACK AND SERIES BNC PLUG TO JACK) CLASS 2                 | MIL-PRF-55339           | MIL-PRF-55339/17       |
| 964 | M55339/18   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES BNC PLUG TO SERIES N PLUG), CLASS 2                             | MIL-PRF-55339           | MIL-PRF-55339/18       |
| 965 | M55339/19   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES N JACK TO SERIES C PLUG), CLASS 2                               | MIL-PRF-55339           | MIL-PRF-55339/19       |
| 966 | M55339/20   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES BNC JACK TO SERIES N PLUG), CLASS 2                             | MIL-PRF-55339           | MIL-PRF-55339/20       |
| 967 | M55339/21   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES C JACK TO SERIES N PLUG), CLASS 2                               | MIL-PRF-55339           | MIL-PRF-55339/21       |
| 968 | M55339/22   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES BNC JACK TO SERIES C PLUG), CLASS 2                             | MIL-PRF-55339           | MIL-PRF-55339/22       |
| 969 | M55339/23   | Adapter, Connector, Coaxial, Radio Frequency, In-Line, (Between Series C Jack To Series BNC Plug), Class 2                             | MIL-PRF-55339           | MIL-PRF-55339/23       |
| 970 | M55339/24   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, FLANGE MOUNTED, (WITHIN SERIES BNC PLUG TO SERIES N JACK), CLASS 2                       | MIL-PRF-55339           | MIL-PRF-55339/24       |
| 971 | M55339/25   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, JAMNUT MOUNTED, (BETWEEN SERIES BNC JACK TO SERIES N JACK), CLASS 2             | MIL-PRF-55339           | MIL-PRF-55339/25       |
| 972 | M55339/28   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN LINE, JAMNUT MOUNTED, (WITHIN SERIES SMA PLUG TO SERIES SMA PLUG (HERMETIC)), CLASS 2 | MIL-PRF-55339           | MIL-PRF-55339/28       |
| 973 | M55339/29   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (WITHIN SERIES SMA PLUG TO SMA PLUG), CLASS 2                                   | MIL-PRF-55339           | MIL-PRF-55339/29       |
| 974 | M55339/30   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, "T", (WITHIN SERIES SMA PLUG TO TWO SERIES SMA JACKS), CLASS 2                           | MIL-PRF-55339           | MIL-PRF-55339/30       |
| 975 | M55339/31   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (WITHIN SERIES SMA JACK TO SMA SERIES JACK), CLASS 2                            | MIL-PRF-55339           | MIL-PRF-55339/31       |
| 976 | M55339/32   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES TNC) RIGHT ANGLE, MALE TO FEMALE                                          | MIL-PRF-55339           | MIL-PRF-55339/32       |
| 977 | M55339/33   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES TNC) CLASS 2, STRAIGHT PLUG                                               | MIL-PRF-55339           | MIL-PRF-55339/33       |

| No. | Part Number | Description                                                                                                                | Governing Specification | Detailed Specification |
|-----|-------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 978 | M55339/34   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY. (WITHIN SERIES TNC, (HERMETIC)), CLASS 2, RECEPTACLE                         | MIL-PRF-55339           | MIL-PRF-55339/34       |
| 979 | M55339/35   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES TNC), CLASS 2, "T" PLUG                                       | MIL-PRF-55339           | MIL-PRF-55339/35       |
| 980 | M55339/36   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (WITHIN SERIES TNC), CLASS 2, STRAIGHT PLUG                                  | MIL-PRF-55339           | MIL-PRF-55339/36       |
| 981 | M55339/37   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY (BETWEEN SERIES BNC TO SERIES TNC), CLASS 2, STRAIGHT PLUG                    | MIL-PRF-55339           | MIL-PRF-55339/37       |
| 982 | M55339/38   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY (BETWEEN SERIES BNC TO SERIES TNC), CLASS 2, STRAIGHT PLUG                    | MIL-PRF-55339           | MIL-PRF-55339/38       |
| 983 | M55339/39   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY (BETWEEN SERIES BNC TO SERIES TNC), CLASS 2, STRAIGHT PLUG                    | MIL-PRF-55339           | MIL-PRF-55339/39       |
| 984 | M55339/40   | ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA (MALE) TO SERIES TNC (FEMALE)), CLASS 2, STRAIGHT PLUG  | MIL-PRF-55339           | MIL-PRF-55339/40       |
| 985 | M55339/41   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA (FEMALE) TO SERIES TNC (FEMALE)), CLASS 2, STRAIGHT PLUG | MIL-PRF-55339           | MIL-PRF-55339/41       |
| 986 | M55339/42   | Adapter, Connector, Coaxial, Radio Frequency, (Between Series SMA (Female) to Series TNC (Male)), Class 2, Straight Plug   | MIL-PRF-55339           | MIL-PRF-55339/42       |
| 987 | M55339/43   | ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA (MALE) TO SERIES TNC (MALE)), CLASS 2, STRAIGHT PLUG    | MIL-PRF-55339           | MIL-PRF-55339/43       |
| 988 | M55339/44   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE (BETWEEN SERIES SMA JACK TO SERIES BNC), CLASS 2                     | MIL-PRF-55339           | MIL-PRF-55339/44       |
| 989 | M55339/45   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES SMA PLUG TO SERIES BNC PLUG), CLASS 2               | MIL-PRF-55339           | MIL-PRF-55339/45       |
| 990 | M55339/46   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (BETWEEN SERIES SMA JACK TO SERIES BNC JACK), CLASS 2               | MIL-PRF-55339           | MIL-PRF-55339/46       |
| 991 | M55339/47   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN LINE, (BETWEEN SERIES SMA PLUG TO SERIES BNC JACK), CLASS 2               | MIL-PRF-55339           | MIL-PRF-55339/47       |
| 992 | M55339/48   | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA TO SERIES TNC), CLASS 2, STRAIGHT PLUG                   | MIL-PRF-55339           | MIL-PRF-55339/48       |

| No.  | Part Number  | Description                                                                                                                 | Governing Specification | Detailed Specification |
|------|--------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 993  | M55339/49    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES N JACK TO SERIES BNC PLUG)                                    | MIL-PRF-55339           | MIL-PRF-55339/49       |
| 994  | M55339/50    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY (WITHIN SERIES TNC JACK TO TWO SERIES TNC JACKS), CLASS 2, "T" JAMNUT MOUNT    | MIL-PRF-55339           | MIL-PRF-55339/50       |
| 995  | M55339/51    | ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES TNC TO SERIES N), CLASS 2. STRAIGHT PLUG                      | MIL-PRF-55339           | MIL-PRF-55339/51       |
| 996  | M55339/52    | ADAPTER, CONNECTOR, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA TO N)                                         | MIL-PRF-55339           | MIL-PRF-55339/52       |
| 997  | M55339/53    | ADAPTER, CONNECTOR, ELECTRICAL, COAXIAL, RADIO FREQUENCY, PIN CONTACT (WITHIN SERIES SMA), RIGHT ANGLE                      | MIL-PRF-55339           | MIL-PRF-55339/53       |
| 998  | M55339/54    | ADAPTER, CONNECTOR, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (BETWEEN SERIES SMA TO N)                                         | MIL-PRF-55339           | MIL-PRF-55339/54       |
| 999  | M55339/55    | ADAPTER, CONNECTORS, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA, CONNECTOR SAVER                                      | MIL-PRF-55339           | MIL-PRF-55339/55       |
| 1000 | S-311-P/4-05 | CONNECTORS, ELECTRICAL, RECTANGULAR, SUBMINIATURE, POLARIZED SHELL, DETAILED SPECIFICATION FOR                              | GSFC S-311-P/4          | GSFC S-311-P/4-05      |
| 1001 | S-311-P/4-07 | CONNECTORS, ELECTRICAL, RECTANGULAR, SUBMINIATURE, RACK AND PANEL, DETAILED SPECIFICATION FOR                               | GSFC S-311-P/4          | GSFC S-311-P/4-07      |
| 1002 | S-311-P/4-09 | CONNECTORS, ELECTRICAL, POLARIZED SHELL, RACK AND PANEL, FOR SPACE FLIGHT USE                                               | GSFC S-311-P/4          | GSFC S-311-P/4-09      |
| 1003 | 311P10       | Connectors, Electrical, Rectangular, Miniature, Polarized Shell, Rack and Panel, for Space Flight Use                       | GSFC S-311-P-10         | GSFC S-311-P-10        |
| 1004 | 700-42       | Connectors, Electrical, Rectangular, Polarized Shell, For Space Flight Use, Detail Specification For                        | GSFC S-311-P-718/1      | GSFC S-311-P-718/1     |
| 1005 | 700-42/3     | Connectors, Electrical, Rectangular, Polarized Shell, EMI Shielding (Size 1) For Space Flight Use, Detail Specification For | GSFC S-311-P-718/3      | GSFC S-311-P-718/3     |
| 1006 | 700-42/5     | Connectors, Electrical, Rectangular, Polarized Shell, EMI Shielding (Size 2) For Space Flight Use, Detail Specification For | GSFC S-311-P-718/5      | GSFC S-311-P-718/5     |
| 1007 | 700-42/6     | Connectors, Electrical, Rectangular, Polarized Shell, EMI Shielding (Size 3) For Space Flight Use, Detail Specification For | GSFC S-311-P-718/6      | GSFC S-311-P-718/6     |
| 1008 | NLSO         | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                      | MSFC 40M38277           | MSFC 40M38277          |

| No.  | Part Number | Description                                                                                                                                                                                 | Governing Specification | Detailed Specification |
|------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1009 | NLS3        | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1010 | NLS5        | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1011 | NLS6        | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1012 | NLS6G       | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1013 | NLS6W       | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1014 | NLS7        | Circular Connectors, Low Silhouette, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                      | MSFC 40M38277           | MSFC 40M38277          |
| 1015 | NBS0        | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1016 | NBS3        | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1017 | NBS5        | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1018 | NBS6        | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1019 | NBS6G       | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1020 | NBS6W       | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1021 | NBS7        | Circular Connectors, Miniature, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                           | MSFC 40M38298           | MSFC 40M38298          |
| 1022 | NB0         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1023 | NB3         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1024 | NB4         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1025 | NB5         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1026 | NB6         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1027 | NB6G        | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1028 | NB7         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1029 | NB8         | Circular Connectors, Low Outgassing, Bayonet Coupled, -150°C to +200°C                                                                                                                      | MSFC 40M39569           | MSFC 40M39569          |
| 1030 | M29600/1    | Connector, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Sealing Plug, Size 8 (Series A)                       | SAE-AS29600             | SAE-AS29600/1          |
| 1031 | M29600/2    | Connector, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Backshell, Shield Terminating, (Series A and B)       | SAE-AS29600             | SAE-AS29600/2          |
| 1032 | M29600/3    | Connector, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environmental Resistant, Removable Crimp Contacts, Backshell 90 Degrees, Self Locking (Series A and B) | SAE-AS29600             | SAE-AS29600/3          |

| No.  | Part Number | Description                                                                                                                                                                                | Governing Specification | Detailed Specification |
|------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1033 | M29600/4    | Connector, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environmental Resistant, Removable Crimp Contact, Backshell 45 Degrees, Self Locking (Series A and B) | SAE-AS29600             | SAE-AS29600/4          |
| 1034 | M29600/5    | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Self Locking, Environmental Resistant, Removable Crimp Contacts, Dust Cover (Series A)               | SAE-AS29600             | SAE-AS29600/5          |
| 1035 | M29600/6    | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environmental Resistant, Removable Crimp Contacts, Stowage Receptacle (Series B)                     | SAE-AS29600             | SAE-AS29600/6          |
| 1036 | M29600/7    | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Threaded, Environment Resistant, Removable Crimp Contacts, Nut, Hexagon, Connector Mounting          | SAE-AS29600             | SAE-AS29600/7          |
| 1037 | M29600/10   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Receptacle, Flanged (Series A)                      | SAE-AS29600             | SAE-AS29600/10         |
| 1038 | M29600/11   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Receptacle, Jam Nut (Series A)                      | SAE-AS29600             | SAE-AS29600/11         |
| 1039 | M29600/12   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Plug (Series A)                                     | SAE-AS29600             | SAE-AS29600/12         |
| 1040 | M29600/20   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Receptacle, Flanged (Series B)                      | SAE-AS29600             | SAE-AS29600/20         |
| 1041 | M29600/21   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Receptacle, Jam Nut (Series B)                      | SAE-AS29600             | SAE-AS29600/21         |
| 1042 | M29600/22   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Removable Crimp Contacts, Plug (Series B)                                     | SAE-AS29600             | SAE-AS29600/22         |
| 1043 | M29600/23   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Contacts, Socket, Crimp Removable, (for MIL-C-29600 Series B)                 | SAE-AS29600             | SAE-AS29600/23         |
| 1044 | M29600/24   | Connectors, Electrical, Circular, Miniature, Composite, High Density, Quick Coupling, Environment Resistant, Contacts, Pin, Crimp Removable, (Series B)                                    | SAE-AS29600             | SAE-AS29600/24         |
| 1045 | M81659/9    | Connectors, Electrical, Rectangular, Receptacle Environment Resistant, Crimp Contacts, Double Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 1, Shell Designator A     | SAE-AS81659             | SAE-AS81659/9          |

| No.  | Part Number | Description                                                                                                                                                                             | Governing Specification | Detailed Specification |
|------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1046 | M81659/29   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts (Single Insert, Type II, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                            | SAE-AS81659             | SAE-AS81659/29         |
| 1047 | M81659/31   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Single Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                      | SAE-AS81659             | SAE-AS81659/31         |
| 1048 | M81659/33   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts, (Dual Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                              | SAE-AS81659             | SAE-AS81659/33         |
| 1049 | M81659/35   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Dual Insert, Type II, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                       | SAE-AS81659             | SAE-AS81659/35         |
| 1050 | M81659/37   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts, (Triple Insert, Type II, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                           | SAE-AS81659             | SAE-AS81659/37         |
| 1051 | M81659/39   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Triple Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                      | SAE-AS81659             | SAE-AS81659/39         |
| 1052 | M81659/41   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts, (Quadruple Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                         | SAE-AS81659             | SAE-AS81659/41         |
| 1053 | M81659/43   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Quadruple Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                   | SAE-AS81659             | SAE-AS81659/43         |
| 1054 | M81659/53   | Connectors, Electrical, Rectangular, Plug, Environment Resistant, Crimp Contacts, Triple Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator B       | SAE-AS81659             | SAE-AS81659/53         |
| 1055 | M81659/56   | Connectors, Electrical, Rectangular, Receptacle, Environment Resistant, Crimp Contacts, Triple Insert, Type II, Class 2 (-65 Degrees C to +200 Degrees C), Series 2, Shell Designator B | SAE-AS81659             | SAE-AS81659/56         |
| 1056 | M81659/57   | Connectors, Electrical, Rectangular, Plug Environment Resistant, Crimp Contacts, Quadruple Insert, Type II, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator B     | SAE-AS81659             | SAE-AS81659/57         |
| 1057 | M81659/58   | Connectors, Electrical, Rectangular, Plug, Environment Resistant, Crimp Contacts, Quadruple Insert, Type II, Class 2 (-65 Degrees C to +200 Degrees C), Series 2, Shell Designator B    | SAE-AS81659             | SAE-AS81659/58         |
| 1058 | M81659/61   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Single Insert, Type III, Class 1 (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                     | SAE-AS81659             | SAE-AS81659/61         |
| 1059 | M81659/62   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Dual Insert, Type III, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                      | SAE-AS81659             | SAE-AS81659/62         |

| No.  | Part Number | Description                                                                                                                                                                              | Governing Specification | Detailed Specification |
|------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1060 | M81659/63   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Triple Insert, Type III, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                     | SAE-AS81659             | SAE-AS81659/63         |
| 1061 | M81659/64   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Quadruple Insert, Type III, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                  | SAE-AS81659             | SAE-AS81659/64         |
| 1062 | M81659/65   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts, (Single Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                            | SAE-AS81659             | SAE-AS81659/65         |
| 1063 | M81659/66   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Single Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                      | SAE-AS81659             | SAE-AS81659/66         |
| 1064 | M81659/67   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Single Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A, Clinch Nut Mounting) | SAE-AS81659             | SAE-AS81659/67         |
| 1065 | M81659/68   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Single Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A, Float Mounting)      | SAE-AS81659             | SAE-AS81659/68         |
| 1066 | M81659/69   | Connectors, Electrical, Rectangular, Plug, Crimp Contacts, (Dual Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                              | SAE-AS81659             | SAE-AS81659/69         |
| 1067 | M81659/70   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Dual Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A)                        | SAE-AS81659             | SAE-AS81659/70         |
| 1068 | M81659/71   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Dual Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A, Clinch Nut Mount)      | SAE-AS81659             | SAE-AS81659/71         |
| 1069 | M81659/72   | Connectors, Electrical, Rectangular, Receptacle, Crimp Contacts, (Dual Insert, Type IV, Class 1, (-65 Degrees C to +125 Degrees C), Series 2, Shell Designator A, Float Mounting)        | SAE-AS81659             | SAE-AS81659/72         |
| 1070 | M85028/1    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Jackscrew, Plug, Crimp Removable Pin Contacts, Class E                                                    | SAE-AS85028             | SAE-AS85028/1          |
| 1071 | M85028/2    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Hardware, Receptacle, Crimp Removable Socket Contacts, Class E                                            | SAE-AS85028             | SAE-AS85028/2          |
| 1072 | M85028/3    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Jackscrew, Interfacial Seal, Size 16, Crimp Contacts                                                      | SAE-AS85028             | SAE-AS85028/3          |
| 1073 | M85028/4    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Jackscrew, Sealing Plug, Size 16, Crimp Removable Contacts                                                | SAE-AS85028             | SAE-AS85028/4          |

| No.  | Part Number | Description                                                                                                                                              | Governing Specification | Detailed Specification |
|------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|
| 1074 | M85028/5    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Jackscrew, Wire Seal, Size 16, Crimp Removable Contacts                   | SAE-AS85028             | SAE-AS85028/5          |
| 1075 | M85028/6    | Connector, Electric, Rectangular, Individual Contact Sealing, Polarized Center Jackscrew, Replacement Tool, Wire Seal, Size 16, Crimp Removable Contacts | SAE-AS85028             | SAE-AS85028/6          |
| 1076 | M3607/1     | Connector, Plug, Electrical, Series Pulse, Type UG-34/U                                                                                                  | MIL-C-3607              | M3607/1                |
| 1077 | M3607/2     | Connector, Plug, Electrical, Series Pulse, Type UG-36/U                                                                                                  | MIL-C-3607              | M3607/2                |
| 1078 | M3607/3     | Connector, Receptacle, Electrical, Series Pulse, Type UG-37A/U                                                                                           | MIL-C-3607              | M3607/3                |
| 1079 | M3607/4     | Connector, Receptacle, Electrical Pressurized, Series Pulse, Type UG-38A/U                                                                               | MIL-C-3607              | M3607/4                |
| 1080 | M3607/5     | Connector; Receptacle, Electrical, Pressurized, Series Pulse, Type UG-62 A/U                                                                             | MIL-C-3607              | M3607/5                |
| 1081 | M3607/6     | Connector, Plug, Electrical, Series Pulse, Type UG 174/U                                                                                                 | MIL-C-3607              | M3607/6                |
| 1082 | M3607/7     | Connector, Plug, Electrical, Series Pulse, Type UG-180A/U                                                                                                | MIL-C-3607              | M3607/7                |
| 1083 | M3607/8     | Connector, Receptacle, Electrical, Series Pulse, Type UG-181A/U                                                                                          | MIL-C-3607              | M3607/8                |
| 1084 | M3607/9     | Connector, Receptacle, Electrical, Series Pulse, Type UG-182A/U                                                                                          | MIL-C-3607              | M3607/9                |
| 1085 | M3607/10    | Connector, Adapter, Series Pulse, Type UG-222B/U                                                                                                         | MIL-C-3607              | M3607/10               |
| 1086 | M3607/11    | Connector, Receptacle, Electrical, Series Pulse, Type UG-264/U                                                                                           | MIL-C-3607              | M3607/11               |
| 1087 | M3607/12    | Connector, Adapter, Series Pulse, Type UG-336A/U                                                                                                         | MIL-C-3607              | M3607/12               |
| 1088 | M3607/13    | Connector, Receptacle, Electrical, Series Pulse, Type UG-350/U                                                                                           | MIL-C-3607              | M3607/13               |
| 1089 | M3607/14    | Connector, Adapter, Series, Pulse, Type UG-1110/U                                                                                                        | MIL-C-3607              | M3607/14               |
| 1090 | M3607/15    | Connector, Receptacle, Electrical, Series Pulse, Type UG-1141/U                                                                                          | MIL-C-3607              | M3607/15               |